



Amazon

Exam Questions AWS-Certified-Developer-Associate

Amazon AWS Certified Developer - Associate

NEW QUESTION 1

How long can you keep your Amazon SQS messages in Amazon SQS queues?

- A. From 120 secs up to 4 weeks
- B. From 10 secs up to 7 days
- C. From 60 secs up to 2 weeks
- D. From 30 secs up to 1 week

Answer: C

Explanation:

The SQS message retention period is configurable and can be set anywhere from 1 minute to 2 weeks. The default is 4 days and once the message retention limit is reached your messages will be automatically deleted. The option for longer message retention provides greater flexibility to allow for longer intervals between message production and consumption.

Reference: <https://aws.amazon.com/sqs/faqs/>

NEW QUESTION 2

Which one of the following operations is NOT a DynamoDB operation?

- A. BatchWriteItem
- B. DescribeTable
- C. BatchGetItem
- D. BatchDeleteItem

Answer: D

Explanation:

In DynamoDB, DeleteItem deletes a single item in a table by primary key, but BatchDeleteItem doesn't exist.

Reference: <http://docs.aws.amazon.com/amazondynamodb/latest/developerguide/operationlist.html>

NEW QUESTION 3

Regarding Amazon SNS, when you want to subscribe to a topic and receive notifications to your email, in the Protocol drop-down box, you should select .

- A. Email
- B. Message
- C. SMTP
- D. IMAP

Answer: A

Explanation:

In Amazon SNS, when you want to subscribe to a topic and receive notifications to your email, select Email in the Protocol drop-down box. Enter an email address you can use to receive the notification in the Endpoint field.

Reference: <http://docs.aws.amazon.com/sns/latest/dg/SubscribeTopic.html>

NEW QUESTION 4

In Amazon EC2, which of the following is the type of monitoring data for Amazon EBS volumes that is available automatically in 5-minute periods at no charge?

- A. Primary
- B. Basic
- C. Initial
- D. Detailed

Answer: B

Explanation:

Basic is the type of monitoring data (for Amazon EBS volumes) which is available automatically in 5-minute periods at no charge called.

Reference:

<http://docs.amazonwebservices.com/AWSEC2/latest/UserGuide/monitoring-volume-status.html>

NEW QUESTION 5

In DynamoDB, to get a detailed listing of secondary indexes on a table, you can use the action.

- A. DescribeTable
- B. BatchGetItem
- C. GetItem
- D. TableName

Answer: A

Explanation:

In DynamoDB, DescribeTable returns information about the table, including the current status of the table, when it was created, the primary key schema, and any indexes on the table.

Reference: <http://docs.aws.amazon.com/amazondynamodb/latest/developerguide/SecondaryIndexes.html>

NEW QUESTION 6

A user is planning to create a structured database in the cloud. Which of the below mentioned AWS offerings help the user achieve the goal?

- A. AWS DynamoDB
- B. AWS RDS
- C. AWS SimpleDB
- D. AWS RSD

Answer: B

Explanation:

AWS RDS is a managed database server offered by AWS, which makes it easy to set up, operate, and scale a relational database or structured data in cloud.
Reference: <http://docs.aws.amazon.com/AmazonRDS/latest/UserGuide/Welcome.html>

NEW QUESTION 7

An orgAMzation has launched two applications: one for blogging and one for ECM on the same AWS Linux EC2 instance running in the AWS VPC. The orgAMzation has attached two private IPs (primary and secondary) to the above mentioned instance. The orgAMzation wants the instance OS to recognize the secondary IP address. How can the orgAMzation configure this?

- A. Use the ec2-net-utility package which updates routing tables, uses DHCP to refresh the secondary IP and adds the network interface.
- B. Use the ec2-net-utils package which will configure an additional network interface and update the routing table
- C. Use the ec2-ip-update package which can configure the network interface as well as update the secondary IP with DHCP.
- D. Use the ec2-ip-utility package which can update the routing tables as well as refresh the secondary IP using DHCP.

Answer: B

Explanation:

A Virtual Private Cloud (VPC) is a virtual network dedicated to the user's AWS account. It enables the user to launch AWS resources into a virtual network that the user has defined. With VPC the user can specify multiple private IP addresses for his instances. The number of network interfaces and private IP addresses that a user can specify for an instance depends on the instance type. This scenario helps when the user wants to host multiple websites on a single EC2 instance. After the user has assigned a secondary private IP address to his instance, he needs to configure the operating system on that instance to recognize the secondary private IP address. For AWS Linux, the ec2-net-utils package can take care of this step. It configures additional network interfaces that the user can attach while the instance is running, refreshes secondary IP addresses during DHCP lease renewal, and updates the related routing rules.
Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/MultipleIP.html>

NEW QUESTION 8

You need to develop and run some new applications on AWS and you know that Elastic Beanstalk and CloudFormation can both help as a deployment mechAMsm for a broad range of AWS resources. Which of the following statements best describes the differences between Elastic Beanstalk and C|oudFormation?

- A. Elastic Beanstalk uses Elastic load balancing and CloudFormation doesn't.
- B. CloudFormation is faster in deploying applications than Elastic Beanstalk.
- C. CloudFormation is much more powerful than Elastic Beanstalk, because you can actually design and script custom resources
- D. Elastic Beanstalk is faster in deploying applications than C|oudFormatio

Answer: C

Explanation:

These services are designed to complement each other. AWS Elastic Beanstalk provides an environment to easily develop and run applications in the cloud. It is integrated with developer tools and provides a one-stop experience for you to manage the lifecycle of your applications. AWS CloudFormation is a convenient deployment mechAMsm for a broad range of AWS resources. It supports the infrastructure needs of many different types of applications such as existing enterprise applications, legacy applications, applications built using a variety of AWS resources and container-based solutions (including those built using AWS Elastic Beanstalk).

AWS CloudFormation introduces two new concepts: The template, a JSON-format, text-based file that describes all the AWS resources you need to deploy to run your application and the stack, the set of AWS resources that are created and managed as a single unit when AWS CloudFormation instantiates a template.

Reference: <http://aws.amazon.com/c|oudformation/faqs/>

NEW QUESTION 9

Does AWS CloudFormation support Amazon EC2 tagging?

- A. It depends if the Amazon EC2 tagging has been defined in the template.
- B. No, it doesn't support Amazon EC2 tagging.
- C. No, CloudFormation doesn't support any tagging
- D. Yes, AWS CloudFormation supports Amazon EC2 tagging

Answer: D

Explanation:

In AWS CloudFormation, Amazon EC2 resources that support the tagging feature can also be tagged in an AWS template. The tag values can refer to template parameters, other resource names, resource attribute values (e.g. addresses), or values computed by simple functions (e.g., a concatenated list of strings).

Reference: <http://aws.amazon.com/c|oudformation/faqs/>

NEW QUESTION 10

A user has enabled the automated backup, but not specified the backup window. What will RDS do in this case?

- A. Will throw an error on instance launch
- B. RDS will take 3 AM — 3:30 AM as the default window
- C. RDS assigns a random time period based on the region

D. Will not allow to launch a DB instance

Answer: C

Explanation:

If the user does not specify a preferred backup window while enabling an automated backup, Amazon RDS assigns a default 30-minute backup window which is selected at random from an 8-hour block of time per region. Reference:
<http://docs.aws.amazon.com/AmazonRDS/latest/UserGuide/Overview.BackingUpAndRestoringAmazonRDSInstances.html>

NEW QUESTION 10

A user wants to configure AutoScaling which scales up when the CPU utilization is above 70% and scales down when the CPU utilization is below 30%. How can the user configure AutoScaling for the above mentioned condition?

- A. Use AutoScaling with a schedule
- B. Configure ELB to notify AutoScaling on load increase or decrease
- C. Use dynamic AutoScaling with a policy
- D. Use AutoScaling by manually modifying the desired capacity during a condition

Answer: C

Explanation:

The user can configure the AutoScaling group to automatically scale up and then scale down based on the specified conditions. To configure this, the user must setup policies which will get triggered by the CloudWatch alarms. Reference:
<http://docs.aws.amazon.com/AutoScaling/latest/DeveloperGuide/as-scale-based-on-demand.html>

NEW QUESTION 13

In AWS Elastic Beanstalk, you can update your deployed application even while it is part of a running environment. For a Java application, you can also use to update your deployed application.

- A. the AWS Toolkit for Eclipse
- B. the AWS Toolkit for Visual Studio
- C. the AWS Toolkit for JVM
- D. the AWS Toolkit for Netbeans

Answer: A

Explanation:

In AWS Elastic Beanstalk, you can update your deployed application, even while it is part of a running environment. For a Java application, you can also use the AWS Toolkit for Eclipse to update your deployed application. Reference: <http://docs.aws.amazon.com/elasticbeanstalk/latest/dg/GettingStarted.Walkthrough.html>

NEW QUESTION 14

Can you configure an RDS Read Replica using CloudFormation templates?

- A. Yes, provided that you have root access.
- B. Yes, when you create a new CloudFormation template
- C. Yes, but not for all Regions.
- D. No, you can add the ReadReplica only when the resource is made available by CloudFormation

Answer: B

Explanation:

AWS CloudFormation gives developers and systems administrators an easy way to create and manage collections of AWS resources. You can now set Read Replicas for your databases with RDS when you create a new CloudFormation template. You can start using it with the sample template of CloudFormation. Reference:
https://s3.amazonaws.com/cloudformation-templates-us-east-1/RDS_MySQL_With_Read_Replica.template

NEW QUESTION 19

You have been given a scope to deploy some AWS infrastructure for a large organization. The requirements are that you will have a lot of EC2 instances but may need to add more when the average utilization of your Amazon EC2 fleet is high and conversely remove them when CPU utilization is low. Which AWS services would be best to use to accomplish this?

- A. Amazon CloudFront, Amazon CloudWatch and Elastic Load Balancing.
- B. Auto Scaling, Amazon CloudWatch and AWS CloudTrail.
- C. Auto Scaling, Amazon CloudWatch and Elastic Load Balancing.
- D. Auto Scaling, Amazon CloudWatch and AWS Elastic Beanstalk

Answer: C

Explanation:

Auto Scaling enables you to follow the demand curve for your applications closely, reducing the need to manually provision Amazon EC2 capacity in advance. For example, you can set a condition to add new Amazon EC2 instances in increments to the Auto Scaling group when the average utilization of your Amazon EC2 fleet is high; and similarly, you can set a condition to remove instances in the same increments when CPU utilization is low. If you have predictable load changes, you can set a schedule through Auto Scaling to plan your scaling activities. You can use Amazon CloudWatch to send alarms to trigger scaling activities and Elastic Load Balancing to help distribute traffic to your instances within Auto Scaling groups. Auto Scaling enables you to run your Amazon EC2 fleet at optimal utilization. Reference: <http://aws.amazon.com/autoscaling/>

NEW QUESTION 21

You are building an online store on AWS that uses SQS to process your customer orders. Your backend system needs those messages in the same sequence the customer orders have been put in. How can you achieve that?

- A. You can do this with SQS but you also need to use SWF
- B. Messages will arrive in the same order by default
- C. You can use sequencing information on each message
- D. It is not possible to do this with SQS

Answer: C

Explanation:

Amazon SQS is engineered to always be available and deliver messages. One of the resulting tradeoffs is that SQS does not guarantee first in, first out delivery of messages. For many distributed applications, each message can stand on its own, and as long as all messages are delivered, the order is not important. If your system requires that order be preserved, you can place sequencing information in each message, so that you can reorder the messages when the queue returns them. Reference: <http://docs.aws.amazon.com/AWSSimpleQueueService/latest/SQSDeveloperGuide/Welcome.html>

NEW QUESTION 24

A user is trying to understand AWS SNS. To which of the below mentioned end points is SNS unable to send a notification?

- A. AWS SES
- B. Email JSON
- C. AWS SQS
- D. HTTP

Answer: A

Explanation:

Amazon Simple Notification Service (Amazon SNS) is a fast, flexible, and fully managed push messaging service. Amazon SNS can deliver notifications by SMS text message or email to the Amazon Simple Queue Service (SQS) queues or to any HTTP endpoint. The user can select one the following transports as part of the subscription requests: "HTTP", "HTTPS", "Email", "Email-JSON", "SQS", "and SMS". Reference: <http://aws.amazon.com/sns/faqs/>

NEW QUESTION 29

A user is trying to create a list of IAM users with the AWS console. When the IAM users are created which of the below mentioned credentials will be enabled by default for the user?

- A. IAM access key and secret access key
- B. IAM X.509 certificates
- C. Nothin
- D. Everything is disabled by default
- E. IAM passwords

Answer: C

Explanation:

Newly created IAM users have no password and no access key (access key ID and secret access key). If the user needs to administer your AWS resources using the AWS Management Console, you can create a password for the user. If the user needs to interact with AWS programmatically (using the command line interface (CLI), the AWS SDK, or service-specific APIs), you can create an access key for that user. The credentials you create for users are what they use to uniquely identify themselves to AWS. Reference: http://docs.aws.amazon.com/IAM/latest/UserGuide/Using_WorkingWithGroupsAndUsers.html

NEW QUESTION 30

Bob is an IAM user who has access to the EC2 services. Admin is an IAM user who has access to all the AWS services including IAM. Can Bob change his password?

- A. No, the IAM user can never change the password
- B. Yes, provided Admin has given Bob access to change his password
- C. Yes, only from AWS CLI
- D. Yes, only from the AWS console

Answer: B

Explanation:

The IAM users by default cannot change their password. The root owner or IAM administrator needs to set the policy in the password policy page, which should allow the user to change their password. Once it is enabled, the IAM user can always change their passwords from the AWS console or CLI. Reference: http://docs.aws.amazon.com/IAM/latest/UserGuide/Using_ManagingUserPwdSelf.html

NEW QUESTION 34

An orgAMzation is setting up their website on AWS. The orgAMzation is working on various security measures to be performed on the AWS EC2 instances. Which of the below mentioned security mechAMsms will not help the orgAMzation to avoid future data leaks and identify security weaknesses?

- A. Perform SQL injection for application testing.
- B. Run penetration testing on AWS with prior approval from Amazon.
- C. Perform a hardening test on the AWS instance.
- D. Perform a Code Check for any memory leak

Answer: D

Explanation:

AWS security follows the shared security model where the user is as much responsible as Amazon. Since Amazon is a public cloud it is bound to be targeted by hackers. If an organization is planning to host their application on AWS EC2, they should perform the below mentioned security checks as a measure to find any security weakness/data leaks:

Perform penetration testing as performed by attackers to find any vulnerability. The organization must take an approval from AWS before performing penetration testing

Perform hardening testing to find if there are any unnecessary ports open Perform SQL injection to find any DB security issues

The code memory checks are generally useful when the organization wants to improve the application performance.

Reference: <http://aws.amazon.com/security/penetration-testing/>

NEW QUESTION 35

Which of the below mentioned commands allows the user to share the AMI with his peers using the AWS EC2 CLI?

- A. ec2-share-image-public
- B. ec2-share-image-account
- C. ec2-share-image
- D. ec2-modify-image-attribute

Answer: D

Explanation:

A user can share an AMI with another user / peer using the command: ec2-modify-image-attribute

<AMI-ID> -| -a <AWS Account ID>

Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/sharingamis-explicit.html>

NEW QUESTION 38

In relation to Amazon Simple Workflow Service (Amazon SWF), what is an "Activity Worker"?

- A. An individual task undertaken by a workflow
- B. The automation of a business process
- C. A piece of software that implements tasks
- D. All answers listed are correct

Answer: C

Explanation:

In relation to Amazon Simple Workflow Service (Amazon SWF), an activity worker is a program that receives activity tasks, performs them, and provides results back. Which translates to a piece of software that implements tasks.

Reference: <http://docs.aws.amazon.com/amazonswf/latest/developerguide/swf-dg-develop-act.html>

NEW QUESTION 42

Which Amazon service is not used by Elastic Beanstalk?

- A. Amazon S3
- B. Amazon ELB
- C. Auto scaling
- D. Amazon EMR

Answer: D

Explanation:

Elastic Beanstalk leverages AWS services such as Amazon Elastic Cloud Compute (Amazon EC2), Amazon Simple Storage Service (Amazon S3), Amazon Simple Notification Service (Amazon SNS), Elastic Load Balancing and Auto Scaling to deliver the same highly reliable, scalable, and cost-effective infrastructure that hundreds of thousands of businesses depend on today.

Reference: <http://docs.aws.amazon.com/elasticbeanstalk/latest/dg/welcome.html>

NEW QUESTION 46

Which of the below mentioned options can be a good use case for storing content in AWS RRS?

- A. Storing mission critical data Files
- B. Storing infrequently used log files
- C. Storing a video file which is not reproducible
- D. Storing image thumbnails

Answer: D

Explanation:

AWS RRS provides the same functionality as AWS S3, but at a cheaper rate. It is ideally suited for non-mission, critical applications, such as files which can be reproduced.

Reference: <http://docs.aws.amazon.com/AmazonS3/latest/dev/UsingRRS.html>

NEW QUESTION 50

AWS Elastic Beanstalk will change the health status of a web server environment tier to gray color when:

- A. AWS Elastic Beanstalk detects other problems with the environment that are known to make the application unavailable

- B. Your application hasn't responded to the application health check URL within the last one hour.
- C. Your application hasn't responded to the application health check URL within the last five minutes.
- D. Your application's health status is unknown because status is reported when the application is not in the ready state.

Answer: D

Explanation:

AWS Elastic Beanstalk will change the health status of a web server environment tier to gray color when your application's health status is unknown (because status is reported when the application is not in the ready state).

Reference: <http://docs.aws.amazon.com/elasticbeanstalk/latest/dg/using-features.healthstatus.html>

NEW QUESTION 52

A user wants to access RDS from an EC2 instance using IP addresses. Both RDS and EC2 are in the same region, but different AZs. Which of the below mentioned options help configure that the instance is accessed faster?

- A. Configure the Private IP of the Instance in RDS security group
- B. Security group of EC2 allowed in the RDS security group
- C. Configuring the elastic IP of the instance in RDS security group
- D. Configure the Public IP of the instance in RDS security group

Answer: A

Explanation:

If the user is going to specify an IP range in RDS security group, AWS recommends using the private IP address of the Amazon EC2 instance. This provides a more direct network route from the Amazon EC2 instance to the Amazon RDS DB instance, and does not incur network charges for the data sent outside of the Amazon network.

Reference: http://docs.aws.amazon.com/AmazonRDS/latest/UserGuide/USER_WorkingWithSecurityGroups.html

NEW QUESTION 57

Does Amazon DynamoDB support both increment and decrement atomic operations?

- A. No, neither increment nor decrement operations.
- B. Only increment, since decrement are inherently impossible with DynamoDB's data model.
- C. Only decrement, since increment are inherently impossible with DynamoDB's data model.
- D. Yes, both increment and decrement operation

Answer: D

Explanation:

Amazon DynamoDB supports increment and decrement atomic operations.

Reference: <http://docs.aws.amazon.com/amazondynamodb/latest/developerguide/APISummary.html>

NEW QUESTION 58

ExamKiller (with AWS account ID 111122223333) has created 50 IAM users for its orgAMzation's employees. What will be the AWS console URL for these associates?

- A. [https:// 111122223333.signin.aws.amazon.com/console/](https://111122223333.signin.aws.amazon.com/console/)
- B. [https:// signin.aws.amazon.com/console/](https://signin.aws.amazon.com/console/)
- C. <https://signin.aws.amazon.com/111122223333/console/>
- D. <https://signin.aws.amazon.com/console/111122223333/>

Answer: A

Explanation:

When an orgAMzation is using AWS IAM for creating various users and manage their access rights, the IAM user cannot use the login URL

<http://aws.amazon.com/console> to access AWS management console. The console login URL for the IAM user will have AWS account ID of that orgAMzation to identify the IAM user belongs to particular account. The AWS console login URL for the IAM user will be https://<AWS_Account_ID>.signin.aws.amazon.com/console/. In this case it will be [https:// 111122223333.signin.aws.amazon.com/console/](https://111122223333.signin.aws.amazon.com/console/)

Reference: <http://docs.aws.amazon.com/IAM/latest/UserGuide/AccountAlias.html>

NEW QUESTION 59

A user is setting up an Elastic Load Balancer(ELB). Which of the below parameters should the user consider so as the instance gets registered with the ELB?

- A. ELB DNS
- B. IP address
- C. Security group
- D. ELB IP

Answer: B

Explanation:

The EC2 instances are registered with the load balancer using the IP addresses associated with the instances. When an instance is stopped and then started, the IP address associated with the instance changes. This prevents the load balancer from routing traffic to the restarted instance. When the user stops and then starts registered EC2 instances, it is recommended that to de-register the stopped instance from load balancer, and then register the restarted instance. Failure to do so may prevent the load balancer from performing health checks and routing the traffic to the restarted instance.

NEW QUESTION 62

When you use the AWS Elastic Beanstalk console to deploy a new application .

- A. you'll need to upload each file separately
- B. you'll need to create each file and path
- C. you'll need to upload a source bundle
- D. you'll need to create each file

Answer: C

Explanation:

When you use the AWS Elastic Beanstalk console to deploy a new application or an application version, you'll need to upload a source bundle.

Reference:

<http://docs.aws.amazon.com/elasticbeanstalk/latest/dg/using-features.deployment.source.html>

NEW QUESTION 67

A user has created a snapshot of an EBS volume. Which of the below mentioned usage cases is not possible with respect to a snapshot?

- A. Mirroring the volume from one AZ to another AZ
- B. Launch an instance
- C. Decrease the volume size
- D. Increase the size of the volume

Answer: C

Explanation:

The EBS snapshots are a point in time backup of the volume. It is helpful to move the volume from one AZ to another or launch a new instance. The user can increase the size of the volume but cannot decrease it less than the original snapshot size.

Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/EBSSnapshots.html>

NEW QUESTION 71

A user is creating an EBS volume. He asks for your advice. Which advice mentioned below should you not give to the user for creating an EBS volume?

- A. Take the snapshot of the volume when the instance is stopped
- B. Stripe multiple volumes attached to the same instance
- C. Create an AMI from the attached volume
- D. Attach multiple volumes to the same instance

Answer: C

Explanation:

When a user creates an EBS volume, the user can attach it to a running instance. The user can attach multiple volumes to the same instance and stripe them together to increase the I/O. The user can take a snapshot from the existing volume but cannot create an AMI from the volume. However, the user can create an AMI from a snapshot.

Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/EBSVolumes.html>

NEW QUESTION 73

Which of the following device names is reserved for the root device for Linux instances of Amazon EC2?

- A. /dev/sda1
- B. /dev/sd[b-e]
- C. xvd[a-e]
- D. /dev/sd[f-p][1 -6]

Answer: A

Explanation:

/dev/sda1 is the name of the device reserved for the root device for Linux instances. Reference:

http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/device_naming.html

NEW QUESTION 76

Your supervisor has asked you to build a simple file synchronization service for your department. He doesn't want to spend too much money and he wants to be notified of any changes to files by email. What do you think would be the best Amazon service to use for the email solution?

- A. Amazon CloudSearch
- B. Amazon Elastic Transcoder
- C. Amazon SES
- D. Amazon AppStream

Answer: C

Explanation:

File change notifications can be sent via email to users following the resource with Amazon Simple Email Service (Amazon SES), an easy-to-use, cost-effective email solution.

Reference: http://media.amazonwebservices.com/architecturecenter/AWS_ac_ra_filesync_08.pdf

NEW QUESTION 81

ExamKiller has three AWS accounts. They have created separate IAM users within each account. ExamKiller wants a single IAM console URL such as

<https://examkiller.signin.aws.amazon.com/console/> for all account users. How can this be achieved?

- A. Merge all the accounts with consolidated billing
- B. Create the same account alias with each account ID
- C. It is not possible to have the same IAM account login URL for separate AWS accounts
- D. Create the S3 bucket with an alias name and use the redirect rule to forward requests to various accounts

Answer: C

Explanation:

If a user wants the URL of the AWS IAM sign-in page to have a company name instead of the AWS account ID, he can create an alias for his AWS account ID. The alias should be unique.

Reference: <http://docs.aws.amazon.com/IAM/latest/UserGuide/AccountAlias.html>

NEW QUESTION 84

A user has enabled automated backup for an RDS instance. What is the longest duration for which the user can retain the automated backup?

- A. 25 days
- B. 15 days
- C. 45 days
- D. 35 days

Answer: D

Explanation:

Amazon RDS provides two different methods for backing up and restoring the Amazon DB instances: automated backups and DB snapshots. Automated backups automatically back up the DB instance during a specific, user-definable backup window, and keep the backups for a limited, user-specified period of time. The maximum period can be 35 days.

Reference: <http://docs.aws.amazon.com/AmazonRDS/latest/UserGuide/Overview.BackingUpAndRestoringAmazonRDSInstances.html>

NEW QUESTION 87

A user is uploading archives to Glacier. The user is trying to understand key Glacier resources. Which of the below mentioned options is not a Glacier resource?

- A. Notification configuration
- B. Archive ID
- C. Job
- D. Archive

Answer: B

Explanation:

AWS Glacier has four resources. Vault and Archives are core data model concepts. Job is required to initiate download of archive. The notification configuration is required to send user notification when archive is available for download.

Reference: <http://docs.aws.amazon.com/amazonglacier/latest/dev/amazon-glacier-data-model.html>

NEW QUESTION 91

An organization has 10 departments. The organization wants to track the AWS usage of each department. Which of the below mentioned options meets the requirement?

- A. Setup IAM groups for each department and track their usage
- B. Create separate accounts for each department, but use consolidated billing for payment and tracking
- C. Create separate accounts for each department and track them separately
- D. Setup IAM users for each department and track their usage

Answer: B

Explanation:

The cost of an IAM user or groups can never be tracked separately for the purpose of billing. The best solution in this case is to create a separate account for each department and use consolidated billing. Reference: http://docs.aws.amazon.com/IAM/latest/UserGuide/IAM_Introduction.html

NEW QUESTION 95

An EC2 instance has one additional EBS volume attached to it. How can a user attach the same volume to another running instance in the same AZ?

- A. Terminate the first instance and only then attach to the new instance
- B. Attach the volume as read only to the second instance
- C. Detach the volume first and attach to new instance
- D. No need to detach
- E. Just select the volume and attach it to the new instance, it will take care of mapping internally

Answer: C

Explanation:

If an EBS volume is attached to a running EC2 instance, the user needs to detach the volume from the original instance and then attach it to a new running instance. The user doesn't need to stop / terminate the original instance.

Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/ebs-detaching-volume.html>

NEW QUESTION 96

A root AWS account owner has created three IAM users: Bob, John and Michael. Michael is the IAM administrator. Bob and John are not the superpower users, but users with some pre-defined policies. John does not have access to modify his password. Thus, he asks Bob to change his password. How can Bob change John's password?

- A. This statement is fals
- B. It should be Michael who changes the password for John
- C. It is not possible that John cannot modify his password
- D. Provided Bob is the manager of John
- E. Provided Michael has added Bob to a group, which has permissions to modify the IAM passwords

Answer: D

Explanation:

Generally with IAM users, the password can be modified in two ways. The first option is to define the IAM level policy which allows each user to modify their own passwords. The other option is to create a group and create a policy for the group which can change the passwords of various IAM users.

Reference: <http://docs.aws.amazon.com/IAM/latest/UserGuide/HowToPwdlAMUser.html>

NEW QUESTION 100

Does DynamoDB support in-place atomic updates?

- A. It is not defined
- B. Yes
- C. It does support in-place non-atomic updates
- D. No

Answer: B

Explanation:

DynamoDB supports in-place atomic updates. Reference:

<http://docs.aws.amazon.com/amazondynamodb/latest/developerguide/WorkingWithItems.html#WorkingWithItems.AtomicCounters>

NEW QUESTION 103

You have an environment that consists of a public subnet using Amazon VPC and 3 instances that are running in this subnet. These three instances can successfully communicate with other hosts on the Internet. You launch a fourth instance in the same subnet, using the same AMI and security group configuration you used for the others, but find that this instance cannot be accessed from the Internet. What should you do to enable internet access?

- A. Deploy a NAT instance into the public subnet.
- B. Modify the routing table for the public subnet
- C. Configure a publically routable IP Address In the host OS of the fourth instance.
- D. Assign an Elastic IP address to the fourth instanc

Answer: D

NEW QUESTION 108

Which of the following statements about SWF are true? Choose 3 answers

- A. SWF tasks are assigned once and never duplicated
- B. SWF requires an S3 bucket for workflow storage
- C. SWF workflow executions can last up to a year
- D. SWF triggers SNS notifications on task assignment
- E. SWF uses deciders and workers to complete tasks
- F. SWF requires atleast 1 EC2 instance per domain

Answer: ACE

NEW QUESTION 110

A startup s photo-sharing site is deployed in a VPC. An ELB distributes web traffic across two subnets. ELB session stickiness is configured to use the AWS-generated session cookie, with a session TTL of 5 minutes. The webserver Auto Scaling Group is configured as: min-size=4, max-size=4.

The startups preparing for a public launch, by running load-testing software installed on a single EC2 instance running in us-west-2a. After 60 minutes of load-testing, the webserver logs show:

WEBSERVER LOGS	# of HTTP requests from load-tester	# of HTTP requests from private beta users
webserver #1 (subnet in us-west-2a):	19,210	434
webserver #2 (subnet in us-west-2a):	21,790	490
webserver #3 (subnet in us-west-2b):	0	410
webserver #4 (subnet in us-west-2b):	0	428

Which recommendations can help ensure load-testing HTTP requests are evenly distributed across the four webserver? Choose 2 answers

- A. Launch and run the load-tester EC2 instance from us-east-1 instead.
- B. Re-configure the load-testing software to re-resolve DNS for each web request.
- C. Use a 3rd-party load-testing service which offers globally-distributed test clients.
- D. Configure ELB and Auto Scaling to distribute across us-west-2a and us-west-2c.
- E. Configure ELB session stickiness to use the app-specific session cooki

Answer: BE

NEW QUESTION 115

Company C is currently hosting their corporate site in an Amazon S3 bucket with Static Website Hosting enabled. Currently, when visitors go to <http://www.companyc.com> the index.html page is returned. Company C now would like a new page welcome.html to be returned when a visitor enters <http://www.companyc.com> in the browser.

Which of the following steps will allow Company C to meet this requirement? Choose 2 answers

- A. Upload an html page named welcome.html to their S3 bucket
- B. Create a welcome subfolder in their S3 bucket
- C. Set the Index Document property to welcome.html
- D. Move the index.html page to a welcome subfolder
- E. Set the Error Document property to welcome.html

Answer: AC

NEW QUESTION 118

What AWS products and features can be deployed by Elastic Beanstalk? Choose 3 answers

- A. Auto scaling groups
- B. Route 53 hosted zones
- C. Elastic Load Balancers
- D. RDS Instances
- E. Elastic IP addresses
- F. SQS Queues

Answer: ACD

NEW QUESTION 123

Which code snippet below returns the URL of a load balanced web site created in CloudFormation with an AWS::ElasticLoadBalancing::LoadBalancer resource name "ElasticLoad Balancer"?

- A. `"Fn::Join" : ["http://", {"Fn::GetAtr" : ["ElasticLoadBalancer","DNSName"]}]]`
- B. `"Fn::Join" : ["http://", {"Fn::GetAtr" : ["ElasticLoadBalancer","Url"]}]]`
- C. `"Fn::Join" : ["http://", {"Ref" : "ElasticLoadBalancerUrl"}]]`
- D. `"Fn::Join" : ["http://", {"Ref" : "ElasticLoadBalancerDNSName"}]]`

Answer: B

NEW QUESTION 127

Your application is trying to upload a 6 GB file to Simple Storage Service and receive a "Your proposed upload exceeds the maximum allowed object size." error message.

What is a possible solution for this?

- A. None, Simple Storage Service objects are limited to 5 GB
- B. Use the multi-part upload API for this object
- C. Use the large object upload API for this object
- D. Contact support to increase your object size limit
- E. Upload to a different region

Answer: B

NEW QUESTION 129

A corporate web application is deployed within an Amazon VPC, and is connected to the corporate data center via IPSec VPN. The application must authenticate against the on-premise LDAP server. Once authenticated, logged-in users can only access an S3 keyspace specific to the user.

Which two approaches can satisfy the objectives? Choose 2 answers

- A. The application authenticates against LDA
- B. The application then calls the IAM Security Service to login to IAM using the LDAP credential
- C. The application can use the IAM temporary credentials to access the appropriate S3 bucket.
- D. The application authenticates against LDAP, and retrieves the name of an IAM role associated with the use
- E. The application then calls the IAM Security Token Service to assume that IAM Rol
- F. The application can use the temporary credentials to access the appropriate S3 bucket.
- G. The application authenticates against IAM Security Token Service using the LDAP credential
- H. The application uses those temporary AWS security credentials to access the appropriate S3 bucket.
- I. Develop an identity broker which authenticates against LDAP, and then calls IAM Security Token Service to get IAM federated user credential
- J. The application calls the identity broker to get IAM federated user credentials with access to the appropriate S3 bucket.
- K. Develop an identity broker which authenticates against IAM Security Token Service to assume an IAM Role to get temporary AWS security credential
- L. The application calls the identity broker to get AWS temporary security credentials with access to the appropriate S3 bucket.

Answer: BD

NEW QUESTION 134

You are writing to a DynamoDB table and receive the following exception: "ProvisionedThroughputExceededException". though according to your Cloudwatch metrics for the table, you are not exceeding your provisioned throughput.

What could be an explanation for this?

- A. You haven't provisioned enough DynamoDB storage instances
- B. You're exceeding your capacity on a particular Range Key
- C. You're exceeding your capacity on a particular Hash Key

- D. You're exceeding your capacity on a particular Sort Key
- E. You haven't configured DynamoDB Auto Scaling triggers

Answer: C

NEW QUESTION 139

You run an ad-supported photo sharing website using S3 to serve photos to visitors of your site. At some point you find out that other sites have been linking to the photos on your site, causing loss to your business. What is an effective method to mitigate this?

- A. Store photos on an EBS volume of the web server
- B. Remove public read access and use signed URLs with expiry dates.
- C. Use CloudFront distributions for static content.
- D. Block the IPs of the offending websites in Security Group

Answer: B

NEW QUESTION 141

Games-R-Us is launching a new game app for mobile devices. Users will log into the game using their existing Facebook account and the game will record player data and scoring information directly to a DynamoDB table.

What is the most secure approach for signing requests to the DynamoDB API?

- A. Create an IAM user with access credentials that are distributed with the mobile app to sign the requests
- B. Distribute the AWS root account access credentials with the mobile app to sign the requests
- C. Request temporary security credentials using web identity federation to sign the requests
- D. Establish cross account access between the mobile app and the DynamoDB table to sign the requests

Answer: C

NEW QUESTION 142

.....

Thank You for Trying Our Product

We offer two products:

1st - We have Practice Tests Software with Actual Exam Questions

2nd - Questions and Answers in PDF Format

AWS-Certified-Developer-Associate Practice Exam Features:

- * AWS-Certified-Developer-Associate Questions and Answers Updated Frequently
- * AWS-Certified-Developer-Associate Practice Questions Verified by Expert Senior Certified Staff
- * AWS-Certified-Developer-Associate Most Realistic Questions that Guarantee you a Pass on Your FirstTry
- * AWS-Certified-Developer-Associate Practice Test Questions in Multiple Choice Formats and Updatesfor 1 Year

100% Actual & Verified — Instant Download, Please Click
[Order The AWS-Certified-Developer-Associate Practice Test Here](#)