

1z0-808 Dumps

Java SE 8 Programmer I

<https://www.certleader.com/1z0-808-dumps.html>



NEW QUESTION 1

Given the code fragment:

```
public static void main(String[] args) {  
    int ans;  
    try {  
        int num = 10;  
        int div = 0;  
        ans = num / div;  
    } catch (ArithmeticException ae) {  
        ans = 0; // line n1  
    } catch (Exception e) {  
        System.out.println("Invalid calculation");  
    }  
    System.out.println("Answer = " + ans); // line n2  
}
```

What is the result?

- A. Answer = 0
- B. Invalid calculation
- C. Compilation fails only at line n1.
- D. Compilation fails only at line n2.
- E. Compilation fails at line n1 and line2.

Answer: C**Explanation:**

```
1  
2 public class Test {  
3     public static void main(String[] args) {  
4         int ans;  
5         try {  
6             int num = 10;  
7             int div = 0;  
8             ans = num / div;  
9         } catch (ArithmeticException ae) {  
10            ans = 0;  
11        } catch (Exception e) {  
12            System.out.println("Invalid calculation");  
13            variable ans might not have been initialized  
14        System.out.println("Answer = " + ans); //line n2  
15        }  
16    }  
17 }
```

NEW QUESTION 2

Given the code fragments:

Person.java:

```
public class Person {
    String name;
    int age;

    public Person(String n, int a) {
        name = n;
        age = a;
    }

    public String getName() {
        return name;
    }

    public int getAge() {
        return age;
    }
}
```

Test.java:

```
public static void checkAge(List<Person> list, Predicate<Person> predicate) {
    for (Person p : list) {
        if (predicate.test(p)) {
            System.out.println(p.name + " ");
        }
    }
}

public static void main(String[] args) {
    List<Person> iList = Arrays.asList(new Person("Hank", 45),
                                       new Person("Charlie", 40),
                                       new Person("Smith", 38));

    //line n1
}
```

Which code fragment, when inserted at line n1, enables the code to print Hank?

- A**
- ```
checkAge (iList, () -> p. get Age () > 40);
```
- B**
- ```
checkAge(iList, Person p -> p.getAge( ) > 40);
```
- C**
- ```
checkAge (iList, p -> p.getAge () > 40);
```
- D**
- ```
checkAge(iList, (Person p) -> { p.getAge() > 40; });
```

- A. Option A
B. Option B
C. Option C
D. Option D

Answer: C

NEW QUESTION 3

You are asked to develop a program for a shopping application, and you are given this information:

- The application must contain the classes Toy, EduToy, and ConsToy. The Toy class is the superclass of the other two classes.
- The int calculatePrice (Toy t) method calculates the price of a toy.
- The void printToy (Toy t) method prints the details of a toy.

Which definition of the Toy class adds a valid layer of abstraction to the class hierarchy?

- A
- ```
public abstract class Toy{
 public abstract int calculatePrice(Toy t);
 public void printToy(Toy t) { /* code goes here */ }
}
```
- B
- ```
public abstract class Toy {
    public int calculatePrice(Toy t) ;
    public void printToy(Toy t) ;
}
```
- C
- ```
public abstract class Toy {
 public int calculatePrice(Toy t);
 public final void printToy(Toy t){ /* code goes here */ }
}
```
- D
- ```
public abstract class Toy {
    public abstract int calculatePrice(Toy t) { /* code goes here */ }
    public abstract void printToy(Toy t) { /* code goes here */ }
}
```

- A. Option A
B. Option B
C. Option C
D. Option D

Answer: A

NEW QUESTION 4

Given:

```
public class Test {
    public static void main(String[] args) {
        int x = 1;
        int y = 0;
        if(x++ > ++y) {
            System.out.print("Hello ");
        } else {
            System.out.print("Welcome ");
        }
        System.out.print("Log " + x + ":" + y);
    }
}
```

What is the result?

- A. Hello Log 1:0
B. Hello Log 2:1
C. Welcome Log 2:1
D. Welcome Log 1:0

Answer: C

NEW QUESTION 5

Given the definitions of the MyString class and the Test class:

```
package p1;
class MyString {
    String msg;
    MyString(String msg) {
        this.msg = msg;
    }
}
```

Test.java:

```
package p1;
public class Test {
    public static void main(String[] args) {
        System.out.println("Hello " + new StringBuilder("Java SE 8"));
        System.out.println("Hello " + new MyString("Java SE 8").msg);
    }
}
```

What is the result?

- A**
- ```
Hello Java SE 8
Hello Java SE 8
```
- B**
- ```
Hello java.lang.StringBuilder@<<hashCode1>>
Hello p1.MyString@<<hashCode2>>
```
- C**
- ```
Hello Java SE 8
Hello p1.MyString@<<hashCode>>
```
- D** Compilation fails at the Test class

- A. Option A  
B. Option B  
C. Option C  
D. Option D  
E. Option E

**Answer: D**

#### NEW QUESTION 6

Given the code fragment:

```
int x = 100;
int a = x++;
int b = ++x;
int c = x++;
int d = (a < b) ? (a < c) ? a : (b < c) ? b : c : x;
System.out.println(d);
```

What is the result?

- A. 100  
B. 101  
C. 102  
D. 103  
E. Compilation fails

**Answer: E**

#### NEW QUESTION 7

Given this code for a Planet object:



```
public class Planet {
 public String name;
 public int moons;

 public Planet(String name, int moons) {
 this.name = name;
 this.moons = moons;
 }
}
```

And this method:

```
public static void main(String[] args){
 Planet[] planets = {
 new Planet("Mercury", 0),
 new Planet("Venus", 0),
 new Planet("Earth", 1),
 new Planet("Mars", 2)
 };

 System.out.println(planets);
 System.out.println(planets[2].name);
 System.out.println(planets[2].moons);
}
```

What is the output?

- A
- ```
planets  
Earth  
1
```
- B
- ```
[LPlanets.Planet;@15db9742
Earth
1
```
- C
- ```
[LPlanets.Planet;@15db9742  
Planets.Planet@6d06d69c  
1
```
- D
- ```
[LPlanets.Planet;@15db9742
Planets.Planet@6d06d69c
[LPlanets.Moon;@7852e922
```
- E
- ```
[LPlanets.Planet;@15db9742  
Venus  
0
```

- A. Option A
B. Option B
C. Option C
D. Option D
E. Option E

Answer: C

NEW QUESTION 8

Given the code fragment:

```
public static void main(String[] args) {  
    short s1 = 200;  
    Integer s2 = 400;  
    Long s3 = (long) s1 + s2;           //line n1  
    String s4 = (String) (s3 * s2);    //line n2  
    System.out.println("Sum is " + s4);  
}
```

What is the result?

- A. Sum is 600
- B. Compilation fails at line n1.
- C. Compilation fails at line n2.
- D. A ClassCastException is thrown at line n1.
- E. A ClassCastException is thrown at line n2.

Answer: C

NEW QUESTION 9

Given the code fragment:

```
public static void main(String[] args) {  
    int data[] = {2010, 2013, 2014, 2015, 2014};  
    int key = 2014;  
    int count = 0;  
    for (int e: data) {  
        if (e != key) {  
            continue;  
            count++;  
        }  
    }  
    System.out.print(count + " Found");  
}
```

What is the result?

- A. Compilation fails.
- B. 0 Found
- C. 1 Found
- D. 3 Found

Answer: A

NEW QUESTION 10

Given:

```
public class App {  
    int count;  
    public static void displayMsg () {  
        count++;                               // line n1  
        System.out.println ("Welcome "+"Visit Count: "+count); // line n2  
    }  
    public static void main (String [] args) {  
        App.displayMsg ();                     // line n3  
        App.displayMsg ();                     // line n4  
    }  
}
```

What is the result?

- A. Compilation fails at line n3 and line n4.
- B. Compilation fails at line n1 and line n2.
- C. Welcome Visit Count:1Welcome Visit Count: 1
- D. Welcome Visit Count:1Welcome Visit Count: 2

Answer: B

NEW QUESTION 10

Which two are benefits of polymorphism? (Choose two.)

- A. Faster code at runtime
- B. More efficient code at runtime
- C. More dynamic code at runtime
- D. More flexible and reusable code
- E. Code that is protected from extension by other classes

Answer: BD

NEW QUESTION 14

Given:


```
public class Test {
    public static void main(String[] args) {
        Test ts = new Test();
        System.out.print(isAvailable + " ");
        isAvailable= ts.doStuff();
        System.out.println(isAvailable);
    }
    public static boolean doStuff() {
        return !isAvailable;
    }
    static boolean isAvailable = true;
}
```

What is the result?

- A. Compilation fails.
- B. false true
- C. true false
- D. true true
- E. false false

Answer: C

Explanation:



NEW QUESTION 15

Given:

```
public class App {
    int count;
    public static void displayMsg() {
        System.out.println("Welcome Visit Count: " + count++); // line n1
    }
    public static void main(String[] args) {
        App.displayMsg();
        displayMsg(); // line n2
    }
}
```

What is the result?

- A. Welcome Visit Count:0Welcome Visit Count: 1
- B. Compilation fails at line n2.
- C. Compilation fails at line n1.
- D. Welcome Visit Count:0Welcome Visit Count: 0

Answer: C

Explanation:



NEW QUESTION 18

Which two statements are true about Java byte code? (Choose two.)

- A. It can be serialized across network.

- B. It can run on any platform that has a Java compiler.
- C. It can run on any platform.
- D. It has “.java” extension.
- E. It can run on any platform that has the Java Runtime Environment.

Answer: AE

NEW QUESTION 20

This grid shows the state of a 2D array:

0	0	
	X	0
X		X

The grid is created with this code:

```
char[][] grid = new char[3][3];  
grid[1][1] = 'X';  
grid[0][0] = '0';  
grid[2][0] = 'X';  
grid[0][1] = '0';  
grid[2][2] = 'X';  
grid[1][2] = '0';  
//line n1
```

Which line of code, when inserted in place of //line n1, adds an X into the grid so that the grid contains three consecutive Xs?

- A. grid[2][1] = 'X';
- B. grid[3][2] = 'X';
- C. grid[3][1] = 'X';
- D. grid[2][3] = 'X';

Answer: D

NEW QUESTION 21

Given:

```
public class Fieldinit {  
    char c;  
    boolean b;  
    float f;  
    void printAll() {  
        System.out.println ("c = " + c);  
        System.out.println ("b = " + b);  
        System.out.println ("f = " + f);  
    }  
    public static void main (String [] args) {  
        FieldInit f = new FieldInit ();  
        f.printAll ();  
    }  
}
```

What is the result?

A

```
c=  
b = false  
f = 0.0
```

B

```
c= null  
b = true  
f = 0.0
```

C

```
c=0  
b = false  
f = 0.0f
```

D

```
c= null  
b = false  
f = 0.0F
```

- A. Option A
- B. Option B
- C. Option C
- D. Option D

Answer: A**NEW QUESTION 25**

Given:

```
public class Test {  
    public static void main(String[] args) {  
        boolean a = new Boolean(Boolean.valueOf(args[0]));  
        boolean b = new Boolean(args[1]);  
        System.out.println(a + " " + b);  
    }  
}
```

And given the commands:

```
javac Test.java  
java Test 1 null
```

What is the result?

- A. 1 null
- B. true false
- C. false false
- D. true true
- E. A ClassCastException is thrown at runtime.

Answer: D**NEW QUESTION 26**

Given the code fragment:

```
public class Employee {
    String name;
    boolean contract;
    double salary;
    Employee() {
        // line n1
    }
    public String toString(){
        return name + ":" + contract + ":" + salary;
    }
    public static void main(String[] args) {
        Employee e = new Employee();
        // line n2
        System.out.print(e);
    }
}
```

Which two modifications, when made independently, enable the code to print Joe:true: 100.0? (Choose two.)

- ☐ A) Replace line n2 with:
e.name = "Joe";
e.contract = true;
e.salary = 100;
- ☐ B) Replace line n2 with:
this.name = "Joe";
this.contract = true;
this.salary = 100;
- ☐ C) Replace line n1 with:
this.name = new String("Joe");
this.contract = new Boolean(true);
this.salary = new Double(100);
- ☐ D) Replace line n1 with:
name = "Joe";
contract = TRUE;
salary = 100.0f;
- ☐ E) Replace line n1 with:
this("Joe", true, 100);

- A. Option A
- B. Option B
- C. Option C
- D. Option D
- E. Option E

Answer: AC

NEW QUESTION 31

Given:

```
interface Readable {
    public void readBook();
    public void setBookMark();
}

abstract class Book implements Readable { // line n1
    public void readBook() { }
    // line n2
}

class EBook extends Book { // line n3
    public void readBook() { }
    // line n4
}
```

And given the code fragment: Book book1 = new EBook(); book1.readBook();
Which option enables the code to compile?

- ☐ A) Replace the code fragment at line n1 with:
class Book implements Readable {
- ☐ B) At line n2 insert:
public abstract void setBookMark();
- ☐ C) Replace the code fragment at line n3 with:
abstract class EBook extends Book {
- ☐ D) At line n4 insert:
public void setBookMark() { }

A. Option A
B. Option B
C. Option C
D. Option D

Answer: D

NEW QUESTION 34

Given:

```
class Product {  
    double price;  
}  
  
public class Test {  
    public void updatePrice(Product product, double price) {  
        price = price * 2;  
        product.price = product.price + price;  
    }  
    public static void main(String[] args) {  
        Product prt = new Product();  
        prt.price = 200;  
        double newPrice = 100;  
  
        Test t = new Test();  
        t.updatePrice(prt, newPrice);  
        System.out.println(prt.price + " : " + newPrice);  
    }  
}
```

What is the result?

- A. 200.0 : 100.0
B. 400.0 : 200.0
C. 400.0 : 100.0
D. Compilation fails.

Answer: C

NEW QUESTION 38

Given:

```
class X {  
    static int i;  
    int j;  
    public static void main(String[] args) {  
        X x1 = new X();  
        X x2 = new X();  
        x1.i = 3;  
        x1.j = 4;  
        x2.i = 5;  
        x2.j = 6;  
        System.out.println(  
            x1.i + " " +  
            x1.j + " " +  
            x2.i + " " +  
            x2.j);  
    }  
}
```

What is the result?

- A. 3 4 5 6
- B. 3 4 3 6
- C. 5 4 5 6
- D. 3 6 4 6

Answer: C

NEW QUESTION 42

Which three statements are true about exception handling? (Choose three.)

- A. Only unchecked exceptions can be rethrown.
- B. All subclasses of the RuntimeException class are not recoverable.
- C. The parameter in a catch block is of Throwable type.
- D. All subclasses of the RuntimeException class must be caught or declared to be thrown.
- E. All subclasses of the RuntimeException class are unchecked exceptions.
- F. All subclasses of the Error class are not recoverable.

Answer: BCD

NEW QUESTION 44

Which is true about the switch statement?

- A. Its expression can evaluate to a collection of values.
- B. The break statement, at the end of each case block, is optional.
- C. Its case label literals can be changed at runtime.
- D. It must contain the default section.

Answer: B

NEW QUESTION 49

Given the code fragment:

```
public static void main(String[] args) {  
    LocalDate date = LocalDate.of(2012, 01, 32);  
    date.plusDays(10);  
    System.out.println(date);  
}
```

What is the result?

- A. 2012-02-10
- B. 2012-02-11
- C. Compilation fails
- D. A DateTimeException is thrown at runtime.

Answer: D

NEW QUESTION 50

Given the code fragment:

```
abstract class Planet {  
    protected void revolve() {                //line n1  
    }  
  
    abstract void rotate();                    //line n2  
}  
  
class Earth extends Planet {  
    void revolve() {                            //line n3  
    }  
  
    protected void rotate() {                  //line n4  
    }  
}
```

Which two modifications, made independently, enable the code to compile? (Choose two.)

- A. Make the method at line n1 public.
- B. Make the method at line n2 public.
- C. Make the method at line n3 public.
- D. Make the method at line n3 protected.
- E. Make the method at line n4 public.

Answer: CD

NEW QUESTION 52

Given:


```
class Caller {
    private void init () {
        System.out.println("Initialized");
    }

    private void start () {
        init();
        System.out.println("Started");
    }
}

public class TestCall {
    public static void main(String[] args) {
        Caller c = new Caller();
        c.start(); // line n1
        c.init();  // line n2
    }
}
```

What is the result?

- A. Compilation fails at line n1.
- B. InitializedStartedInitialized
- C. InitializedStarted
- D. Compilation fails at line n2.

Answer: D

NEW QUESTION 55

Given the code fragment:

```
7.  StringBuilder sb1 = new StringBuilder("Duke");
8.  String str1 = sb1.toString();
9.  // insert code here
10. System.out.print(str1 == str2);
```

Which code fragment, when inserted at line 9, enables the code to print true?

- A. String str2 = str1;
- B. String str2 = new String(str1);
- C. String str2 = sb1.toString();
- D. String str2 = "Duke";

Answer: A

NEW QUESTION 59

Given:

```
public class Triangle {
    static double area;
    int b = 2, h = 3;
    public static void main(String[] args) {
        double p, b, h;          //line n1
        if (area == 0) {
            b = 3;
            h = 4;
            p = 0.5;
            area = p * b * h;      //line n2
        }
        System.out.println("Area is " + area);
    }
}
```

What is the result?

- A. Area is 6.0
- B. Area is 3.0
- C. Compilation fails at line n1
- D. Compilation fails at line n2.

Answer: D

NEW QUESTION 61

Given:

```
class Test {  
    public static void main (String [] args) {  
        int numbers [ ];  
        numbers = new int [2];  
        numbers [0] = 10;  
        numbers [1] = 20;  
  
        numbers = new int [4];  
        numbers [2] = 30;  
        numbers [3] = 40;  
        for (int x : numbers) {  
            System.out.print (" " + x) ;  
        }  
    }  
}
```

What is the result?

- A. 10 20 30 40
- B. 0 0 30 40
- C. Compilation fails.
- D. An exception is thrown at runtime.

Answer: C**NEW QUESTION 65**

Given the code fragment:

```
int wd = 0;  
String days[] = ("sun", "mon", "wed", "sat");  
for (String s:days) {  
    switch (s) {  
        case "sat":  
        case "sun":  
            wd -= 1;  
            break;  
        case "mon":  
            wd++;  
        case "wed":  
            wd += 2;  
    }  
}  
System.out.println(wd);
```

What is the result?

- A. 3
- B. 4
- C. -1
- D. Compilation fails.

Answer: A**NEW QUESTION 67**

Given the code fragment:

```
public static void main(String[] args) {  
    StringBuilder sb = new StringBuilder("Java");  
    String s = "Java";  
  
    if (sb.toString().equals(s.toString())) {  
        System.out.println("Match 1");  
    } else if (sb.equals(s)) {  
        System.out.println("Match 2");  
    } else {  
        System.out.println("No Match");  
    }  
}
```

What is the result?

- A. Match 1
- B. Match 2
- C. No Match
- D. A NullPointerException is thrown at runtime.

Answer: A

NEW QUESTION 68

Given:

```
class Caller {
    private void init () {
        System.out.println("Initialized");
    }

    private void start () {
        init();
        System.out.println("Started");
    }
}

public class TestCall {
    public static void main(String[] args) {
        Caller c = new Caller();
        c.start();
        c.init();
    }
}
```

What is the result?

- A. An exception is thrown at runtime.
- B. InitializedStartedInitialized
- C. InitializedStarted
- D. Compilation fails.

Answer: D

NEW QUESTION 69

Given this segment of code:

```
ArrayList<Cycle> myList = new ArrayList<>();
myList.add(new Motorcycle());
```

Which two statements, if either were true, would make the code compile? (Choose two.)

- A. Motorcycle is an interface that implements the Cycle class.
- B. Cycle is an interface that is implemented by the Motorcycle class.
- C. Cycle is an abstract superclass of Motorcycle.
- D. Cycle and Motorcycle both extend the Transportation superclass.
- E. Cycle and Motorcycle both implement the Transportation interface.
- F. Motorcycle is a superclass of Cycle.

Answer: BC

NEW QUESTION 72

Which statement best describes encapsulation?

- A. Encapsulation ensures that classes can be designed so that only certain fields and methods of an object are accessible from other objects.
- B. Encapsulation ensures that classes can be designed so that their methods are inheritable.
- C. Encapsulation ensures that classes can be designed with some fields and methods declared as abstract.
- D. Encapsulation ensures that classes can be designed so that if a method has an argument MyType x, any subclass of MyType can be passed to that method.

Answer: A

NEW QUESTION 74

Given the code fragment:

```
LocalDate date1 = LocalDate.now();
LocalDate date2 = LocalDate.of(6, 20, 2014);
LocalDate date3 = LocalDate.parse("2014-06-20", DateTimeFormatter.ISO_DATE);
System.out.println("date1 = " + date1);
System.out.println("date2 = " + date2);
System.out.println("date3 = " + date3);
```

Assume that the system date is June 20, 2014. What is the result?

- A
- ```
date1 = 2014-06-20
date2 = 2014-06-20
date3 = 2014-06-20
```
- B
- ```
date1 = 06/20/2014
date2 = 2014-06-20
date3 = Jun 20, 2014
```
- C Compilation fails.
- D An exception is thrown at runtime.

- A. Option A
B. Option B
C. Option C
D. Option D

Answer: A

NEW QUESTION 77

Which statement will empty the contents of a StringBuilder variable named sb?

- A. s
B. deleteAll ();
C. s
D. delete (0, s
E. size ());
F. s
G. delete (0, s
H. length ());
I. s
J. removeAll ();

Answer: C

NEW QUESTION 81

Given:

```
class Vehicle {
    int x;
    Vehicle() {
        this(10); // line n1
    }
    Vehicle(int x) {
        this.x = x;
    }
}

class Car extends Vehicle {
    int y;
    Car() {
        super();
        this(20); // line n2
    }
    Car(int y) {
        this.y = y;
    }
    public String toString() {
        return super.x + ":" + this.y;
    }
}
```

And given the code fragment:

And given the code fragment:

```
Vehicle y = new Car();
System.out.println(y);
```

What is the result?

- A. 10:20
- B. 0:20
- C. Compilation fails at line n1
- D. Compilation fails at line n2

Answer: D

NEW QUESTION 85

Given the code fragment:

```
if (aVar++ < 10) {  
    System.out.println(aVar + " Hello Universe!");  
} else {  
    System.out.println(aVar + " Hello World!");  
}
```

What is the result if the integer aVar is 9?

- A. Compilation fails.
- B. 10 Hello Universe!
- C. 10 Hello World!
- D. 9 Hello World!

Answer: B

NEW QUESTION 87

Which three statements are true about the structure of a Java class? (Choose three.)

- A. A class cannot have the same name as its field.
- B. A public class must have a main method.
- C. A class can have final static methods.
- D. A class can have overloaded private constructors.
- E. Fields need to be initialized before use.
- F. Methods and fields are optional components of a class.

Answer: BDE

NEW QUESTION 92

Given:

```
public class App {  
    public static void main(String[] args) {  
        int i = 10;  
        int j = 20;  
        int k =(j += i)/ 5;  
        System.out.print(i + " : " + j + " : " + k);  
    }  
}
```

What is the result?

- A. 10 : 30 : 6
- B. 10 : 22 : 22
- C. 10 : 22 : 20
- D. 10 : 22 : 6

Answer: A

NEW QUESTION 94

.....

Thank You for Trying Our Product

* 100% Pass or Money Back

All our products come with a 90-day Money Back Guarantee.

* One year free update

You can enjoy free update one year. 24x7 online support.

* Trusted by Millions

We currently serve more than 30,000,000 customers.

* Shop Securely

All transactions are protected by VeriSign!

100% Pass Your 1z0-808 Exam with Our Prep Materials Via below:

<https://www.certleader.com/1z0-808-dumps.html>