

## AWS-Certified-DevOps-Engineer-Professional Dumps

### Amazon AWS Certified DevOps Engineer Professional

<https://www.certleader.com/AWS-Certified-DevOps-Engineer-Professional-dumps.html>



**NEW QUESTION 1**

What method should I use to author automation if I want to wait for a CloudFormation stack to finish completing in a script?

- A. Event subscription using SQS.
- B. Event subscription using SNS.
- C. Poll using `ListStacks` / `list-stacks`.
- D. Poll using `GetStackStatus` / `get-stack-status`.

**Answer: C**

**Explanation:**

Event driven systems are good for IFTTT logic, but only polling will make a script wait to complete. ListStacks / list-stacks is a real method, GetStackStatus / get-stack-status is not.

Reference: <http://docs.aws.amazon.com/cli/latest/reference/cloudformation/list-stacks.html>

**NEW QUESTION 2**

Your application consists of 10% writes and 90% reads. You currently service all requests through a Route53 Alias Record directed towards an AWS ELB, which sits in front of an EC2 Auto Scaling Group. Your system is getting very expensive when there are large traffic spikes during certain news events, during which many more people request to read similar data all at the same time. What is the simplest and cheapest way to reduce costs and scale with spikes like this?

- A. Create an S3 bucket and asynchronously replicate common requests responses into S3 object
- B. When a request comes in for a precomputed response, redirect to AWS S3.
- C. Create another ELB and Auto Scaling Group layer mounted on top of the other system, adding a tier to the system
- D. Serve most read requests out of the top layer.
- E. Create a CloudFront Distribution and direct Route53 to the Distribution
- F. Use the ELB as an Origin and specify Cache Behaviours to proxy cache requests which can be served late.
- G. Create a Memcached cluster in AWS ElastiCache
- H. Create cache logic to serve requests which can be served late from the in-memory cache for increased performance.

**Answer: C**

**Explanation:**

CloudFront is ideal for scenarios in which entire requests can be served out of a cache and usage patterns involve heavy reads and spikiness in demand. A cache behavior is the set of rules you configure for a given URL pattern based on file extensions, file names, or any portion of a URL path on your website (e.g., \*.jpg). You can configure multiple cache behaviors for your web distribution. Amazon CloudFront will match incoming viewer requests with your list of URL patterns, and if there is a match, the service will honor the cache behavior you configure for that URL pattern. Each cache behavior can include the following Amazon CloudFront configuration values: origin server name, viewer connection protocol, minimum expiration period, query string parameters, cookies, and trusted signers for private content.

Reference: <https://aws.amazon.com/Cloudfront/dynamic-content/>

**NEW QUESTION 3**

You are building a game high score table in DynamoDB. You will store each user's highest score for each game, with many games, all of which have relatively similar usage levels and numbers of players. You need to be able to look up the highest score for any game. What's the best DynamoDB key structure?

- A. HighestScore as the hash / only key.
- B. GameID as the hash key, HighestScore as the range key.
- C. GameID as the hash / only key.
- D. GameID as the range / only key

**Answer: B**

**Explanation:**

Since access and storage for games is uniform, and you need to have ordering within each game for the scores (to access the highest value), your hash (partition) key should be the GameID, and there should be a range key for HighestScore.

Reference: <http://docs.aws.amazon.com/amazondynamodb/latest/developerguide/GuidelinesForTables.html#GuidelinesForTables.Partitions>

**NEW QUESTION 4**

What is server immutability?

- A. Not updating a server after creation.
- B. The ability to change server counts.
- C. Updating a server after creation.
- D. The inability to change server count

**Answer: A**

**Explanation:**

Disposable upgrades offer a simpler way to know if your application has unknown dependencies. The underlying EC2 instance usage is considered temporary or ephemeral in nature for the period of deployment until the current release is active. During the new release, a new set of EC2 instances are rolled out by terminating older instances. This type of upgrade technique is more common in an immutable infrastructure.

Reference: <https://d0.awsstatic.com/whitepapers/overview-of-deployment-options-on-aws.pdf>

**NEW QUESTION 5**

You are creating an application which stores extremely sensitive financial information. All information in the system must be encrypted at rest and in transit. Which of these is a violation of this policy?

- A. ELB SSL termination.

- B. ELB Using Proxy Protocol v1.
- C. CloudFront Viewer Protocol Policy set to HTTPS redirection.
- D. Telling S3 to use AES256 on the server-side

**Answer:** A

**Explanation:**

Terminating SSL terminates the security of a connection over HTTP, removing the S for "Secure" in HTTPS. This violates the "encryption in transit" requirement in the scenario.

Reference:

<http://docs.aws.amazon.com/ElasticLoadBalancing/latest/DeveloperGuide/elb-listener-config.html>

**NEW QUESTION 6**

Your system automatically provisions EIPs to EC2 instances in a VPC on boot. The system provisions the whole VPC and stack at once. You have two of them per VPC. On your new AWS account, your attempt to create a Development environment failed, after successfully creating Staging and Production environments in the same region. What happened?

- A. You didn't choose the Development version of the AMI you are using.
- B. You didn't set the Development flag to true when deploying EC2 instances.
- C. You hit the soft limit of 5 EIPs per region and requested a 6th.
- D. You hit the soft limit of 2 VPCs per region and requested a 3rd

**Answer:** C

**Explanation:**

There is a soft limit of 5 EIPs per Region for VPC on new accounts. The third environment could not allocate the 6th EIP.

Reference: [http://docs.aws.amazon.com/general/latest/gr/aws\\_service\\_limits.html#limits\\_vpc](http://docs.aws.amazon.com/general/latest/gr/aws_service_limits.html#limits_vpc)

**NEW QUESTION 7**

To monitor API calls against our AWS account by different users and entities, we can use to create a history of calls in bulk for later review, and use for reacting to AWS API calls in real-time.

- A. AWS Config; AWS Inspector
- B. AWS CloudTrail; AWS Config
- C. AWS CloudTrail; CloudWatch Events
- D. AWS Config; AWS Lambda

**Answer:** C

**Explanation:**

CloudTrail is a batch API call collection service, CloudWatch Events enables real-time monitoring of calls through the Rules object interface.

Reference: <https://aws.amazon.com/whitepapers/security-at-scale-governance-in-aws/>

**NEW QUESTION 8**

Which of these is not an intrinsic function in AWS CloudFormation?

- A. Fn::Equals
- B. Fn::If
- C. Fn::Not
- D. Fn::Parse

**Answer:** D

**Explanation:**

This is the complete list of Intrinsic Functions...: Fn::Base64, Fn::And, Fn::Equals, Fn::If, Fn::Not, Fn::Or, Fn::FindInMap, Fn::GetAtt, Fn::GetAZs, Fn::Join, Fn::Select, Ref

Reference:

<http://docs.aws.amazon.com/AWSCloudFormation/latest/UserGuide/intrinsic-function-reference.html>

**NEW QUESTION 9**

For AWS Auto Scaling, what is the first transition state an instance enters after leaving steady state when scaling in due to health check failure or decreased load?

- A. Terminating
- B. Detaching
- C. Terminating:Wait
- D. EnteringStandby

**Answer:** A

**Explanation:**

When Auto Scaling responds to a scale in event, it terminates one or more instances. These instances are detached from the Auto Scaling group and enter the Terminating state.

Reference: <http://docs.aws.amazon.com/AutoScaling/latest/DeveloperGuide/AutoScalingGroupLifecycle.html>

**NEW QUESTION 10**

You need to create a simple, holistic check for your system's general availability and uptime. Your system presents itself as an HTTP-speaking API. What is the most simple tool on AWS to achieve this with?

- A. Route53 Health Checks
- B. CloudWatch Health Checks
- C. AWS ELB Health Checks
- D. EC2 Health Checks

**Answer:** A

**Explanation:**

You can create a health check that will run into perpetuity using Route53, in one API call, which will ping your service via HTTP every 10 or 30 seconds. Amazon Route 53 must be able to establish a TCP connection with the endpoint within four seconds. In addition, the endpoint must respond with an HTTP status code of 200 or greater and less than 400 within two seconds after connecting.

Reference:

<http://docs.aws.amazon.com/Route53/latest/DeveloperGuide/dns-failover-determining-health-of-endpoints.html>

**NEW QUESTION 10**

What is the scope of an EC2 security group?

- A. Availability Zone
- B. Placement Group
- C. Region
- D. VPC

**Answer:** C

**Explanation:**

A security group is tied to a region and can be assigned only to instances in the same region. You can't enable an instance to communicate with an instance outside its region using security group rules. Traffic from an instance in another region is seen as WAN bandwidth.

Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/resources.html>

**NEW QUESTION 11**

You are building out a layer in a software stack on AWS that needs to be able to scale out to react to increased demand as fast as possible. You are running the code on EC2 instances in an Auto Scaling Group behind an ELB. Which application code deployment method should you use?

- A. SSH into new instances that come online, and deploy new code onto the system by pulling it from an S3 bucket, which is populated by code that you refresh from source control on new pushes.
- B. Bake an AMI when deploying new versions of code, and use that AMI for the Auto Scaling Launch Configuration.
- C. Create a Dockerfile when preparing to deploy a new version to production and publish it to S3. Use UserData in the Auto Scaling Launch configuration to pull down the Dockerfile from S3 and run it when new instances launch.
- D. Create a new Auto Scaling Launch Configuration with UserData scripts configured to pull the latest code at all times.

**Answer:** B

**Explanation:**

the bootstrapping process can be slower if you have a complex application or multiple applications to install. Managing a fleet of applications with several build tools and dependencies can be a challenging task during rollouts. Furthermore, your deployment service should be designed to do faster rollouts to take advantage of Auto Scaling.

Reference: <https://d0.awsstatic.com/whitepapers/overview-of-deployment-options-on-aws.pdf>

**NEW QUESTION 16**

Which status represents a failure state in AWS CloudFormation?

- A. `UPDATE_COMPLETE_CLEANUP_IN_PROGRESS`
- B. `DELETE_COMPLETE_WITH_ARTIFACTS`
- C. `ROLLBACK_IN_PROGRESS`
- D. `ROLLBACK_FAILED`

**Answer:** C

**Explanation:**

ROLLBACK\_IN\_PROGRESS means an UpdateStack operation failed and the stack is in the process of trying to return to the valid, pre-update state. UPDATE\_COMPLETE\_CLEANUP\_IN\_PROGRESS means an update was successful, and CloudFormation is deleting any replaced, no longer used resources. ROLLBACK\_FAILED is not a CloudFormation state (but UPDATE\_ROLLBACK\_FAILED is). DELETE\_COMPLETE\_WITH\_ARTIFACTS does not exist at all.

Reference:

<http://docs.aws.amazon.com/AWSCloudFormation/latest/UserGuide/using-cfn-updating-stacks.html>

**NEW QUESTION 17**

When thinking of AWS Elastic Beanstalk's model, which is true?

- A. Applications have many deployments, deployments have many environments.
- B. Environments have many applications, applications have many deployments.
- C. Applications have many environments, environments have many deployments.
- D. Deployments have many environments, environments have many application

**Answer:** C

**Explanation:**

Applications group logical services. Environments belong to Applications, and typically represent different deployment levels (dev, stage, prod, fo forth).

Deployments belong to environments, and are pushes of bundles of code for the environments to run.  
Reference: <http://docs.aws.amazon.com/elasticbeanstalk/latest/dg/welcome.html>

**NEW QUESTION 18**

You run operations for a company that processes digital wallet payments at a very high volume. One second of downtime, during which you drop payments or are otherwise unavailable, loses you on average USD 100. You balance the financials of the transaction system once per day. Which database setup is best suited to address this business risk?

- A. A multi-AZ RDS deployment with synchronous replication to multiple standbys and read-replicas for fast failover and ACID properties.
- B. A multi-region, multi-master, active-active RDS configuration using database-level ACID design principles with database trigger writes for replication.
- C. A multi-region, multi-master, active-active DynamoDB configuration using application control-level BASE design principles with change-stream write queue buffers for replication.
- D. A multi-AZ DynamoDB setup with changes streamed to S3 via AWS Kinesis, for highly durable storage and BASE properties.

**Answer:** C

**Explanation:**

Only the multi-master, multi-region DynamoDB answer makes sense. Multi-AZ deployments do not provide sufficient availability when a business loses USD 360,000 per hour of unavailability. As RDS does not natively support multi-region, and ACID does not perform well/at all over large distances between regions, only the DynamoDB answer works. Reference:

<http://docs.aws.amazon.com/amazondynamodb/latest/developerguide/Streams.CrossRegionRepl.html>

**NEW QUESTION 19**

When thinking of DynamoDB, what are true of Local Secondary Key properties?

- A. Either the partition key or the sort key can be different from the table, but not both.
- B. Only the sort key can be different from the table.
- C. The partition key and sort key can be different from the table.
- D. Only the partition key can be different from the table.

**Answer:** B

**Explanation:**

Global secondary index — an index with a partition key and a sort key that can be different from those on the table. A global secondary index is considered "global" because queries on the index can span all of the data in a table, across all partitions.

Reference: <http://docs.aws.amazon.com/amazondynamodb/latest/developerguide/SecondaryIndexes.html>

**NEW QUESTION 24**

Which deployment method, when using AWS Auto Scaling Groups and Auto Scaling Launch Configurations, enables the shortest time to live for individual servers?

- A. Pre-baking AMIs with all code and configuration on deploys.
- B. Using a Dockerfile bootstrap on instance launch.
- C. Using UserData bootstrapping scripts.
- D. Using AWS EC2 Run Commands to dynamically SSH into the fleet.

**Answer:** A

**Explanation:**

Note that the bootstrapping process can be slower if you have a complex application or multiple applications to install. Managing a fleet of applications with several build tools and dependencies can be a challenging task during rollouts. Furthermore, your deployment service should be designed to do faster rollouts to take advantage of Auto Scaling. Prebaking is a process of embedding a significant portion of your application artifacts within your base AMI. During the deployment process you can customize application installations by using EC2 instance artifacts such as instance tags, instance metadata, and Auto Scaling groups.

Reference: <https://d0.awsstatic.com/whitepapers/overview-of-deployment-options-on-aws.pdf>

**NEW QUESTION 29**

Which major database needs a BYO license?

- A. PostgreSQL
- B. MariaDB
- C. MySQL
- D. Oracle

**Answer:** D

**Explanation:**

Oracle is not open source, and requires a bring your own license model.

Reference: [http://docs.aws.amazon.com/AmazonRDS/latest/UserGuide/CHAP\\_Oracle.html](http://docs.aws.amazon.com/AmazonRDS/latest/UserGuide/CHAP_Oracle.html)

**NEW QUESTION 33**

What is the maximum supported single-volume throughput on EBS?

- A. 320 MiB/s
- B. 160 MiB/s
- C. 40 MiB/s
- D. 640 MiB/s

**Answer:**

A

**Explanation:**

The ceiling throughput for PIOPS on EBS is 320MiB/s.

Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/EBSVolumeTypes.html>

**NEW QUESTION 35**

You need to know when you spend \$1000 or more on AWS. What's the easy way for you to see that notification?

- A. AWS CloudWatch Events tied to API calls, when certain thresholds are exceeded, publish to SNS.
- B. Scrape the billing page periodically and pump into Kinesis.
- C. AWS CloudWatch Metrics + Billing Alarm + Lambda event subscription
- D. When a threshold is exceeded, email the manager.
- E. Scrape the billing page periodically and publish to SNS

**Answer: C****Explanation:**

Even if you're careful to stay within the free tier, it's a good idea to create a billing alarm to notify you if you exceed the limits of the free tier. Billing alarms can help to protect you against unknowingly accruing charges if you inadvertently use a service outside of the free tier or if traffic exceeds your expectations. Reference: <http://docs.aws.amazon.com/awsaccountbilling/latest/aboutv2/free-tier-alarms.html>

**NEW QUESTION 38**

Your serverless architecture using AWS API Gateway, AWS Lambda, and AWS DynamoDB experienced a large increase in traffic to a sustained 400 requests per second, and dramatically increased in failure rates. Your requests, during normal operation, last 500 milliseconds on average. Your DynamoDB table did not exceed 50% of provisioned throughput, and Table primary keys are designed correctly. What is the most likely issue?

- A. Your API Gateway deployment is throttling your requests.
- B. Your AWS API Gateway Deployment is bottlenecking on request (de)serialization.
- C. You did not request a limit increase on concurrent Lambda function executions.
- D. You used Consistent Read requests on DynamoDB and are experiencing semaphore lock

**Answer: C****Explanation:**

AWS API Gateway by default throttles at 500 requests per second steady-state, and 1000 requests per second at spike. Lambda, by default, throttles at 100 concurrent requests for safety. At 500 milliseconds (half of a second) per request, you can expect to support 200 requests per second at 100 concurrency. This is less than the 400 requests per second your system now requires. Make a limit increase request via the AWS Support Console.

AWS Lambda: Concurrent requests safety throttle per account -> 100

Reference: [http://docs.aws.amazon.com/general/latest/gr/aws\\_service\\_limits.html#limits\\_lambda](http://docs.aws.amazon.com/general/latest/gr/aws_service_limits.html#limits_lambda)

**NEW QUESTION 42**

For AWS CloudFormation, which stack state refuses UpdateStack calls?

- A. `UPDATE_ROLLBACK_FAILED`
- B. `UPDATE_ROLLBACK_COMPLETE`
- C. `UPDATE_COMPLETE`
- D. `CREATE_COMPLETE`

**Answer: A****Explanation:**

When a stack is in the `UPDATE_ROLLBACK_FAILED` state, you can continue rolling it back to return it to a working state (to `UPDATE_ROLLBACK_COMPLETE`). You cannot update a stack that is in the `UPDATE_ROLLBACK_FAILED` state. However, if you can continue to roll it back, you can return the stack to its original settings and try to update it again.

Reference:

<http://docs.aws.amazon.com/AWSCloudFormation/latest/UserGuide/using-cfn-updating-stacks-continue-update-rollback.html>

**NEW QUESTION 43**

You need to migrate 10 million records in one hour into DynamoDB. All records are 1.5KB in size. The data is evenly distributed across the partition key. How many write capacity units should you provision during this batch load?

- A. 6667
- B. 4166
- C. 5556
- D. 2778

**Answer: C****Explanation:**

You need 2 units to make a 1.5KB write, since you round up. You need 20 million total units to perform this load. You have 3600 seconds to do so. Divide and round up for 5556.

Reference: <http://docs.aws.amazon.com/amazondynamodb/latest/developerguide/HowItWorks.ProvisionedThroughput.html>

**NEW QUESTION 44**

What is the scope of an EBS volume?

- A. VPC
- B. Region
- C. Placement Group
- D. Availability Zone

**Answer:** D

**Explanation:**

An Amazon EBS volume is tied to its Availability Zone and can be attached only to instances in the same Availability Zone.  
Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/resources.html>

**NEW QUESTION 46**

Which of these is not an intrinsic function in AWS CloudFormation?

- A. Fn::Split
- B. Fn::FindInMap
- C. Fn::Select
- D. Fn::GetAZs

**Answer:** A

**Explanation:**

This is the complete list of Intrinsic Functions...: Fn::Base64, Fn::And, Fn::Equals, Fn::If, Fn::Not, Fn::Or, Fn::FindInMap, Fn::GetAtt, Fn::GetAZs, Fn::Join, Fn::Select, Ref  
Reference:  
<http://docs.aws.amazon.com/AWSCloudFormation/latest/UserGuide/intrinsic-function-reference.html>

**NEW QUESTION 48**

You need to replicate API calls across two systems in real time. What tool should you use as a buffer and transport mechanism for API call events?

- A. AWS SQS
- B. AWS Lambda
- C. AWS Kinesis
- D. AWS SNS

**Answer:** C

**Explanation:**

AWS Kinesis is an event stream service. Streams can act as buffers and transport across systems for in-order programmatic events, making it ideal for replicating API calls across systems.  
A typical Amazon Kinesis Streams application reads data from an Amazon Kinesis stream as data records. These applications can use the Amazon Kinesis Client Library, and they can run on Amazon EC2 instances. The processed records can be sent to dashboards, used to generate alerts, dynamically change pricing and advertising strategies, or send data to a variety of other AWS services. For information about Streams features and pricing, see Amazon Kinesis Streams.  
Reference: <http://docs.aws.amazon.com/kinesis/latest/dev/introduction.html>

**NEW QUESTION 53**

What is the scope of AWS IAM?

- A. Global
- B. Availability Zone
- C. Region
- D. Placement Group

**Answer:** A

**Explanation:**

IAM resources are all global; there is not regional constraint. Reference: <https://aws.amazon.com/iam/faqs/>

**NEW QUESTION 56**

You are building a mobile app for consumers to post cat pictures online. You will be storing the images in AWS S3. You want to run the system very cheaply and simply. Which one of these options allows you to build a photo sharing application without needing to worry about scaling expensive uploads processes, authentication/authorization and so forth?

- A. Build the application out using AWS Cognito and web identity federation to allow users to log in using Facebook or Google Account
- B. Once they are logged in, the secret token passed to that user is used to directly access resources on AWS, like AWS S3.
- C. Use JWT or SANIL compliant systems to build authorization policie
- D. Users log in with a username and password, and are given a token they can use indefinitely to make calls against the photo infrastructure.
- E. Use AWS API Gateway with a constantly rotating API Key to allow access from the client-sid
- F. Construct a custom build of the SDK and include S3 access in it.
- G. Create an AWS oAuth Service Domain ad grant public signup and access to the domai
- H. During setup, add at least one major social media site as a trusted Identity Provider for users.

**Answer:** A

**Explanation:**

The short answer is that Amazon Cognito is a superset of the functionality provided by web identity federation. It supports the same providers, and you configure your app and authenticate with those providers in the same way. But Amazon Cognito includes a variety of additional features. For example, it enables your users

to start using the app as a guest user and later sign in using one of the supported identity providers.

Reference:

<https://blogs.aws.amazon.com/security/post/Tx3SYCORF5EKRCO/How-Does-Amazon-Cognito-Relate-to-Existing-Web-Identity-Federatio>

#### NEW QUESTION 57

Your CTO has asked you to make sure that you know what all users of your AWS account are doing to change resources at all times. She wants a report of who is doing what over time, reported to her once per week, for as broad a resource type group as possible. How should you do this?

- A. Create a global AWS CloudTrail Trail
- B. Configure a script to aggregate the log data delivered to S3 once per week and deliver this to the CTO.
- C. Use CloudWatch Events Rules with an SNS topic subscribed to all AWS API call
- D. Subscribe the CTO to an email type delivery on this SNS Topic.
- E. Use AWS IAM credential reports to deliver a CSV of all uses of IAM User Tokens over time to the CTO.
- F. Use AWS Config with an SNS subscription on a Lambda, and insert these changes over time into a DynamoDB tabl
- G. Generate reports based on the contents of this table.

**Answer:** A

#### Explanation:

This is the ideal use case for AWS CloudTrail.

CloudTrail provides visibility into user activity by recording API calls made on your account. CloudTrail records important information about each API call, including the name of the API, the identity of the caller, the time of the API call, the request parameters, and the response elements returned by the AWS service. This information helps you to track changes made to your AWS resources and to troubleshoot operational issues. CloudTrail makes it easier to ensure compliance with internal policies and regulatory standards. Reference: <https://aws.amazon.com/Cloudtrail/faqs/>

#### NEW QUESTION 58

What is the order of most-to-least rapidly-scaling (fastest to scale first)?

(A) EC2 + ELB + Auto Scaling (B) Lambda (C) RDS

- A. B, A, C
- B. C, B, A
- C. C, A, B
- D. A, C, B

**Answer:** A

#### Explanation:

Lambda is designed to scale instantly. EC2 + ELB + Auto Scaling require single-digit minutes to scale out. RDS will take at least 15 minutes, and will apply OS patches or any other updates when applied. Reference: <https://aws.amazon.com/lambda/faqs/>

#### NEW QUESTION 62

Which is not a restriction on AWS EBS Snapshots?

- A. Snapshots which are shared cannot be used as a basis for other snapshots.
- B. You cannot share a snapshot containing an AWS Access Key ID or AWS Secret Access Key.
- C. You cannot share unencrypted snapshots.
- D. Snapshot restorations are restricted to the region in which the snapshots are create

**Answer:** A

#### Explanation:

Snapshots shared with other users are usable in full by the recipient, including but limited to the ability to base modified volumes and snapshots.

Reference:

<http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/ebs-modifying-snapshot-permissions.html>

#### NEW QUESTION 67

You need to deploy a new application version to production. Because the deployment is high-risk, you need to roll the new version out to users over a number of hours, to make sure everything is working correctly. You need to be able to control the proportion of users seeing the new version of the application down to the percentage point.

You use ELB and EC2 with Auto Scaling Groups and custom AMIs with your code pre-installed assigned to Launch Configurations. There are no database-level changes during your deployment. You have been told you cannot spend too much money, so you must not increase the number of EC2 instances much at all during the deployment, but you also need to be able to switch back to the original version of code quickly if something goes wrong. What is the best way to meet these requirements?

- A. Create a second ELB, Auto Scaling Launch Configuration, and Auto Scaling Group using the Launch Configuratio
- B. Create AMIs with all code pre-installe
- C. Assign the new AMI to the second Auto Scaling Launch Configuratio
- D. Use Route53 Weighted Round Robin Records to adjust the proportion of traffic hitting the two ELBs.
- E. Use the Blue-Green deployment method to enable the fastest possible rollback if neede
- F. Create a full second stack of instances and cut the DNS over to the new stack of instances, and change the DNS back if a rollback is needed.
- G. Create AMIs with all code pre-installe
- H. Assign the new AMI to the Auto Scaling Launch Configuration, to replace the old on
- I. Gradually terminate instances running the old code (launched with the old Launch Configuration) and allow the new AMIs to boot to adjust the traffic balance to the new cod
- J. On rollback, reverse the process by doing the same thing, but changing the AMI on the Launch Config back to the original code.
- K. Migrate to use AWS Elastic Beanstal
- L. Use the established and well-tested Rolling Deployment setting AWS provides on the new Application Environment, publishing a zip bundle of the new code and adjusting the wait period to spread the deployment over tim

M. Re-deploy the old code bundle to rollback if needed.

**Answer:** A

**Explanation:**

Only Weighted Round Robin DNS Records and reverse proxies allow such fine-grained tuning of traffic splits. The Blue-Green option does not meet the requirement that we mitigate costs and keep overall EC2 fleet size consistent, so we must select the 2 ELB and ASG option with WRR DNS tuning. This method is called A/B deployment and/or Canary deployment.

Reference: <https://d0.awsstatic.com/whitepapers/overview-of-deployment-options-on-aws.pdf>

**NEW QUESTION 72**

What is required to achieve gigabit network throughput on EC2? You already selected cluster-compute, 10GB instances with enhanced networking, and your workload is already network-bound, but you are not seeing 10 gigabit speeds.

- A. Enable bplex networking on your servers, so packets are non-blocking in both directions and there's no switching overhead.
- B. Ensure the instances are in different VPCs so you don't saturate the Internet Gateway on any one VPC.
- C. Select PIOPS for your drives and mount several, so you can provision sufficient disk throughput.
- D. Use a placement group for your instances so the instances are physically near each other in the same Availability Zone.

**Answer:** D

**Explanation:**

You are not guaranteed 10gigabit performance, except within a placement group.

A placement group is a logical grouping of instances within a single Availability Zone. Using placement groups enables applications to participate in a low-latency, 10 Gbps network. Placement groups are recommended for applications that benefit from low network latency, high network throughput, or both. Reference:

<http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/placement-groups.html>

**NEW QUESTION 75**

If I want CloudFormation stack status updates to show up in a continuous delivery system in as close to real time as possible, how should I achieve this?

- A. Use a long-poll on the Resources object in your CloudFormation stack and display those state changes in the UI for the system.
- B. Use a long-poll on the `ListStacks` API call for your CloudFormation stack and display those state changes in the UI for the system.
- C. Subscribe your continuous delivery system to an SNS topic that you also tell your CloudFormation stack to publish events into.
- D. Subscribe your continuous delivery system to an SQS queue that you also tell your CloudFormation stack to publish events into.

**Answer:** C

**Explanation:**

Use NotificationARNs.member.N when making a CreateStack call to push stack events into SNS in nearly real-time.

Reference:

<http://docs.aws.amazon.com/AWSCloudFormation/latest/UserGuide/using-cfn-updating-stacks-monitor-stack.html>

**NEW QUESTION 80**

Which of these is not a reason a Multi-AZ RDS instance will failover?

- A. An Availability Zone outage
- B. A manual failover of the DB instance was initiated using Reboot with failover
- C. To autoscale to a higher instance class
- D. The primary DB instance fails

**Answer:** C

**Explanation:**

The primary DB instance switches over automatically to the standby replica if any of the following conditions occur: An Availability Zone outage, the primary DB instance fails, the DB instance's server type is changed, the operating system of the DB instance is, undergoing software patching, a manual failover of the DB instance was initiated using Reboot with failover

Reference: <http://docs.aws.amazon.com/AmazonRDS/latest/UserGuide/Concepts.MultiAZ.html>

**NEW QUESTION 85**

You need to create an audit log of all changes to customer banking data. You use DynamoDB to store this customer banking data. It's important not to lose any information due to server failures. What is an elegant way to accomplish this?

- A. Use a DynamoDB StreamSpecification and stream all changes to AWS Lambda
- B. Log the changes to AWS CloudWatch Logs, removing sensitive information before logging.
- C. Before writing to DynamoDB, do a pre-write acknowledgment to disk on the application server, removing sensitive information before logging
- D. Periodically rotate these log files into S3.
- E. Use a DynamoDB StreamSpecification and periodically flush to an EC2 instance store, removing sensitive information before putting the object
- F. Periodically flush these batches to S3.
- G. Before writing to DynamoDB, do a pre-write acknowledgment to disk on the application server, removing sensitive information before logging
- H. Periodically pipe these files into CloudWatch Logs.

**Answer:** A

**Explanation:**

All suggested periodic options are sensitive to server failure during or between periodic flushes. Streaming to Lambda and then logging to CloudWatch Logs will make the system resilient to instance and Availability Zone failures.

Reference: <http://docs.aws.amazon.com/lambda/latest/dg/with-ddb.html>

**NEW QUESTION 88**

You need your API backed by DynamoDB to stay online during a total regional AWS failure. You can tolerate a couple minutes of lag or slowness during a large failure event, but the system should recover with normal operation after those few minutes. What is a good approach?

- A. Set up DynamoDB cross-region replication in a master-standby configuration, with a single standby in another region
- B. Create an Auto Scaling Group behind an ELB in each of the two regions DynamoDB is running in
- C. Add a Route53 Latency DNS Record with DNS Failover, using the ELBs in the two regions as the resource records.
- D. Set up a DynamoDB Multi-Region table
- E. Create an Auto Scaling Group behind an ELB in each of the two regions DynamoDB is running in
- F. Add a Route53 Latency DNS Record with DNS Failover, using the ELBs in the two regions as the resource records.
- G. Set up a DynamoDB Multi-Region table
- H. Create a cross-region ELB pointing to a cross-region Auto Scaling Group, and direct a Route53 Latency DNS Record with DNS Failover to the cross-region ELB.
- I. Set up DynamoDB cross-region replication in a master-standby configuration, with a single standby in another region
- J. Create a cross-region ELB pointing to a cross-region Auto Scaling Group, and direct a Route53 Latency DNS Record with DNS Failover to the cross-region ELB.

**Answer:** A

**Explanation:**

There is no such thing as a cross-region ELB, nor such thing as a cross-region Auto Scaling Group, nor such thing as a DynamoDB Multi-Region Table. The only option that makes sense is the cross-regional replication version with two ELBs and ASGs with Route53 Failover and Latency DNS.

Reference: <http://docs.aws.amazon.com/amazondynamodb/latest/developerguide/Streams.CrossRegionRepl.html>

**NEW QUESTION 92**

You have an asynchronous processing application using an Auto Scaling Group and an SQS Queue. The Auto Scaling Group scales according to the depth of the job queue. The completion velocity of the jobs has gone down, the Auto Scaling Group size has maxed out, but the inbound job velocity did not increase. What is a possible issue?

- A. Some of the new jobs coming in are malformed and unprocessable.
- B. The routing tables changed and none of the workers can process events anymore.
- C. Someone changed the IAM Role Policy on the instances in the worker group and broke permissions to access the queue.
- D. The scaling metric is not functioning correctly

**Answer:** A

**Explanation:**

The IAM Role must be fine, as if it were broken, NO jobs would be processed since the system would never be able to get any queue messages. The same reasoning applies to the routing table change. The scaling metric is fine, as instance count increased when the queue depth increased due to more messages entering than exiting. Thus, the only reasonable option is that some of the recent messages must be malformed and unprocessable.

Reference:

<https://github.com/andrew-templeton/cloudacademy/blob/fca920b45234bbe99cc0e8efb9c65134884dd489/questions/null>

**NEW QUESTION 94**

Your company wants to understand where cost is coming from in the company's production AWS account. There are a number of applications and services running at any given time. Without expending too much initial development time, how best can you give the business a good understanding of which applications cost the most per month to operate?

- A. Create an automation script which periodically creates AWS Support tickets requesting detailed intra-month information about your bill.
- B. Use custom CloudWatch Metrics in your system, and put a metric data point whenever cost is incurred.
- C. Use AWS Cost Allocation Tagging for all resources which support it
- D. Use the Cost Explorer to analyze costs throughout the month.
- E. Use the AWS Price API and constantly running resource inventory scripts to calculate total price based on multiplication of consumed resources over time.

**Answer:** C

**Explanation:**

Cost Allocation Tagging is a built-in feature of AWS, and when coupled with the Cost Explorer, provides a simple and robust way to track expenses.

You can also use tags to filter views in Cost Explorer. Note that before you can filter views by tags in Cost Explorer, you must have applied tags to your resources and activate them, as described in the following sections. For more information about Cost Explorer, see Analyzing Your Costs with Cost Explorer. Reference:

<http://docs.aws.amazon.com/awsaccountbilling/latest/aboutv2/cost-alloc-tags.html>

**NEW QUESTION 95**

There is a very serious outage at AWS. EC2 is not affected, but your EC2 instance deployment scripts stopped working in the region with the outage. What might be the issue?

- A. The AWS Console is down, so your CLI commands do not work.
- B. S3 is unavailable, so you can't create EBS volumes from a snapshot you use to deploy new volumes.
- C. AWS turns off the `DeployCode` API call when there are major outages, to protect from system floods.
- D. None of the other answers make sense
- E. If EC2 is not affected, it must be some other issue

**Answer:** B

**Explanation:**

S3 stores all snapshots. If S3 is unavailable, snapshots are unavailable.

Amazon EC2 also uses Amazon S3 to store snapshots (backup copies) of the data volumes. You can use snapshots for recovering data quickly and reliably in case of application or system failures. You can also use snapshots as a baseline to create multiple new data volumes, expand the size of an existing data volume, or move data volumes across multiple Availability Zones, thereby making your data usage highly scalable. For more information about using data volumes and snapshots, see Amazon Elastic Block Store.

Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/AmazonS3.html>

**NEW QUESTION 98**

Which of the following tools does not directly support AWS OpsWorks, for monitoring your stacks?

- A. AWS Config
- B. Amazon CloudWatch Metrics
- C. AWS CloudTrail
- D. Amazon CloudWatch Logs

**Answer:** A

**Explanation:**

You can monitor your stacks in the following ways: AWS OpsWorks uses Amazon CloudWatch to provide thirteen custom metrics with detailed monitoring for each instance in the stack; AWS OpsWorks integrates with AWS CloudTrail to log every AWS OpsWorks API call and store the data in an Amazon S3 bucket; You can use Amazon CloudWatch Logs to monitor your stack's system, application, and custom logs. Reference: <http://docs.aws.amazon.com/opsworks/latest/userguide/monitoring.html>

**NEW QUESTION 99**

What is a circular dependency in AWS CloudFormation?

- A. When a Template references an earlier version of itself.
- B. When Nested Stacks depend on each other.
- C. When Resources form a DependsOn loop.
- D. When a Template references a region, which references the original Template

**Answer:** C

**Explanation:**

To resolve a dependency error, add a DependsOn attribute to resources that depend on other resources in your template. In some cases, you must explicitly declare dependencies so that AWS CloudFormation can create or delete resources in the correct order. For example, if you create an Elastic IP and a VPC with an Internet gateway in the same stack, the Elastic IP must depend on the Internet gateway attachment. For additional information, see DependsOn Attribute. Reference: <http://docs.aws.amazon.com/AWSCloudFormation/latest/UserGuide/troubleshooting.html#troubleshooting-errors-dependence-error>

**NEW QUESTION 100**

You need to run a very large batch data processing job one time per day. The source data exists entirely in S3, and the output of the processing job should also be written to S3 when finished. If you need to version control this processing job and all setup and teardown logic for the system, what approach should you use?

- A. Model an AWS EMR job in AWS Elastic Beanstalk.
- B. Model an AWS EMR job in AWS CloudFormation.
- C. Model an AWS EMR job in AWS OpsWorks.
- D. Model an AWS EMR job in AWS CLI Compose

**Answer:** B

**Explanation:**

To declaratively model build and destroy of a cluster, you need to use AWS CloudFormation. OpsWorks and Elastic Beanstalk cannot directly model EMR Clusters. The CLI is not declarative, and CLI Composer does not exist.

Reference:

<http://docs.aws.amazon.com/AWSCloudFormation/latest/UserGuide/aws-resource-emr-cluster.html>

**NEW QUESTION 104**

What is true of the way that encryption works with EBS?

- A. Snapshotting an encrypted volume makes an encrypted snapshot; restoring an encrypted snapshot creates an encrypted volume when specified / requested.
- B. Snapshotting an encrypted volume makes an encrypted snapshot when specified / requested; restoring an encrypted snapshot creates an encrypted volume when specified / requested.
- C. Snapshotting an encrypted volume makes an encrypted snapshot; restoring an encrypted snapshot always creates an encrypted volume.
- D. Snapshotting an encrypted volume makes an encrypted snapshot when specified / requested; restoring an encrypted snapshot always creates an encrypted volume.

**Answer:** C

**Explanation:**

Snapshots that are taken from encrypted volumes are automatically encrypted. Volumes that are created from encrypted snapshots are also automatically encrypted. Your encrypted volumes and any associated snapshots always remain protected. For more information, see Amazon EBS Encryption.

Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/EBSEncryption.html>

**NEW QUESTION 109**

You are designing a system which needs, at minimum, 8 m4.large instances operating to service traffic. When designing a system for high availability in the us-east-1 region, which has 6 Availability Zones, your company needs to be able to handle death of a full availability zone. How should you distribute the servers, to save as much cost as possible, assuming all of the EC2 nodes are properly linked to an ELB? Your VPC account can utilize us-east-1's AZ's a through f, inclusive.

- A. 3 servers in each of AZ's a through d, inclusive.
- B. 8 servers in each of AZ's a and b.
- C. 2 servers in each of AZ's a through e, inclusive.
- D. 4 servers in each of AZ's a through c, inclusive.

**Answer:** C

**Explanation:**

You need to design for N+1 redundancy on Availability Zones.  $ZONE\_COUNT = (REQUIRED\_INSTANCES / INSTANCE\_COUNT\_PER\_ZONE) + 1$ . To minimize cost, spread the instances across as many possible zones as you can. By using a though e, you are allocating 5 zones. Using 2 instances, you have 10 total instances. If a single zone fails, you have 4 zones left, with 2 instances each, for a total of 8 instances. By spreading out as much as possible, you have increased cost by only 25% and significantly de-risked an availability zone failure.

Reference:

<http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/using-regions-availability-zones.html#concepts-regions-availability-zones>

**NEW QUESTION 112**

What is web identity federation?

- A. Use of an identity provider like Google or Facebook to become an AWS IAM User.
- B. Use of an identity provider like Google or Facebook to exchange for temporary AWS security credentials.
- C. Use of AWS IAM User tokens to log in as a Google or Facebook user.
- D. Use of AWS STS Tokens to log in as a Google or Facebook use

**Answer:** B

**Explanation:**

users of your app can sign in using a well-known identity provider (IdP) -such as Login with Amazon, Facebook, Google, or any other OpenID Connect (OIDC)-compatible IdP, receive an authentication token, and then exchange that token for temporary security credentials in AWS that map to an IAM role with permissions to use the resources in your AWS account.

Reference: [http://docs.aws.amazon.com/IAM/latest/UserGuide/id\\_roles\\_providers\\_oidc.html](http://docs.aws.amazon.com/IAM/latest/UserGuide/id_roles_providers_oidc.html)

**NEW QUESTION 117**

You were just hired as a DevOps Engineer for a startup. Your startup uses AWS for 100% of their infrastructure. They currently have no automation at all for deployment, and they have had many failures while trying to deploy to production. The company has told you deployment process risk mitigation is the most important thing now, and you have a lot of budget forttools and AWS resources.

Their stack: 2-tier API

Data stored in DynamoDB or S3, depending on type Compute layer is EC2 in Auto Scaling Groups They use Route53 for DNS pointing to an ELB

An ELB balances load across the EC2 instances

The scaling group properly varies between 4 and 12 EC2 sewers.

Which of the following approaches, given this company's stack and their priorities, best meets the company's needs?

- A. Model the stack in AWS Elastic Beanstalk as a single Application with multiple Environment
- B. Use Elastic Beanstalk's Rolling Deploy option to progressively roll out application code changes when promoting across environments.
- C. Model the stack in 3 CloudFormation templates: Data layer, compute layer, and networking laye
- D. Write stack deployment and integration testing automation following Blue-Green methodologies.
- E. Model the stack in AWS OpsWorks as a single Stack, with 1 compute layer and its associated EL
- F. Use Chef and App Deployments to automate Rolling Deployment.
- G. Model the stack in 1 CloudFormation template, to ensure consistency and dependency graph resolutio
- H. Write deployment and integration testing automation following Rolling Deployment methodologies.

**Answer:** B

**Explanation:**

AWS recommends Blue-Green for zero-downtime deploys. Since you use DynamoDB, and neither AWS OpsWorks nor AWS Elastic Beanstalk directly supports DynamoDB, the option selecting CloudFormation and Blue-Green is correct.

You use various strategies to migrate the traffic from your current application stack (blue) to a new version of the application (green). This is a popular technique for deploying applications with zero downtime. The deployment services like AWS Elastic Beanstalk, AWS CloudFormation, or AWS OpsWorks are particularly useful as they provide a simple way to clone your running application stack. You can set up a new version of your application (green) by simply cloning current version of the application (blue). Reference: <https://d0.awsstatic.com/whitepapers/overview-of-deployment-options-on-aws.pdf>

**NEW QUESTION 120**

What is the scope of an EBS snapshot?

- A. Availability Zone
- B. Placement Group
- C. Region
- D. VPC

**Answer:** C

**Explanation:**

An EBS snapshot is tied to its region and can only be used to create volumes in the same region. You can copy a snapshot from one region to another. For more information, see Copying an Amazon EBS Snapshot.

Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/resources.html>

**NEW QUESTION 121**

When thinking of AWS Elastic Beanstalk, which statement is true?

- A. Worker tiers pull jobs from SNS.
- B. Worker tiers pull jobs from HTTP.
- C. Worker tiers pull jobs from JSON.
- D. Worker tiers pull jobs from SQ

**Answer:** D

**Explanation:**

Elastic Beanstalk installs a daemon on each Amazon EC2 instance in the Auto Scaling group to process Amazon SQS messages in the worker environment. The daemon pulls data off the Amazon SQS queue, inserts it into the message body of an HTTP POST request, and sends it to a user-configurable URL path on the local host. The content type for the message body within an HTTP POST request is application/json by default.

Reference:

<http://docs.aws.amazon.com/elasticbeanstalk/latest/dg/using-features-managing-env-tiers.html>

**NEW QUESTION 122**

You need the absolute highest possible network performance for a cluster computing application. You already selected homogeneous instance types supporting 10 gigabit enhanced networking, made sure that your workload was network bound, and put the instances in a placement group. What is the last optimization you can make?

- A. Use 9001 MTU instead of 1500 for Jumbo Frames, to raise packet body to packet overhead ratios.
- B. Segregate the instances into different peered VPCs while keeping them all in a placement group, so each one has its own Internet Gateway.
- C. Bake an AMI for the instances and relaunch, so the instances are fresh in the placement group and donot have noisy neighbors.
- D. Turn off SYN/ACK on your TCP stack or begin using UDP for higher throughpu

**Answer:** A

**Explanation:**

For instances that are collocated inside a placement group, jumbo frames help to achieve the maximum network throughput possible, and they are recommended in this case. For more information, see Placement Groups.

Reference: [http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/network\\_mtu.htm|#jumbo\\_frame\\_instances](http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/network_mtu.htm|#jumbo_frame_instances)

**NEW QUESTION 127**

.....

## Thank You for Trying Our Product

\* 100% Pass or Money Back

All our products come with a 90-day Money Back Guarantee.

\* One year free update

You can enjoy free update one year. 24x7 online support.

\* Trusted by Millions

We currently serve more than 30,000,000 customers.

\* Shop Securely

All transactions are protected by VeriSign!

**100% Pass Your AWS-Certified-DevOps-Engineer-Professional Exam with Our Prep Materials Via below:**

<https://www.certleader.com/AWS-Certified-DevOps-Engineer-Professional-dumps.html>