

## 1z0-082 Dumps

### Oracle Database Administration I

<https://www.certleader.com/1z0-082-dumps.html>



**NEW QUESTION 1**

Examine this command:

```
ALTER DATABASE
    MOVE DATAFILE '/u01/sales1.dbf'
    TO '/u01/sales01.dbf'
    REUSE;
```

Which two statements are true? (Choose two.)

- A. DML may be performed on tables with one or more extents in this data file during the execution of this command.
- B. The tablespace containing SALES1.DBF must be altered READ ONLY before executing the command.
- C. The tablespace containing SALES1.DBF must be altered OFFLINE before executing the command.
- D. If Oracle Managed Files (OMF) is used, then the file is renamed but moved to DB\_CREATE\_FILE\_DEST.
- E. The file is renamed and stored in the same location

**Answer:** AB

**NEW QUESTION 2**

Examine this description of the TRANSACTIONS table:

Name	Null?	Type
TRANSACTION_ID	NOT NULL	VARCHAR2 (6)
TRANSACTION_DATE		DATE
AMOUNT		NUMBER (10, 2)
CUSTOMER_ID		VARCHAR2 (6)

Which two SQL statements execute successfully? (Choose two.)

- A. SELECT customer\_id AS "CUSTOMER-ID", transaction\_date AS DATE, amount + 100 "DUES" FROM transactions;
- B. SELECT customer\_id AS "CUSTOMER-ID", transaction\_date AS "DATE", amount + 100 DUES FROM transactions;
- C. SELECT customer\_id AS CUSTOMER-ID, transaction\_date AS TRANS\_DATE, amount + 100 "DUES AMOUNT" FROM transactions;
- D. SELECT customer\_id CUSTID, transaction\_date TRANS\_DATE, amount + 100 DUES FROM transactions;
- E. SELECT customer\_id AS 'CUSTOMER-ID', transaction\_date AS DATE, amount + 100 'DUES AMOUNT' FROM transactions;

**Answer:** BD

**NEW QUESTION 3**

Which three statements are true about the tools used to configure Oracle Net Services? (Choose three.)

- A. The Oracle Net Configuration Assistant is only used when running the Oracle installer
- B. Oracle Net Manager can be used to centrally configure listeners on any database server target
- C. The lsnrctl utility requires a listener.ora file to exist before it is started
- D. Oracle Net Manager can be used to locally configure naming methods on a database server
- E. Enterprise Manager Cloud Control can be used to centrally configure listeners on any managed database server
- F. Enterprise Manager Cloud Control can be used to centrally configure net service names for any databaseserver target

**Answer:** BDE

**NEW QUESTION 4**

Which three statements are true about advanced connection options supported by Oracle Net for connection to Oracle Database instances? (Choose three.)

- A. Connect Time Failover requires the use of Transparent Application Failover (TAF)
- B. Source Routing requires the use of a name server
- C. Source Routing enables the use of Connection Manager (CMAN) which enables network traffic to be routed through a firewall
- D. Load Balancing can balance the number of connections to dispatchers when using a Shared Server configuration
- E. Load Balancing requires the use of a name server
- F. Connect Time Failover requires the connect string to have two or more listener addresses configured

**Answer:** BCF

**NEW QUESTION 5**

In the ORCL database, UNDOTBS1 is the active undo tablespace with these properties:

- \1. A size of 100 MB
- \2. AUTOEXTEND is off
- \3. UNDO\_RETENTION is set to 15 minutes
- \4. It has RETENTION GUARANTEE

UNDOTBS1 fills with uncommitted undo 10 minutes after the database opens. What will happen when the next update is attempted by any transaction?

- A. It succeeds and the generated undo is stored in SYSTEM.
- B. It fails and returns the error message "ORA-30036: unable to extend segment by 8 in undo tablespace 'UNDOTBS1'".
- C. It succeeds and the least recently written undo block of UNDOTBS1 is overwritten by the generated undo.
- D. It succeeds and the generated undo is stored in SYSAUX.

E. It succeeds and the least recently read undo block of UNDOTBS1 is overwritten by the generated undo.

**Answer:** C

#### NEW QUESTION 6

The CUSTOMERS table has a CUST\_CREDIT\_LIMIT column of data type NUMBER. Which two queries execute successfully? (Choose two.)

- A. SELECT NVL(cust\_credit\_limit \* .15, 'Not Available') FROM customers;
- B. SELECT NVL2(cust\_credit\_limit \* .15, 'Not Available') FROM customers;
- C. SELECT NVL(TO\_CHAR(cust\_credit\_limit \* .15), 'Not Available') FROM customers;
- D. SELECT TO\_CHAR(NVL(cust\_credit\_limit \* .15, 'Not Available')) FROM customers;
- E. SELECT NVL2(cust\_credit\_limit, TO\_CHAR(cust\_credit\_limit \* .15), 'Not Available') FROM customers;

**Answer:** BC

#### NEW QUESTION 7

You execute this command:

```
CREATE BIGFILE TABLESPACE big_tbs
    DATAFILE '/u01/oracle/data/big_f1.dbf'
    SIZE 20G;
```

Sufficient storage is available in filesystem /u01.

Which two statements are true about the BIG\_TBS tablespace? (Choose two.)

- A. AUTOEXTEND is possible for the datafile
- B. It must be bigger than the largest SMALLFILE tablespace
- C. Additional data files may not be added
- D. It will be a dictionary-managed tablespace by default
- E. It will always have a 32K blocksize

**Answer:** AB

#### NEW QUESTION 8

Which three statements are true about dropping and unused columns in an Oracle database? (Choose three.)

- A. A primary key column referenced by another column as a foreign key can be dropped if using the CASCADE option.
- B. An UNUSED column's space is reclaimed automatically when the block containing that column is next queried.
- C. An UNUSED column's space is reclaimed automatically when the row containing that column is next queried.
- D. Partition key columns cannot be dropped.
- E. A DROP COLUMN command can be rolled back
- F. A column that is set to UNUSED still counts towards the limit of 1000 columns per table

**Answer:** ABF

#### NEW QUESTION 9

Which two statements are true regarding Oracle database space management within blocks managed by Automatic Segment Space Management (ASSM)? (Choose two.)

- A. PCTFREE defaults to 10% for all blocks in all segments for all compression methods
- B. ASSM assigns blocks to one of four fullness categories based on what percentage of the block is allocated for rows
- C. Update operations always attempt to find blocks with free space appropriate to the length of the row being updated
- D. Insert operations always attempt to find blocks with free space appropriate to the length of the row being inserted
- E. A block will always be eligible for inserts if the row is short enough to fit into the block

**Answer:** CE

#### NEW QUESTION 10

The INVOICE table has a QTY\_SOLD column of data type NUMBER and an INVOICE\_DATE column of data type DATE. NLS\_DATE\_FORMAT is set to DD-MON-RR.

Which two are true about data type conversions involving these columns in query expressions? (Choose two.)

- A. CONCAT (qty\_sold, invoice\_date) : requires explicit conversion
- B. invoice\_date = '15-march-2019' : uses implicit conversion
- C. invoice\_date > '01-02-2019' : uses implicit conversion
- D. qty\_sold BETWEEN '101' AND '110' : uses implicit conversion
- E. qty\_sold = '0554982' uses implicit conversion

**Answer:** BD

#### NEW QUESTION 10

Which three statements are true about Oracle synonyms? (Choose three.)

- A. A synonym cannot be created for a PL/SQL package
- B. A synonym can be available to all users
- C. A SEQUENCE can have a synonym
- D. A synonym created by one user can refer to an object belonging to another user

E. Any user can drop a PUBLIC synonym

**Answer:** BCD

**NEW QUESTION 14**

Which three functions are performed by dispatchers in a shared server configuration? (Choose three.)

- A. writing inbound request to the common request queue from all shared server connections
- B. checking for outbound shared server responses on the common outbound response queue
- C. receiving inbound requests from processes using shared server connections
- D. sending each connection input request to the appropriate shared server input queue
- E. broadcasting shared server session responses back to requesters on all connections
- F. sending shared server session responses back to requesters on the appropriate connection

**Answer:** ACD

**NEW QUESTION 19**

Examine this command and some partial output:

```
LSNRCTL> start LISTENER_1

Listening Endpoints Summary...
  (DESCRIPTION=(ADDRESS=PROTOCOL=tcp) (HOST=host01.abc.com) (PORT=1562))
Services Summary...
Service "DB01.abc.com " has 1 instance(s).
  Instance "DB01", status UNKNOWN, has 1 handler(s) for this service...
The command completed successfully
```

Why does the DB01.abc.com service show unknown status?

- A. The service DB01.abc.com is dynamically registered
- B. The LOCAL\_LISTENER database parameter is not set to a service name that refers to LISTENER\_1
- C. The service DB01.abc.com is statically registered
- D. The listener is not listening on the default port 1521
- E. The SID\_LIST\_LISTENER section is not contained in the LISTENER.ORA file

**Answer:** B

**NEW QUESTION 21**

Which two statements are true about the SET VERIFY ON command? (Choose two.)

- A. It can be used only in SQL\*Plus
- B. It displays values for variables used only in the WHERE clause of a query
- C. It can be used in SQL Developer and SQL\*Plus
- D. It displays values for variables created by the DEFINE command
- E. It displays values for variables prefixed with &&

**Answer:** AD

**NEW QUESTION 22**

Your database instance was shut down normally and then started in NOMOUNT state. You then execute this command:

```
ALTER DATABASE MOUNT;
```

Which two actions are performed? (Choose two.)

- A. The online redo logs are opened
- B. The online data files are opened
- C. The alert log records the execution details
- D. The Oracle background processes are started
- E. The initialization parameter file is read
- F. The control file is read

**Answer:** DF

**NEW QUESTION 23**

Which three statements are true about single-row functions? (Choose three.)

- A. They can be used only in the WHERE clause of a SELECT statement
- B. The argument can be a column name, variable, literal or an expression
- C. The data type returned can be different from the data type of the argument
- D. They can be nested to any level
- E. They can accept only one argument
- F. They return a single result row per table

**Answer:** BCF

**NEW QUESTION 27**

Which three statements are true about table data storage in an Oracle Database? (Choose three.)

- A. Data block headers contain their own Data Block Address (DBA)
- B. A table row piece can be chained across several database blocks
- C. Multiple row pieces from the same row may be stored in different database blocks
- D. Multiple row pieces from the same row may be stored in the same block
- E. Data block free space is always contiguous in the middle of the block
- F. Index block free space is always contiguous in the middle of the block

**Answer:** BCE

**NEW QUESTION 32**

In one of your databases, you create a user, HR, and then execute this command: GRANT CREATE SESSION TO hr WITH ADMIN OPTION;  
Which three actions can HR perform? (Choose three.)

- A. Revoke the CREATE SESSION privilege from other users
- B. Revoke the CREATE SESSION privilege from user HR
- C. Log in to the database instance
- D. Grant the CREATE SESSION privilege with ADMIN OPTION to other users
- E. Execute DDL statements in the HR schema
- F. Execute DML statements in the HR schema

**Answer:** ADE

**NEW QUESTION 37**

Which two tasks can you perform using DBCA for databases? (Choose two.)

- A. Configure a nonstandard block size for a new database
- B. Register a new database with an available Enterprise Manager Management server
- C. Change the standard block size of an existing database
- D. Configure incremental backups for a new database
- E. Enable flashback database for an existing database

**Answer:** BC

**NEW QUESTION 38**

Which two statements are true about the rules of precedence for operators? (Choose two.)

- A. The concatenation operator || is always evaluated before addition and subtraction in an expression
- B. NULLS influence the precedence of operators in an expression
- C. The + binary operator has the highest precedence in an expression in a SQL statement
- D. Arithmetic operators with equal precedence are evaluated from left to right within an expression
- E. Multiple parentheses can be used to override the default precedence of operators in an expression

**Answer:** CE

**NEW QUESTION 41**

Which two statements are true about the DUAL table? (Choose two.)

- A. It can be accessed only by the SYS user
- B. It consists of a single row and single column of VARCHAR2 data type
- C. It can display multiple rows but only a single column
- D. It can be used to display only constants or pseudo columns
- E. It can be accessed by any user who has the SELECT privilege in any schema
- F. It can display multiple rows and columns

**Answer:** AB

**NEW QUESTION 46**

Examine the description of the EMPLOYEES table:

Name	Null?	Type
EMP_ID	NOT NULL	NUMBER
EMP_NAME		VARCHAR2 (40)
DEPT_ID		NUMBER (2)
SALARY		NUMBER (8, 2)
JOIN_DATE		DATE

Which query is valid?

- A. SELECT dept\_id, AVG(MAX(salary)) FROM employees GROUP BY dept\_id;
- B. SELECT dept\_id, join\_date, SUM(salary) FROM employees GROUP BY dept\_id;
- C. SELECT dept\_id, join\_date, SUM(salary) FROM employees GROUP BY dept\_id, join\_date;

D. SELECT dept\_id, MAX(AVG(salary)) FROM employees GROUP BY dept\_id;

**Answer:** B

**NEW QUESTION 50**

Which two are true about shrinking a segment online? (Choose two.)

- A. It is not possible to shrink either indexes or Index Organized Tables (IOTs)
- B. It always eliminates all migrated rows if any exist in the table
- C. To shrink a table it must have a PRIMARY KEY constraint
- D. To shrink a table it must have a UNIQUE KEY constraint
- E. To shrink a table it must have row movement enabled
- F. It must be in a tablespace that uses Automatic Segment Space Management (ASSM)

**Answer:** CE

**NEW QUESTION 53**

You execute this command:

```
CREATE SMALLFILE TABLESPACE sales  
DATAFILE '/u01/app/oracle/sales01.dbf' SIZE 5G  
SEGMENT SPACE MANAGEMENT AUTO;
```

Which two actions must you take to ensure UNDOTBS01 is used as the default UNDO tablespace? (Choose two.)

- A. It must be smaller than the smallest BIGFILE tablespace
- B. Free space is managed using freelists
- C. Any data files added to the tablespace must have a size of 5 gigabytes
- D. It uses the database default blocksize
- E. It is a locally managed tablespace

**Answer:** DE

**NEW QUESTION 57**

In one of your databases, the user HR has the password HRMGR.

You want to connect to a database instance whose listener listens on port 1531 by using this statement: CONNECT HR/HRMGR@orcl

No name server is used.

Which statement is true about ORCL?

- A. It must be the value of the SERVICE\_NAMES parameter on the client side
- B. It must resolve to a valid connect descriptor in the server's tnsnames.ora file
- C. It must resolve to a valid connect descriptor in the client's tnsnames.ora file
- D. It must be the name of the database to whose instance HR wishes to connect
- E. It must be the name of the server running the database to whose instance HR wishes to connect

**Answer:** E

**NEW QUESTION 60**

Which two statements are true about Enterprise Manager Database Express? (Choose two.)

- A. It is available only when the database is open
- B. It can be used to perform database recovery
- C. The same port number can be used for Database Express configurations for databases on different hosts
- D. It can be used to switch a database into ARCHIVELOGMODE
- E. The same port number can be used for multiple Database Express configurations for multiple databases on the same host

**Answer:** DE

**NEW QUESTION 64**

Which three statements are true about the Oracle Data Dictionary? (Choose three.)

- A. Data dictionary views are created by joins of dictionary base tables and DBA-defined tables
- B. The data dictionary is created and maintained by the database administrator
- C. Views with the same name but different prefixes, such as CDB, DBA, ALL and USER, reference the same base tables from the data dictionary
- D. Base tables can be queried directly
- E. It is owned by the SYSTEM user
- F. Usernames of all users including database administrators are stored in the data dictionary

**Answer:** CDF

**NEW QUESTION 68**

A script abc.sql must be executed to perform a job.

A database user HR, who is defined in this database, executes this command:

```
$ sqlplus hr/hr@orcl @abc.sql
```

 What will happen upon execution?

- A. The command succeeds and HR will be connected to the orcl and abc.sql databases
- B. The command succeeds and HR will be connected to the orcl database instance, and the abc.sql script will be executed
- C. The command fails because the script must refer to the full path name
- D. The command fails and reports an error because @ is used twice

**Answer: B**

**NEW QUESTION 71**

Which two are true about a SQL statement using SET operators such as UNION? (Choose two.)

- A. The data type group of each column returned by the second query must match the data type group of the corresponding column returned by the first query.
- B. The number, but not names, of columns must be identical for all SELECT statements in the query.
- C. The data type of each column returned by the second query must exactly match the data type of the corresponding column returned by the first query.
- D. The names and number of columns must be identical for all SELECT statements in the query.
- E. The data type of each column returned by the second query must be implicitly convertible to the data type of the corresponding column returned by the first query.

**Answer: AC**

**NEW QUESTION 76**

Which three statements are true about the DESCRIBE command? (Choose three.)

- A. It displays the PRIMARY KEY constraint for any column or columns that have that constraint
- B. It can be used from SQL Developer
- C. It displays the NOT NULL constraint for any columns that have that constraint
- D. It can be used to display the structure of an existing view
- E. It displays all constraints that are defined for each column
- F. It can be used only from SQL \*Plus

**Answer: CDF**

**NEW QUESTION 81**

In one of your databases, user KING is:

- \1. Not a DBA user
  - \2. An operating system (OS) user
- Examine this command and its output:

```
SHOW PARAMETER OS_AUTHENT_PREFIX

NAME                                TYPE                                VALUE
-----                                -                                -
os_authent_prefix                    string
```

What must you do so that KING is authenticated by the OS when connecting to the database instance?

- A. Set OS\_AUTHENT\_PREFIX to OPS\$
- B. Have the OS administrator add KING to the OSDBA group
- C. Grant DBA to KING
- D. Unset REMOTE\_LOGIN\_PASSWORDFILE
- E. Alter user KING to be IDENTIFIED EXTERNALLY

**Answer: D**

**NEW QUESTION 86**

You want to use table compression suitable for OLTP that will:

- > Compress rows for all DML statements on that table
- > Minimize the overheads associated with compression

Which compression option is best suited for this?

- A. COLUMN STORE COMPRESS FOR QUERY LOW
- B. ROW STORE COMPRESS BASIC
- C. COLUMN STORE COMPRESS FOR ARCHIVE LOW
- D. COLUMN STORE COMPRESS FOR ARCHIVE HIGH
- E. ROW STORE COMPRESS ADVANCED

**Answer: E**

**NEW QUESTION 91**

A database is configured to use automatic undo management with temporary undo enabled. An UPDATE is executed on a temporary table. Where is the UNDO stored?

- A. in the undo tablespace
- B. in the SYSAUX tablespace
- C. in the SGA
- D. in the PGA
- E. in the temporary tablespace

**Answer: A**

**NEW QUESTION 92**

The ORCL database has RESUMABLE TIMEOUT = 7200 and DEFERRED\_SEGMENT\_CREATION = FALSE  
User U1 has a 1 MB quota in tablespace DATA. U1 executes this command:

SQL> CREATE TABLE t1 AS

(SELECT object\_name, sharing, created FROM dba\_objects);

U1 complains that the command is taking too long to execute.

In the alert log, the database administrator (DBA) finds this: 2017-03-06T12:15:17.183438+05:30

statement in resumable session 'User U1(136), Session 1, Instance 1' was suspended due to ORA-01536: space quota exceeded for tablespace 'DATA'

Which are three actions any one of which the DBA could take to resume the session? (Choose three.)

- A. Add a data file to DATA
- B. Drop other U1 objects in DATA
- C. Increase U1's quota sufficiently in DATA
- D. Set DEFERRED\_SEGMENT\_CREATION to TRUE
- E. Grant UNLIMITED TABLESPACE to U1
- F. Set AUTOEXTEND ON for data files in DATA

**Answer:** CDF

**NEW QUESTION 95**

.....

## Thank You for Trying Our Product

\* 100% Pass or Money Back

All our products come with a 90-day Money Back Guarantee.

\* One year free update

You can enjoy free update one year. 24x7 online support.

\* Trusted by Millions

We currently serve more than 30,000,000 customers.

\* Shop Securely

All transactions are protected by VeriSign!

**100% Pass Your 1z0-082 Exam with Our Prep Materials Via below:**

<https://www.certleader.com/1z0-082-dumps.html>