



Cisco

Exam Questions 300-815

Implementing Cisco Advanced Call Control and Mobility Services (CLACCM)

About ExamBible

[Your Partner of IT Exam](#)

Found in 1998

ExamBible is a company specialized on providing high quality IT exam practice study materials, especially Cisco CCNA, CCDA, CCNP, CCIE, Checkpoint CCSE, CompTIA A+, Network+ certification practice exams and so on. We guarantee that the candidates will not only pass any IT exam at the first attempt but also get profound understanding about the certificates they have got. There are so many alike companies in this industry, however, ExamBible has its unique advantages that other companies could not achieve.

Our Advances

* 99.9% Uptime

All examinations will be up to date.

* 24/7 Quality Support

We will provide service round the clock.


* 100% Pass Rate

Our guarantee that you will pass the exam.

* Unique Gurantee

If you do not pass the exam at the first time, we will not only arrange FULL REFUND for you, but also provide you another exam of your claim, ABSOLUTELY FREE!

NEW QUESTION 1



Refer to the exhibit. In an active SIP call between phone user A and phone user B, phone A initiates a call transfer to phone user C. Which two scenarios are correct? (Choose two.)

- A. Phone_A sends a SIP-REFER message to the Cisco Unified Communications Manager with Phone_C information in the Refer-To section.
- B. Phone_B sends a SIP-REFER message to the Cisco Unified CM with Phone_C information in the Refer-To section.
- C. As soon as Phone_A presses the Transfer button for the first time, Phone_B hears the MOH and the MOH audio is chosen from Phone_B User Hold MOH Audio Source settings.
- D. As soon as Phone_A presses the Transfer button for the first time, Phone_B hears the music on hold and the MOH audio is chosen from Phone_A Network Hold MOH Audio Source settings.
- E. As soon as Phone_A presses the Transfer button for the first time, Phone_B hears the MOH and the MOH audio is chosen from Phone_A User Hold MOH Audio Source settings.

Answer: AC

NEW QUESTION 2

```
SIP/2.0 200 OK
[.truncated..]
v=0
o=UAC 6107 7816 IN IP4 10.10.10.11
s=SIP Call
c=IN IP4 10.10.10.11
t=0 0
m=audio 8190 RTP/AVP 18 110
c=-IN IP4 10.10.10.11
a=rtpmap: 18 G729/8000
a=fmtp: 18 annexb=no
a=rtpmap:110 telephone-event/8000
a=fmtp: 110 0-16
a=ptime: 20

ACK sip:+123456789@10.10.20.20:5060 SIP/2.0
[.truncated..]
v=0
o=UAS 4692 9609 IN IP4 10.10.10.10
s=SIP Call
c=IN IP4 10.10.10.10
t=0 0
m=audio 8056 RTP/AVP 18
c=IN IP4 10.10.10.10
a=rtpmap: 18 G729/8000
a=fmtp: 18 annexb=no
a=ptime:20
```

Refer to the exhibit. Users report that when they dial to Cisco Unity Connection from an external network, they cannot enter any digits. Assuming only in-band DTMF is supported, what is a reason for this malfunction?

- A. The negotiated RTP port is outside of the range described by RFC, so inband DTMFs do not work.
- B. There is SIP Delayed Offer
- C. DTMF is supported only in Early Offer.
- D. The rtpmap:0 value for the negotiated codec is marking DTMF as inactive.
- E. No DTMF is negotiated.

Answer: D

NEW QUESTION 3

What is first preference condition matched in a SIP-enabled incoming dial peer?

- A. incoming uri
- B. target carrier-id
- C. answer-address
- D. incoming called-number

Answer: A

NEW QUESTION 4

Cisco SIP IP telephony is implemented on two floors of your company. Afterward, users report intermittent voice issues in calls established between floors. All calls

are established, and sometimes they work well, but sometimes there is oneway audio or no audio. You determine that there is a firewall between the floors, and the administrator reports that it is allowing SIP signaling and UDP ports from 20000 to 22000 bidirectionally. What are two possible solutions? (Choose two.)

- A. Go to the SIP profile assigned to these IP phones in Cisco Unified CM and change the range of media ports to 16384-32767
- B. Ask the firewall administrator to change the ports to TCP.
- C. Ask the firewall administrator to change the range of UDP ports to 16384-32767.
- D. Go to the SIP profile assigned to these IP phones in Cisco Unified CM and change the range of media ports to 20000-22000.
- E. Go to System Parameters in Cisco Unified Communications Manager and change the range of media ports to 20000-22000.

Answer: AC

NEW QUESTION 5

Which section under the Real-Time Monitoring Tool allows for reviewing the call flow and signaling for a SIP call in real time?

- A. Analysis Manager > Inventory > Trace File Repositories
- B. System > Tools > Trace and Log Central
- C. Voice/Video > Session Trace Log View > Real Time Data
- D. Voice/Video > Session Trace Log View > Open From Local Disk

Answer: C

NEW QUESTION 6

A support engineer is troubleshooting a voice network. When conducting a search for call setup details related to calling search space issues, which trace files should be investigated?

- A. CallManager traces
- B. CTI Manager traces
- C. Cisco IP Manager Assistant
- D. Call logs

Answer: A

NEW QUESTION 7

Which top-level IOS command is needed to begin the configuration of a Cisco Unified Communications Manager Express gateway to enable phones to be registered via SIP?

- A. allow-connections sip to sip
- B. voice service voip
- C. voice register global
- D. voice register dn

Answer: C


NEW QUESTION 8

For s SIP to SIP call flow, when does Cisco Unified Border Element require transcoding resources for DTMF?

- A. interworking between an OOB method and RFC2833 for flow-around calls
- B. interworking between h245-signal and rtp-nte
- C. interworking between an OOB method and RFC2833 for flow-through calls
- D. interworking between h245-alpha numeric and sip-kpml

Answer: A

NEW QUESTION 9



Refer to the exhibit. An administrator is troubleshooting why users are not hearing audio when dialing long distance numbers across their Cisco Unified Border Element. The customer's carrier has a requirement that dialing long distance requires an access code to be entered. Looking at the exhibit, what two actions can be taken to correct signaling? (Choose two.)

- A. Enable PRACK.

- B. Enable Early Offer on the Cisco Unified Border Element.
- C. Enable the supplementary-service media-renegotiate command.
- D. Enable Media Flow Around
- E. Enable Mid-Call Signaling Consumption.

Answer: AB

NEW QUESTION 10

An engineer must route all SIP calls in the form of <user>@example.com to the SIP trunk gateway corporate local. Which two SIP route patterns can be used to accomplish this task? (Choose two.)

- A. example.com@gateway.corporate.local
- B. *@example.com
- C. gateway.corporate.local
- D. example.com
- E. *.*

Answer: BE

NEW QUESTION 10

Which two statements are correct with respect to the Client Matter Code setting in the route pattern configuration? (Choose two.)

- A. The Client Matter Code feature does not support overlap sending because the Cisco Unified CM cannot determine when to prompt the user for the code.
- B. If you check the Allow Overlap Sending check box, the Require Client Matter Code check box becomes disabled.
- C. If you check the Allow Overlap Sending check box, you can also check the Require Client Matter Code check box.
- D. The Client Matter Code feature does support overlap sending because the Cisco Unified Communications Manager can determine when to prompt the user for the code.
- E. The Client Matter Code has the option to configure Authorization Level such as in the Forced Authorization Code.

Answer: AB

NEW QUESTION 12

A network engineer designs a new dial plan and wants to block a certain range of numbers (8135100 through 8135105). What is the most specific route pattern that can be configured to block only the numbers in this range?

- A. 813510[012345]
- B. 813510[12345]
- C. 813510[^0-5]
- D. 81XXXXX

Answer: A

NEW QUESTION 15

Which two descriptions of the Standard Local Route Group deployment are true? (Choose two.)

- A. can be associated under the route group
- B. can be associated only under the route list
- C. chooses the route group that is configured under the device pool of the calling-party device
- D. chooses the route group that is configured under the device pool of the called-party device
- E. can be assigned directly to the route pattern

Answer: BD

NEW QUESTION 16

Refer to the exhibit. An engineer configures Cisco Unified Border Element to connect the enterprise VoIP network with a SIP telephony provider. Calls are not working in either direction. What must be configured in the dial peer 1 to fix the issue?

- A. address 555
- B. codec g729
- C. session-protocol sipv2
- D. incoming called number 555.....

Answer: D

NEW QUESTION 17

After configuring a Cisco CallManager Express with Cisco Unity Express, inbound calls from the PSTN SIP trunk receive a ring tone for 20 seconds and then a busy signal instead of voicemail. Which configuration fixes this problem?

- A. Router(config)# voice service voipRouter(config-voi-serv)#allow-connections h323 to h323
- B. Router(config)#dial-peer voice 2 voipRouter(config-dial-peer)#no vad
- C. Router(config)# voice service voipRouter(config-voi-serv)#allow-connections voice-mail mod
- D. Router(config)# voice service voipRouter(config-voi-serv)#no supplementary-service sip moved-temporarily

Answer: A

NEW QUESTION 18

In Cisco Unified Communications Manager, which tool do you use to check SIP traces?

- A. MTP
- B. CCSIP
- C. RTMT
- D. OS Administration Page

Answer: C

NEW QUESTION 22

If all patterns below are configured in Cisco Unified Communications Manager which would be used when dialing the pattern "123"?

- A. 12!
- B. 12X (urgent priority set)
- C. 1XX (urgent Priority Set)
- D. 12[2-5]

Answer: B

NEW QUESTION 23

Which two types of distribution algorithm are within a line group? (Choose two.)

- A. random
- B. circular
- C. highest preference
- D. top down
- E. bottom up

Answer: BD


NEW QUESTION 28

An engineer is configuring a call park feature in Cisco Unified Communications Manager Express. Which command does the engineer use to ensure that the call is reverted to the user after 60 seconds?

- A. R2(config-ephone-dn)#park reservation-group 60
- B. R2(config-ephone-dn)#park-slot timeout 60 limit 2 recall alternate 3002
- C. R2(config-ephone-dn)#park reservation-group 1
- D. R2(config-ephone-dn)#park-slot timeout 30 limit 2 recall alternate 3002

Answer: B

NEW QUESTION 32



Refer to the exhibit. How many maximum hops can an ILS update traverse?

- A. 3
- B. 6
- C. 9
- D. 12

Answer: A

NEW QUESTION 36

An administrator is configuring a cluster for ILS and wants to limit the amount of entities that Cisco Unified Communications Manager can write to the database for data that is learned through ILS. Which service parameter is used to adjust this limit?

- A. ILS Max Number of Learned Objects in Database
- B. ILS Active Learned Object Upper Limit
- C. Global Data Service Parameter Limit
- D. Imported Dial Plan Replication Database Object Lower Limit

Answer: A

NEW QUESTION 38

Which configuration element of a hunt group allows for changing Calling Party Transformations settings?

- A. line group
- B. hunt pilot
- C. route group
- D. hunt list

Answer: B

NEW QUESTION 40

Which two types of authentication are supported for the configuration of Intercluster Lookup Service? (Choose two.)

- A. TokenID
- B. username and secret key
- C. TLS certificates
- D. passwords
- E. FQDN of the servers defined in DNS

Answer: CD

NEW QUESTION 44

What is the relationship between partition, time schedule, and time period in Time-of-Day routing in Cisco Unified Communications Manager?

- A. A partition can have multiple time schedules assigned
- B. A time schedule contains one or more time periods.
- C. A partition can have one time schedule assigned
- D. A time schedule contains one or more time periods.
- E. A partition can have multiple time schedules assigned
- F. A time schedule contains only one time period.
- G. A partition can have one time schedule assigned
- H. A time schedule contains only one time period.

Answer: A

NEW QUESTION 47

What are the elements for Device Mobility configuration?

- A. physical location, device pool, and Device Mobility group
- B. device pool, Device Mobility group, and region
- C. physical location
- D. Device Mobility group, and region
- E. device pool, Device Mobility group, and Cisco IP phone

Answer: A

NEW QUESTION 49

Which services are needed to successfully implement Cisco Extension Mobility in a standalone Cisco Unified Communications Manager server?

- A. Cisco Extended Functions, Cisco Extension Mobility, and Cisco AXL Web Service
- B. Cisco CallManager, Cisco TFTP, and Cisco CallManager SNMP Service
- C. Cisco CallManager, Cisco TFTP, and Cisco Extension Mobility
- D. Cisco TAPS Service, Cisco TFTP, and Cisco Extension Mobility

Answer: C

NEW QUESTION 53

.....

Relate Links

100% Pass Your 300-815 Exam with ExamBible Prep Materials

<https://www.exambible.com/300-815-exam/>

Contact us

We are proud of our high-quality customer service, which serves you around the clock 24/7.

Viste - <https://www.exambible.com/>