



**Oracle**

## **Exam Questions 1z0-808**

Java SE 8 Programmer I

**NEW QUESTION 1**

Which one of the following code examples uses valid Java syntax?

- A.
- ```
public class Boat {  
  
    public static void main (String [] args) {  
        System.out.println ("I float.");  
    }  
}
```
- B.
- ```
public class Cake {  
    public static void main (String [] ) {  
        System.out.println ("Chocolate");  
    }  
}
```
- C.
- ```
public class Dog {  
    public void main (String [] args) {  
        System.out.println ("Squirrel.");  
    }  
}
```
- D.
- ```
public class Bank {  
    public static void main (String () args) {  
        System.out.println ("Earn interest.");  
    }  
}
```

- A. Option A  
B. Option B  
C. Option C  
D. Option D

**Answer:** A

**NEW QUESTION 2**

Given the following classes:

```
public class Employee {  
    public int salary;  
}  
  
public class Manager extends Employee {  
    public int budget;  
}  
  
public class Director extends Manager {  
    public int stockOptions;  
}
```

And given the following main method:

```
public static void main(String[] args) {  
    Employee employee = new Employee();  
    Manager manager = new Manager();  
    Director director = new Director();  
    //line n1  
}
```

Which two options fail to compile when placed at line n1 of the main method? (Choose two.)

- A. employee.salary = 50\_000;
- B. director.salary = 80\_000;
- C. employee.budget = 200\_000;
- D. manager.budget = 1\_000\_000;
- E. manager.stockOption = 500;
- F. director.stockOptions = 1\_000;

**Answer:** CE

### NEW QUESTION 3

Given the code fragment:

```
public static void main (String[] args) {  
    String[] arr = {"Hi", "How", "Are", "You"};  
    List<String> arrList = new ArrayList<>(Arrays.asList(arr));  
    if (arrList.removeIf((String s) -> (return s.length() <= 2;))) {  
        System.out.println(s + "removed")'  
    }  
}
```

What is the result?

- A. Compilation fails.
- B. Hi removed
- C. An UnsupportedOperationException is thrown at runtime.
- D. The program compiles, but it prints nothing.

**Answer:** A

### NEW QUESTION 4

Given:

```
public class Test {  
    public static void main(String[] args) {  
        int x = 1;  
        int y = 0;  
        if(x++ > ++y) {  
            System.out.print("Hello ");  
        } else {  
            System.out.print("Welcome ");  
        }  
        System.out.print("Log " + x + ":" + y);  
    }  
}
```

What is the result?

- A. Hello Log 1:0
- B. Hello Log 2:1
- C. Welcome Log 2:1
- D. Welcome Log 1:0

**Answer:** C

### NEW QUESTION 5

Given this code for a Planet object:

```
public class Planet {
    public String name;
    public int moons;

    public Planet(String name, int moons) {
        this.name = name;
        this.moons = moons;
    }
}
```

And this method:

```
public static void main(String[] args){
    Planet[] planets = {
        new Planet("Mercury", 0),
        new Planet("Venus", 0),
        new Planet("Earth", 1),
        new Planet("Mars", 2)
    };

    System.out.println(planets);
    System.out.println(planets[2].name);
    System.out.println(planets[2].moons);
}
```

What is the output?

- A
- ```
planets
Earth
1
```
- B
- ```
[LPlanets.Planet;@15db9742
Earth
1
```
- C
- ```
[LPlanets.Planet;@15db9742
Planets.Planet@6d06d69c
1
```
- D
- ```
[LPlanets.Planet;@15db9742
Planets.Planet@6d06d69c
[LPlanets.Moon;@7852e922
```
- E
- ```
[LPlanets.Planet;@15db9742
Venus
0
```

- A. Option A  
 B. Option B  
 C. Option C  
 D. Option D  
 E. Option E

**Answer: C**

#### NEW QUESTION 6

Which two are benefits of polymorphism? (Choose two.)

- A. Faster code at runtime  
 B. More efficient code at runtime  
 C. More dynamic code at runtime  
 D. More flexible and reusable code  
 E. Code that is protected from extension by other classes

**Answer:** BD

#### NEW QUESTION 7

Which statement is true about the switch statement?

- A. It must contain the default section.
- B. The break statement, at the end of each case block, is mandatory.
- C. Its case label literals can be changed at runtime.
- D. Its expression must evaluate to a single value.

**Answer:** D

#### NEW QUESTION 8

Given the code fragment:

```
public static void main(String[] args) {  
    int ii = 0;  
    int jj = 7;  
    for (ii = 0; ii < jj - 1; ii = ii + 2) {  
        System.out.print(ii + " ");  
    }  
}
```

What is the result?

- A. 2 4
- B. 0 2 4 6
- C. 0 2 4
- D. Compilation fails

**Answer:** C

#### NEW QUESTION 9

Which two statements are true about Java byte code? (Choose two.)

- A. It can be serialized across network.
- B. It can run on any platform that has a Java compiler.
- C. It can run on any platform.
- D. It has ".java" extension.
- E. It can run on any platform that has the Java Runtime Environment.

**Answer:** AE

#### NEW QUESTION 10

This grid shows the state of a 2D array:

|   |   |   |
|---|---|---|
| 0 | 0 |   |
|   | X | 0 |
| X |   | X |

The grid is created with this code:

```
char[][] grid = new char[3][3];  
grid[1][1] = 'X';  
grid[0][0] = '0';  
grid[2][0] = 'X';  
grid[0][1] = '0';  
grid[2][2] = 'X';  
grid[1][2] = '0';  
//line n1
```

Which line of code, when inserted in place of //line n1, adds an X into the grid so that the grid contains three consecutive Xs?

- A. grid[2][1] = 'X';
- B. grid[3][2] = 'X';
- C. grid[3][1] = 'X';
- D. grid[2][3] = 'X';

**Answer:** D

#### NEW QUESTION 10

Given the code fragment:

```
public static void main(String[] args) {  
    LocalDate date = LocalDate.of(2012, 1, 30);  
    date.plusDays(10);  
    System.out.println(date);  
}
```



What is the result?

- A. 2012-02-10 00:00
- B. 2012-01-30
- C. 2012-02-10
- D. A DateTimeException is thrown at runtime.

**Answer: B**

**Explanation:**



#### NEW QUESTION 15

Given:

```
class Patient {
    String name;
    public Patient (String name) {
        this.name = name;
    }
}
```

And the code fragment:

```
8. public class Test {
9.     public static void main (String [] args) {
10.         List ps = new ArrayList ();
11.         Patient p2 = new Patient ("Mike");
12.         ps.add(p2);
13.
14.         // insert code here
15.
16.         if (f >= 0) {
17.             System.out.print ("Mike Found");
18.         }
19.     }
20. }
```

Which code fragment, when inserted at line 14, enables the code to print Mike Found?

A

```
int f = ps.indexOf (p2);
```

B

```
int f = ps.indexOf (Patient ("Mike") );
```

C

```
int f = ps.indexOf (new Patient "Mike") );
```

D

```
Patient p = new Patient("Mike");  
int f = ps.indexOf(p)
```

- A. Option A
- B. Option B
- C. Option C
- D. Option D

Answer: A

### NEW QUESTION 19

Given:

```
public class Test {  
    public static void main(String[] args) {  
        boolean a = new Boolean(Boolean.valueOf(args[0]));  
        boolean b = new Boolean(args[1]);  
        System.out.println(a + " " + b);  
    }  
}
```

And given the commands:

```
javac Test.java  
java Test 1 null
```

What is the result?

- A. 1 null
- B. true false
- C. false false
- D. true true
- E. A ClassCastException is thrown at runtime.

Answer: D

### NEW QUESTION 23

Given the code fragment:

```
public class Employee {  
    String name;  
    boolean contract;  
    double salary;  
    Employee() {  
        // line n1  
    }  
    public String toString(){  
        return name + ":" + contract + ":" + salary;  
    }  
    public static void main(String[] args) {  
        Employee e = new Employee();  
        // line n2  
        System.out.print(e);  
    }  
}
```

Which two modifications, when made independently, enable the code to print Joe:true: 100.0? (Choose two.)

- ☐ A) Replace line n2 with:  
e.name = "Joe";  
e.contract = true;  
e.salary = 100;
- ☐ B) Replace line n2 with:  
this.name = "Joe";  
this.contract = true;  
this.salary = 100;
- ☐ C) Replace line n1 with:  
this.name = new String("Joe");  
this.contract = new Boolean(true);  
this.salary = new Double(100);
- ☐ D) Replace line n1 with:  
name = "Joe";  
contract = TRUE;  
salary = 100.0f;
- ☐ E) Replace line n1 with:  
this("Joe", true, 100);

- A. Option A  
B. Option B  
C. Option C  
D. Option D  
E. Option E

**Answer:** AC

#### NEW QUESTION 25

Given:

```
interface Readable {  
    public void readBook();  
    public void setBookMark();  
}  
  
abstract class Book implements Readable {    // line n1  
    public void readBook() { }  
    // line n2  
}  
  
class EBook extends Book {                    // line n3  
    public void readBook() { }  
    // line n4  
}
```

And given the code fragment: Book book1 = new EBook(); book1.readBook();  
Which option enables the code to compile?

- ☐ A) Replace the code fragment at line n1 with:  
class Book implements Readable {
- ☐ B) At line n2 insert:  
public abstract void setBookMark();
- ☐ C) Replace the code fragment at line n3 with:  
abstract class EBook extends Book {
- ☐ D) At line n4 insert:  
public void setBookMark() { }

- A. Option A  
B. Option B  
C. Option C  
D. Option D

**Answer:** D

#### NEW QUESTION 30

Given:



```
class X {
    int i;
    static int j;
    public static void main(String[] args) {
        X x1 = new X();
        X x2 = new X();
        x1.i = 3;
        x1.j = 4;
        x2.i = 5;
        x2.j = 6;
        System.out.println(
            x1.i + " " +
            x1.j + " " +
            x2.i + " " +
            x2.j);
    }
}
```

What is the result?

- A. 3 4 5 6
- B. 3 4 3 6
- C. 5 4 5 6
- D. 3 6 5 6

**Answer:** D

**Explanation:**

```
3 6 5 6
Completed with exit code: 0
```

#### NEW QUESTION 31

Given:

```
interface I {
    public void displayI();
}
abstract class C2 implements I {
    public void displayC2() {
        System.out.print("C2");
    }
}
class C1 extends C2 {
    public void displayI() {
        System.out.print("C1");
    }
}
```

And the code fragment:

```
C2 obj1 = new C1();
I obj2 = new C1();

C2 s = (C2) obj2;
I t = obj1;

t.displayI();
s.displayC2();
```

What is the result?

- A. C1C2
- B. C1C1
- C. Compilation fails.
- D. C2C2

**Answer:** A

**Explanation:**

lund

src

App.java

```

1
2 interface I {
3     public void displayI();
4 }
5 abstract class C2 implements I {
6     public void displayC2() {
7         System.out.print("C2");
8     }
9 }
10 class C1 extends C2 {
11     public void displayI() {
12         System.out.print("C1");
13     }
14
15 }
16
17 public class App {
18     public static void main(String[] args) {
19         C2 obj1 = new C1();
20         I obj2 = new C1();
21
22         C2 s = (C2) obj2;
23         I t = obj1;
24
25         t.displayI();
26         s.displayC2();
27     }
28
29 }

```

Console 1

Console 2

Console 3

Console 4

C1C2  
Completed with exit code: 0

#### NEW QUESTION 32

Given the code fragment:

```
abstract class Planet {  
    protected void revolve() {                //line n1  
    }  
  
    abstract void rotate();                    //line n2  
}  
  
class Earth extends Planet {  
    void revolve() {                            //line n3  
    }  
  
    protected void rotate() {                  //line n4  
    }  
}
```

Which two modifications, made independently, enable the code to compile? (Choose two.)

- A. Make the method at line n1 public.
- B. Make the method at line n2 public.
- C. Make the method at line n3 public.
- D. Make the method at line n3 protected.
- E. Make the method at line n4 public.

**Answer:** CD

#### NEW QUESTION 35

Given:

Base.java:

```
class Base {  
    public void test(){  
        System.out.println("Base ");  
    }  
}
```

DerivedA.java:

```
class DerivedA extends Base {  
    public void test(){  
        System.out.println("DerivedA ");  
    }  
}
```

DerivedB.java:

```
class DerivedB extends DerivedA {  
    public void test(){  
        System.out.println("DerivedB ");  
    }  
    public static void main(String[] args) {  
        Base b1 = new DerivedB();  
        Base b2 = new DerivedA();  
        Base b3 = new DerivedB();  
        Base b4 = b3;  
        b1 = (Base) b2;  
        b1.test();  
        b4.test();  
    }  
}
```

What is the result?

- A. BaseDerivedA
- B. BaseDerivedB
- C. DerivedBDerivedB
- D. DerivedBDerivedA
- E. A ClassCastException is thrown at runtime.

**Answer:** D

#### NEW QUESTION 40

Given the code fragment:

```
7.  StringBuilder sb1 = new StringBuilder("Duke");  
8.  String str1 = sb1.toString();  
9.  // insert code here  
10. System.out.print(str1 == str2);
```

Which code fragment, when inserted at line 9, enables the code to print true?

- A. String str2 = str1;
- B. String str2 = new String(str1);
- C. String str2 = sb1. toString();
- D. String str2 = "Duke";

**Answer:** A

#### NEW QUESTION 41

Given:

```
class Test {  
    public static void main (String [] args) {  
        int numbers [ ];  
        numbers = new int [2];  
        numbers [0] = 10;  
        numbers [1] = 20;  
  
        numbers = new int [4];  
        numbers [2] = 30;  
        numbers [3] = 40;  
        for (int x : numbers) {  
            System.out.print (" " + x) ;  
        }  
    }  
}
```

What is the result?

- A. 10 20 30 40
- B. 0 0 30 40
- C. Compilation fails.
- D. An exception is thrown at runtime.

**Answer:** C

#### NEW QUESTION 43

What is the name of the Java concept that uses access modifiers to protect variables and hide them within a class?

- A. Encapsulation
- B. Inheritance
- C. Abstraction
- D. Instantiation
- E. Polymorphism

**Answer:** A

#### Explanation:

Using the private modifier is the main way that an object encapsulates itself and hide data from the outside world.

#### NEW QUESTION 44

Given:

```
public class Test {
    int x, y;

    public Test(int x, int y) {
        initialize(x, y);
    }

    public void initialize(int x, int y) {
        this.x = x * x;
        this.y = y * y;
    }

    public static void main(String[] args) {
        int x = 3, y = 5;
        Test obj = new Test(x, y);
        System.out.println(x + " " + y);
    }
}
```

What is the result?

- A. Compilation fails.
- B. 3 5
- C. 0 0
- D. 9 25

**Answer: B**

#### NEW QUESTION 46

Given:

```
class Student {
    String name;
    public Student(String name) {
        this.name = name;
    }
}

public class Test {
    public static void main(String[] args) {
        Student[] students = new Student[3];
        students[1] = new Student("Richard");
        students[2] = new Student("Donald");
        for (Student s : students) {
            System.out.println("" + s.name);
        }
    }
}
```

What is the result?

- A. nullRichardDonald
- B. RichardDonald
- C. Compilation fails.
- D. An `ArrayIndexOutOfBoundsException` is thrown at runtime.
- E. A `NullPointerException` is thrown at runtime.

**Answer: E**

#### NEW QUESTION 48

Which three are advantages of the Java exception mechanism? (Choose three.)

- A. Improves the program structure because the error handling code is separated from the normal program function
- B. Provides a set of standard exceptions that covers all possible errors
- C. Improves the program structure because the programmer can choose where to handle exceptions
- D. Improves the program structure because exceptions must be handled in the method in which they occurred
- E. Allows the creation of new exceptions that are customized to the particular program being created

**Answer: ACE**

#### NEW QUESTION 52

Given the code fragment:



```
String[] strs = {"A", "B"};
int idx = 0;
for (String s : strs) {
    strs[idx].concat(" element " + idx);
    idx++;
}
for (idx = 0; idx < strs.length; idx++) {
    System.out.println(strs[idx]);
}
```

What is the result?

- A. AB
- B. A element 0B element 1
- C. A NullPointerException is thrown at runtime.
- D. A 0B 1

**Answer: C**

#### NEW QUESTION 57

Given:

```
class Vehicle {
    int x;
    Vehicle() {
        this(10); // line n1
    }
    Vehicle(int x) {
        this.x = x;
    }
}

class Car extends Vehicle {
    int y;
    Car() {
        super();
        this(20); // line n2
    }
    Car(int y) {
        this.y = y;
    }
    public String toString() {
        return super.x + ":" + this.y;
    }
}
```

And given the code fragment:

And given the code fragment:

```
Vehicle y = new Car();
System.out.println(y);
```

What is the result?

- A. 10:20
- B. 0:20
- C. Compilation fails at line n1
- D. Compilation fails at line n2

**Answer: D**

#### NEW QUESTION 61

Which three statements are true about the structure of a Java class? (Choose three.)

- A. A public class must have a main method.
- B. A class can have only one private constructors.
- C. A method can have the same name as a field.
- D. A class can have overloaded static methods.
- E. The methods are mandatory components of a class.
- F. The fields need not be initialized before use.

**Answer: ACE**

#### NEW QUESTION 62

.....

## Thank You for Trying Our Product

### We offer two products:

1st - We have Practice Tests Software with Actual Exam Questions

2nd - Questions and Answers in PDF Format

### 1z0-808 Practice Exam Features:

- \* 1z0-808 Questions and Answers Updated Frequently
- \* 1z0-808 Practice Questions Verified by Expert Senior Certified Staff
- \* 1z0-808 Most Realistic Questions that Guarantee you a Pass on Your FirstTry
- \* 1z0-808 Practice Test Questions in Multiple Choice Formats and Updatesfor 1 Year

**100% Actual & Verified — Instant Download, Please Click**  
**[Order The 1z0-808 Practice Test Here](#)**