

Cisco

Exam Questions 300-710

Securing Networks with Cisco Firepower (SNCF)



NEW QUESTION 1

Which two conditions are necessary for high availability to function between two Cisco FTD devices? (Choose two.)

- A. The units must be the same version
- B. Both devices can be part of a different group that must be in the same domain when configured within the FMC.
- C. The units must be different models if they are part of the same series.
- D. The units must be configured only for firewall routed mode.
- E. The units must be the same model.

Answer: AE

NEW QUESTION 2

On the advanced tab under inline set properties, which allows interfaces to emulate a passive interface?

- A. transparent inline mode
- B. TAP mode
- C. strict TCP enforcement
- D. propagate link state

Answer: D

NEW QUESTION 3

What are the minimum requirements to deploy a managed device inline?

- A. inline interfaces, security zones, MTU, and mode
- B. passive interface, MTU, and mode
- C. inline interfaces, MTU, and mode
- D. passive interface, security zone, MTU, and mode

Answer: C

NEW QUESTION 4

Which protocol establishes network redundancy in a switched Firepower device deployment?

- A. STP
- B. HSRP
- C. GLBP
- D. VRRP

Answer: A

NEW QUESTION 5

Which command is run on an FTD unit to associate the unit to an FMC manager that is at IP address 10.0.0.10, and that has the registration key Cisco123?

- A. configure manager local 10.0.0.10 Cisco123
- B. configure manager add Cisco123 10.0.0.10
- C. configure manager local Cisco123 10.0.0.10
- D. configure manager add 10.0.0.10 Cisco123

Answer: D

NEW QUESTION 6

Which object type supports object overrides?

- A. time range
- B. security group tag
- C. network object
- D. DNS server group

Answer: C

NEW QUESTION 7

Which Cisco Firepower rule action displays an HTTP warning page?

- A. Monitor
- B. Block
- C. Interactive Block
- D. Allow with Warning

Answer: C

NEW QUESTION 8

What is the result of specifying of QoS rule that has a rate limit that is greater than the maximum throughput of an interface?

- A. The rate-limiting rule is disabled.
- B. Matching traffic is not rate limited.
- C. The system rate-limits all traffic.
- D. The system repeatedly generates warnings.

Answer: B

NEW QUESTION 9

Which Firepower feature allows users to configure bridges in routed mode and enables devices to perform Layer 2 switching between interfaces?

- A. FlexConfig
- B. BDI
- C. SGT
- D. IRB

Answer: D

NEW QUESTION 10

Which two types of objects are reusable and supported by Cisco FMC? (Choose two.)

- A. dynamic key mapping objects that help link HTTP and HTTPS GET requests to Layer 7 application protocols.
- B. reputation-based objects that represent Security Intelligence feeds and lists, application filters based on category and reputation, and file lists
- C. network-based objects that represent IP address and networks, port/protocols pairs, VLAN tags, security zones, and origin/destination country
- D. network-based objects that represent FQDN mappings and networks, port/protocol pairs, VXLAN tags, security zones and origin/destination country
- E. reputation-based objects, such as URL categories

Answer: BC

NEW QUESTION 10

Which group within Cisco does the Threat Response team use for threat analysis and research?

- A. Cisco Deep Analytics
- B. OpenDNS Group
- C. Cisco Network Response
- D. Cisco Talos

Answer: D

NEW QUESTION 15

Which command-line mode is supported from the Cisco Firepower Management Center CLI?

- A. privileged
- B. user
- C. configuration
- D. admin

Answer: C

NEW QUESTION 17

Which two statements about deleting and re-adding a device to Cisco FMC are true? (Choose two.)

- A. An option to re-apply NAT and VPN policies during registration is available, so users do not need to re-apply the policies after registration is completed.
- B. Before re-adding the device in Cisco FMC, you must add the manager back in the device.
- C. No option to delete and re-add a device is available in the Cisco FMC web interface.
- D. The Cisco FMC web interface prompts users to re-apply access control policies.
- E. No option to re-apply NAT and VPN policies during registration is available, so users need to re-apply the policies after registration is completed.

Answer: DE

NEW QUESTION 18

Which two packet captures does the FTD LINA engine support? (Choose two.)

- A. Layer 7 network ID
- B. source IP
- C. application ID
- D. dynamic firewall importing
- E. protocol

Answer: BE

NEW QUESTION 20

Which Cisco Advanced Malware Protection for Endpoints policy is used only for monitoring endpoint actively?

- A. Windows domain controller
- B. audit

- C. triage
- D. protection

Answer: B

NEW QUESTION 21

Which connector is used to integrate Cisco ISE with Cisco FMC for Rapid Threat Containment?

- A. pxGrid
- B. FTD RTC
- C. FMC RTC
- D. ISEGrid

Answer: A

NEW QUESTION 23

.....

Thank You for Trying Our Product

We offer two products:

1st - We have Practice Tests Software with Actual Exam Questions

2nd - Questions and Answers in PDF Format

300-710 Practice Exam Features:

- * 300-710 Questions and Answers Updated Frequently
- * 300-710 Practice Questions Verified by Expert Senior Certified Staff
- * 300-710 Most Realistic Questions that Guarantee you a Pass on Your First Try
- * 300-710 Practice Test Questions in Multiple Choice Formats and Updates for 1 Year

100% Actual & Verified — Instant Download, Please Click
[Order The 300-710 Practice Test Here](#)