


## 1z0-083 Dumps

### Oracle Database Administration II

<https://www.certleader.com/1z0-083-dumps.html>



**NEW QUESTION 1**

Which four are true about duplicating a database using Recovery Manager (RMAN)? (Choose four.)

- A. Duplication can be done by having the auxiliary database instance pull backup sets from the target database instance.
- B. A connection to an auxiliary instance is always required.
- C. A subset of the target database can be duplicated.
- D. A new DBID is always created for the duplicated database.
- E. A connection to the recovery catalog instance is always required.
- F. A backup of the target database is always required.
- G. Duplication can be done by having the target database instance push copies to the auxiliary database instance.
- H. A connection to the target database instance is always required.

**Answer:** ABCG

**Explanation:**

A duplicate database is a copy of your target database. With the FOR STANDBY clause, it keeps the same unique database identifier (DBID); If FOR STANDBY not specified it creates a new DBID. The duplicate database can include the same content or only a subset from the source database. It can be in the same host or a separate host. The principal work of the duplication is performed by the auxiliary channels. These channels correspond to a server session on the auxiliary instance on the destination host for backup based duplication. For active database duplication the target channels perform the work of pushing data file copies to the auxiliary instance (if number of allocated target channels is greater than the number of allocated auxiliary channels).

**NEW QUESTION 2**

A container database (CDB) contains two pluggable databases PDB1 and PDB2.

The LOCAL\_UNDO\_ENABLED database property is set to FALSE in the CDB. Data file 24 of PDB2 was deleted and you need to restore and recover it.

The only RMAN backup that exists was created with the BACKUP DATABASE command while connected to CDB\$ROOT.

Which three are true? (Choose three.)

- A. Data file 24 can be recovered only while connected to PDB2.
- B. Data file 24 can be restored and recovered while connected to CDB\$ROOT.
- C. Data file 24 can be restored only while connected to CDB\$ROOT.
- D. Data file 24 can be restored only while connected to PDB2.
- E. Data file 24 can be recovered while connected to PDB2.
- F. Data file 24 can be recovered while connected to CDB\$ROOT.

**Answer:** BCF

**NEW QUESTION 3**

Which two are true about RMAN backups when using a media manager to write backups to tape when there are only two tape drives? (Choose two.)

- A. SBT tape compression can be used even if no RMAN compression is configured.
- B. Any backup set written to the SBT device in this configuration can contain a maximum of two backup pieces.
- C. Any backup written to the SBT device in this configuration can contain a maximum of two backup sets.
- D. SBT tape compression and RMAN backup compression should be used in parallel.
- E. The SBT device should be configured to use PARALLELISM 2 to allow both tape drive to be used simultaneously.

**Answer:** DE

**NEW QUESTION 4**

Which two are true about data movement between a non-CDB and a PDB using Data Pump? (Choose two.)

- A. Tablespaces are automatically created as needed while importing full exports in either a non-CDB or a PDB.
- B. Oracle attempts to convert conventional database users to local users when moving schemas from a non-CDB to a PDB.
- C. A new PDB is automatically created when importing a non-CDB into a CDB.
- D. Oracle attempts to convert common users to conventional users when moving schemas from a PDB to a non-CDB.
- E. Moving data from a PDB to a non-CDB is only possible by using transportable tablespace export and import.
- F. Moving data from a non-CDB to a PDB is only possible by using conventional export and import.

**Answer:** DE

**NEW QUESTION 5**

Examine this configuration:

- CDB1 is a container database.
- PDB1 and PDB2 are pluggable databases in CDB1. You execute these commands successfully:

```
$ export ORACLE_SID=cdb1

$sqlplus / as sysdba

SQL> SHUTDOWN IMMEDIATE
...
Oracle instance shut down.

SQL> STARTUP MOUNT
...
Database mounted.
```

Which two are true? (Choose two.)

- A. PDB1 and PDB2 are in MOUNT state.
- B. Redo logs are opened.
- C. PDB1 and PDB2 are in READ ONLY state.
- D. CDB\$ROOT is in MOUNT state.
- E. PDB\$SEED is in READ ONLY state.

**Answer:** BE

#### NEW QUESTION 6

Examine these actions:

- \* 1. Create a new database for a recovery catalog.
- \* 2. Create a tablespace with sufficient space in the catalog database for the recovery catalog.
- \* 3. Configure ARCHIVELOG mode for the catalog database.
- \* 4. Create a user to own the recovery catalog schema with quota on the tablespace that will contain the catalog.
- \* 5. Grant the RECOVERY\_CATALOG\_OWNER role to the recovery catalog schema owner.
- \* 6. Grant the SYSBACKUP privilege to the recovery catalog schema owner.

Which are the minimum actions that must be performed before executing the CREATECATALOG command?

- A. 2, 4, 5, 6
- B. 1, 2, 3, 4, 5, 6
- C. 1, 2, 4, 5
- D. 2, 4, 5
- E. 1, 3, 4, 5

**Answer:** D

#### NEW QUESTION 7

Which three are true about backup, restore, and recovery operations done without using Recovery Manager (RMAN)? (Choose three.)

- A. Backing up a database in NOARCHIVELOG mode using O/S utilities requires that the database instance be started and the database be in the MOUNT state.
- B. Backing up a database in ARCHIVELOG mode using O/S utilities requires that the database instance be started and the database be in MOUNT state.
- C. An Oracle database can be restored from backup files copied using O/S utilities.
- D. Oracle data file backups, copied using an O/S utility, can be added to the RMAN catalog as IMAGE COPIES.
- E. Backing up a database in NOARCHIVELOG mode using O/S utilities requires that the database instance be shut down.
- F. Oracle archive log backups, copied using an O/S utility, can be added to the RMAN catalog as a backup set.
- G. Backing up a database in ARCHIVELOG mode using O/S utilities requires that the database instance be started and the database be in OPEN state.

**Answer:** BDE

#### NEW QUESTION 8

A container database called CDB1 is OMF-enabled.

PDB\_FILE\_NAME\_CONVERT is not configured in CDB1. PDB1 was unplugged from CDB1 earlier in the week. Examine this command, which will be executed in CDB1:

```
CREATE PLUGGABLE DATABASE pdb1
USING '/u01/app/oracle/oradata/pdb1.xml' SOURCE_FILE_NAME_CONVERT =
('/u01/app/oracle/oradata/', '/u02/app/oracle/oradata/');
```

Which two are true? (Choose two.)

- A. PDB1 data files already exist in the correct location.
- B. DBMS\_PDB.CHECK\_PLUG\_COMPATIBILITY must be run in CDB1 before executing the command.
- C. PDB\_FILE\_NAME\_CONVERT must be set before executing the command.
- D. /u01/app/oracle/oradata/pdb1.xml does not contain the current locations of data files for PDB1.
- E. PDB1 must be dropped from CDB1.

**Answer:** AE

#### NEW QUESTION 9

Which three are true in Oracle 19c and later releases? (Choose three.)

- A. If the password file location changes, then the new location is used automatically by the Oracle Server.
- B. Schema Only accounts can be granted administrator privileges.
- C. All the Oracle-supplied accounts are Schema Only accounts.
- D. Privilege Analysis is included in Oracle Enterprise Edition and no longer requires Database Vault.
- E. Unified Auditing can be configured to audit only events that are issued indirectly by an audited user.

F. Unified Auditing can be configured to audit only events that are issued directly by an audited user.

**Answer:** BCD

#### NEW QUESTION 10

Which three are true about Recovery Manager (RMAN) in Oracle Database 19c and later releases? (Choose three.)

- A. It is only possible for RMAN to connect to a pluggable database as a target if an RMAN Virtual Private Catalog is used.
- B. It is always possible for RMAN to connect to a pluggable database as a target if any RMAN Catalog is used.
- C. A Virtual Private Catalog used to register a container database must be created in a pluggable database.
- D. A Virtual Private Catalog used to register a container database can be created in a pluggable database.
- E. It is always possible for RMAN to connect to a pluggable database as a target.
- F. A Virtual Private Catalog used to register a container database can be created in a non-container database.

**Answer:** DEF

#### NEW QUESTION 10

Which three are true about Optimizer Statistics Advisor? (Choose three.)

- A. It can be run only manually.
- B. It is part of the DBMS\_ADVISOR package.
- C. It can recommend changes to improve the statistics gathering process.
- D. It always analyzes all schemas in the database.
- E. It runs automatically every night by default.
- F. It is part of the DBMS\_STATS package.

**Answer:** ACF

#### Explanation:

<https://mikedietrichde.com/2017/08/22/oracle-optimizer-statistics-advisor-in-oracle-database-12-2-0-1/> <https://www.oracle.com/technetwork/database/bi-datawarehousing/twp-bp-for-stats-gather-19c-5324205.pdf>

#### NEW QUESTION 13

Which three can be done using Oracle Database Configuration Assistant (DBCA) starting from Oracle Database 19c? (Choose three.)

- A. cloning a remote container database in interactive mode
- B. cloning a remote pluggable database in silent mode
- C. relocating a remote pluggable database in interactive mode
- D. relocating a remote container database in silent mode
- E. cloning a remote container database in silent mode
- F. relocating a remote pluggable database in silent mode
- G. relocating a remote container database in interactive mode

**Answer:** BEF

#### NEW QUESTION 17

A user complains about poor database performance.

You want to verify if the user's session has waited for certain types of I/O activity. Which view displays all waits waited on by a session at least once?

- A. V\$SESSION\_EVENT
- B. V\$SESSTAT
- C. V\$SESSION\_WAIT
- D. V\$SESSION\_WAIT\_CLASS
- E. V\$SESSION

**Answer:** A

#### NEW QUESTION 22

Which two are true about Oracle Database Configuration Assistant (DBCA) templates? (Choose two.)

- A. The General Purpose of Transaction Processing templates are most suitable when concurrency and recoverability are key criteria.
- B. Oracle DBCA templates can store only logical structure and not database files.
- C. New templates can only be created by modifying an existing user-created template.
- D. The Data Warehouse template is most suitable when transaction response time is the key criterion.
- E. Oracle DBCA templates can be used to create new databases and duplicate existing databases.

**Answer:** AE

#### NEW QUESTION 23

On the 10th of August, you implement an incremental database backup strategy and configure a recovery window of five days.

Level 0 backups are taken on the 10th, 17th, and 24th of August.

Differential level 1 incremental backups are taken daily between the level 0 backups. Today is the 26th of August.

Which backups will be obsolete?

- A. all backups prior to 10th of August
- B. all backups prior to 22nd of August
- C. all backups prior to 24th of August



- D. all backups prior to 20th of August
- E. all backups prior to 17th of August

**Answer:** C

#### NEW QUESTION 28

Examine these queries and their output:

```
SQL> select pdb_name, name, pdb_restore_point, clean_pdb_restore_point
       2 from v$restore_point natural join dba_pdbs;
```

PDB_NAME	NAME	PDB_RESTORE_POINT	CLEAN_PDB_RESTORE_POINT
PDB1	R1	YES	NO

```
SQL> select property_name, property_value
       2 from database_properties where property_name like '%UNDO%';
```

PROPERTY_NAME	PROPERTY_VALUE
LOCAL_UNDO_ENABLED	FALSE

An online RMAN backup of the CDB was taken an hour before Restore Point R1 was created. You want to recover PDB1 to Restore Point R1. How do you achieve this?

- A. Execute FLASHBACK PLUGGABLE DATABASE PDB1 TO RESTORE POINT R1 by using RMAN while connected to PDB1.
- B. Execute FLASHBACK PLUGGABLE DATABASE PDB1 TO RESTORE POINT R1 by using SQL while connected to PDB1.
- C. Execute FLASHBACK PLUGGABLE DATABASE PDB1 TO RESTORE POINT R1 by using SQL while connected to CDB\$ROOT.
- D. Execute FLASHBACK PLUGGABLE DATABASE PDB1 TO RESTORE POINT R1 by using RMAN while connected to CDB\$ROOT.
- E. This cannot be done due to the lack of a clean restore point.

**Answer:** B

#### NEW QUESTION 32

Which two are true about Rapid Home Provisioning (RHP), which has been available since Oracle 18c? (Choose two.)

- A. It is an Oracle Database service
- B. It cannot be used to upgrade Oracle Database homes.
- C. It can be used to provision applications.
- D. It can be used to patch Grid Infrastructure homes containing Oracle Restart.
- E. It can be used to provision middleware.

**Answer:** DE

#### NEW QUESTION 36

Which two are true about duplicating pluggable databases (PDBs) with RMAN? (Choose two.)

- A. Two or more PDBs can be duplicated with the same RMAN DUPLICATE command.
- B. All tablespaces belonging to a PDB must be duplicated when duplicating the PDB.
- C. The auxiliary instance is automatically created with ENABLE\_PLUGGABLE\_DATABASE = TRUE.
- D. A user with SYSDBA or SYSBACKUP must be logged in with RMAN to the PDB to duplicate it.
- E. CDB\$ROOT and PDB\$SEED are automatically duplicated.

**Answer:** CD

#### NEW QUESTION 39

Your CDB has two regular PDBs as well as one application container with two application PDBs and an application seed. No changes have been made to the standard PDB\$SEED. How many default temporary tablespaces can be assigned in the CDB?

- A. three
- B. eight
- C. seven
- D. six
- E. five

**Answer:** C

#### NEW QUESTION 44

Which three are true about RMAN persistent configuration settings, administration, and their effects? (Choose three.)

- A. A target database's persistent RMAN configuration settings are always stored in the target's control file.
- B. Backup older than the recovery window retention policy are always deleted automatically if the backup location has insufficient space.
- C. Backups written to the fast recovery area (FRA) that are obsolete based on the redundancy retention policy can be deleted automatically to free space.
- D. The RMAN SHOW ALL command displays only settings with nondefault values.
- E. A target database's persistent RMAN configuration settings are always synchronized automatically with the RMAN catalog.
- F. The V\$RMAN\_CONFIGURATION view displays only settings with values that have been modified.
- G. A DBA must specify either a redundancy retention policy or a recovery window retention policy.

**Answer:** ABF

**NEW QUESTION 48**

Which three actions are performed by Database Upgrade Assistant (DBUA)? (Choose three.)

- A. It recompiles all stored PL/SQL code by using utlrl.sql.
- B. It empties the RECYCLE BIN.
- C. It performs prerequisite checks to verify if the Oracle database is ready for upgrade.
- D. It sets all user tablespaces to “read-only” before starting the upgrade.
- E. It removes the AUDSYS schema and the AUDIT\_ADMIN and AUDIT\_VIEWER roles
- F. It increases tablespace size, if required, to meet upgrade requirements.

**Answer:** ACF

**NEW QUESTION 51**

Which two are true about creating pluggable databases (PDBs) using snapshots in Oracle 19c and later releases? (Choose two.)

- A. A PDB snapshot is always a full copy of the source PDB.
- B. A PDB snapshot is always a sparse copy of the source PDB.
- C. A snapshot copy PDB depends on a storage snapshot which can only be stored on specific file systems.
- D. A PDB snapshot depends on a storage snapshot which can be stored on any file system.
- E. A PDB snapshot depends on a storage snapshot which can only be stored on specific file systems.
- F. A snapshot copy PDB depends on a storage snapshot which can be stored on any file system.
- G. A snapshot copy PDB can be created from a stand-alone clone PDB.

**Answer:** AE

**NEW QUESTION 52**

Examine this command:

\$ rhpctl move database –sourcehome Oracle\_home\_path –destinationhome Oracle\_home\_path For which two purposes can you use this command? (Choose two.)

- A. to switch an existing Oracle Database home to a newer release of Oracle software on the same server
- B. to switch to a read-only Oracle home
- C. to switch back to the previous Oracle home as part of a rollback operation
- D. to switch the Oracle Database home when using a centralized Rapid Home Provisioning server
- E. to switch to a patched Oracle Database home

**Answer:** CE

**Explanation:**

You can use rhpctl move gihome command with the same syntax to switch from the current Oracle Grid Infrastructure home to a patched home. The rhpctl command enables you to switch from your current Oracle Grid Infrastructure or Oracle Database home to patched Oracle home so that you can provision the new Oracle home as gold image. You can also use the rhpctl command to switch back to the old Oracle home, if you want to roll back the operation.

**NEW QUESTION 56**

Which three are true about thresholds, metrics, and server-generated alerts? (Choose three.)

- A. All metrics are instance related.
- B. Cleared stateful alerts are displayed by querying DBA\_ALERT\_HISTORY.
- C. A space usage management alert is automatically cleared after the underlying problem is resolved.
- D. They are generated by SMON when a tablespace is 97% full.
- E. Metrics are statistical counts for a specific unit.
- F. STATISTICS\_LEVEL must be set to ALL to generate alerts.

**Answer:** BCE

**NEW QUESTION 60**

Which two are true about RMAN encryption? (Choose two.)

- A. RMAN encryption keys are stored in a database keystore.
- B. RMAN can encrypt the Oracle Database password file.
- C. Dual-mode encrypted backups can be restored only if both the password and the keystore used for encryption are available.
- D. The SET ENCRYPTION command overrides encryption settings specified by the CONFIGURE ENCRYPTION command.
- E. Password encryption can be persistently configured using the CONFIGURE ENCRYPTION command.

**Answer:** CD

**NEW QUESTION 64**

Which two are true about common objects? (Choose two.)

- A. They can be created only in CDB\$ROOT.
- B. They can be only metadata-linked in an application container.
- C. They can exist in user-defined schemas only in application containers.
- D. They can exist in CDB\$ROOT and an application root.
- E. They can be extended data-linked in CDB\$ROOT.
- F. They can be created only in an application root.

**Answer:** CF

**NEW QUESTION 69**

Which three are true about Automatic Workload Repository (AWR), Automatic Database Diagnostic Monitor (ADDM), and the Manageability Monitor (MMON) background process? (Choose three.)

- A. ADDM can recommend shrinking the buffer cache.
- B. ADDM can recommend extending the buffer cache.
- C. By default, MMON creates an AWR snapshot every 30 minutes.
- D. ADDM performs its analysis only when a DBA requests it.
- E. By default, AWR snapshots are automatically purged after eight days.
- F. AWR snapshots must be deleted when no longer required by ADDM.

**Answer:** AEF

**NEW QUESTION 70**

Which four are true about performing Tablespace Point -In-Time Recovery (TSPITR) using Recovery Manager (RMAN)?

- A. It can be performed using an auxiliary instance managed by a DBA.
- B. It can be used to recover a truncated table.
- C. RMAN automatically adds any required tablespaces to the recovery set to make it self-contained.
- D. RMAN always includes tablespaces containing undo segments in the recovery set.
- E. It can be performed repeatedly until the correct time is found without using an RMAN catalog.
- F. flashback database must be enabled for it to work.
- G. It can be used to recover a dropped tablespace.
- H. It can be performed using an auxiliary instance managed by RMAN.

**Answer:** AEFH

**NEW QUESTION 73**

Which two are true about instance recovery? (Choose two.)

- A. It is not possible if an archived log is missing.
- B. It is performed automatically after the database is opened; however, blocks requiring recovery are not available until they are recovered.
- C. Setting FAST\_START\_MTTR\_TARGET to a lower value reduces instance recovery time by causing dirty buffers to be written to disk more frequently, thereby reducing the number of I/Os needed during instance recovery.
- D. It is performed by the Recovery Writer (RVWR) background process.
- E. Setting FAST\_START\_MTTR\_TARGET to a higher value reduces instance recovery time by causing the log writer to write more frequently, thereby reducing the number of I/Os needed during instance recovery.
- F. It is performed automatically while the database remains in MOUNT state.
- G. Then the database is opened.

**Answer:** EF

**NEW QUESTION 77**

Which two are true about OS groups and users for OracleGrid Infrastructure and the Oracle Relational Database Management System (RDBMS)? (Choose two.)

- A. By default, members of the OSASM group can access Automatic Storage Management and RDBMS instances.
- B. The primary group for the Oracle Grid Infrastructure and Oracle Database owners must be the Oracle Inventory group.
- C. The Oracle Grid Infrastructure installation must be owned by the grid user.
- D. The Oracle Grid Infrastructure owner owns Oracle Restart and Oracle Automatic Storage Management binaries.
- E. The Oracle Grid Infrastructure owner must have OSOPER, OSBACKUPDBA, and OSKMDBA as secondary groups.
- F. The same OSDBA group must be used for Automatic Storage Management and the Oracle Database.

**Answer:** EF

**NEW QUESTION 81**

Which three are true about Automatic Workload Repository (AWR)? (Choose three.)

- A. By default, AWR snapshots are taken every 60 minutes.
- B. Its collection level is determined by the value of the STATISTICS\_LEVEL database parameter.
- C. By default, AWR snapshots are retained for 7 days.
- D. The taking of AWR snapshots can be disabled.
- E. AWR data is stored in the SYSTEM tablespace.

**Answer:** ABD

**NEW QUESTION 83**

You must transport the UNIVERSITY tablespace from one database to another. The UNIVERSITY tablespace is currently open read/write. The source and destination platforms have different endian formats. Examine this list of actions:

- \* 1. Make the UNIVERSITY tablespace read-only on the source system.
- \* 2. Export the UNIVERSITY tablespace metadata using EXPDP.
- \* 3. Convert the UNIVERSITY tablespace data files to the destination platform format using RMAN on the source system.
- \* 4. Copy the UNIVERSITY tablespace data files to the destination system.
- \* 5. Copy the Data Pump dump set to the destination system.
- \* 6. Convert the UNIVERSITY tablespace data files to the destination platform format using RMAN on the destination system.
- \* 7. Import the UNIVERSITY tablespace metadata using IMPDP.



\* 8. Make the UNIVERSITY tablespace read/write on the destination system.

Which is the minimum number of actions required, in the correct order, to transport the UNIVERSITY tablespace?

- A. 1, 2, 4, 5, 7, 8
- B. 1, 2, 4, 6, 7, 8
- C. 1, 2, 3, 4, 5, 7, 8
- D. 1, 2, 3, 4, 5, 6, 7, 8
- E. 2, 4, 5, 6, 7

**Answer: B**

#### NEW QUESTION 86

Examine this configuration:

1. CDB1 is a container database running in ARCHIVELOG mode.
2. Controlfiles of CDB1 are multiplexed in  
'/u01/app/oracle/oradata/CDB1/controlfile/controlfile01.ctl' and  
'/u02/app/oracle/fast\_recover\_area/cdb1/CDB1/controlfile02.ctl'.
3. The only backup of CDB1 was taken when CONTROLFILE AUTOBACK was OFF
4. SNAPSHOT CONTROLFILE NAME is  
'/u01/app/oracle/product/12.2.0.1/db\_1/dbs/snapcf\_cdb1.f'.

While CDB1 is open, '/u02/app/oracle/fast\_recover\_area/cdb1/CDB1/controlfile02.ctl' is accidentally deleted. To recover from this critical failure, you execute these commands:

```
$ rman target sys/oracle_4U@localhost:1521/cdb1
```

```
RMAN> SHUTDOWN ABORT
```

```
...
```

```
Oracle instance shut down
```

```
RMAN> STARTUP NOMOUNT
```

```
RMAN RESTORE CONTROLFILE FROM  
'/u01/app/oracle/oradata/CDB1/controlfile/controlfile01.ctl';
```

What will be the outcome?

- A. It will create '\$ORACLE\_HOME/dbs/cdb1/CDB1/controlfile02.ctl'
- B. It will create '/u01/app/oracle/oradata/CDB1/controlfile/controlfile02.ctl'.
- C. It will re-create '/u02/app/oracle/fast\_recover\_area/cdb1/CDB1/controlfile02.ctl'
- D. It will create '/u01/app/oracle/product/12.2.0.1/db\_1/dbs/snapcf\_cdb1control02.ctl'.
- E. It will fail because there is no autobackup of the controlfiles.

**Answer: C**

#### NEW QUESTION 89

Examine the command for creating pluggable database PDB2 in container database CDB2.

```
CREATE PLUGGABLE DATABASE pdb2  
  ADMIN USER pdb2_adm  
  IDENTIFIED BY 123pdb  
  ROLES=(CONNECT);
```

Select three options, any one of which is required for it to execute successfully. (Choose three.)

- A. Add the FILE\_NAME\_CONVERT clause to the statement and set the PDB\_FILE\_NAME\_CONVERT parameter.
- B. Add only the CREATE\_FILE\_DEST clause to the statement.
- C. Set only the PDB\_FILE\_NAME\_CONVERT parameter.
- D. Set the PDB\_FILE\_NAME\_CONVERT parameter and enable OMF.
- E. Enable only OMF.
- F. Add the FILE\_NAME\_CONVERT clause to the statement and enable Oracle Managed Files (OMF)

**Answer: BDE**

#### NEW QUESTION 90

Which two are true about the Automatic Database Diagnostic Monitor (ADDM)? (Choose two.)

- A. It analyzes a period of time corresponding to the 12 hours of activity.
- B. It runs automatically after each AWR snapshot.
- C. A DBA can run it manually.
- D. Results are written to the alert log.
- E. It analyzes a period of time corresponding to the last day of activity.

**Answer: BC**

#### NEW QUESTION 93

Examine this configuration:



\* 1.The ORCL database data files are in Automatic Storage Management (Oracle ASM) disk group +DATA. \* 2.ORCL uses disk group +FRAfor the Fast Recovery Area.  
\* 3. LISTENER is the listener for ORCL.  
\* 4. The database, listener, ASM instance, and ASM disk groups are managed by Oracle Restart. 5.All components are currently shut down.  
You execute this command:  

```
$ srvctl start database -d ORCL
```

What is the outcome?

- A. The ORCL database, the Oracle ASM instances, the +DATA and +FRA disk groups, and the LISTENERare started.
- B. Only the ORCL database instance is started.
- C. Only the ORCL database and the ASM instances are started.
- D. Only the ORCL database instance, the Oracle ASM instance, and the +DATA and +FRA disk groups are started.
- E. Only the ORCL database instance and the +DATA and +FRA disk groups are started.

**Answer: D**

#### NEW QUESTION 98

Examine this configuration:

- CDB1is a container database.
- PDB1andPDB2arepluggable databases inCDB1.
- PDB1andPDB2areOPENinREAD WRITEmode.

You execute these commands successfully:

```
$ export ORACLE_SID=CDB1  
$ sqlplus / as sysdba
```

```
SQL> ALTER SESSION SET CONTAINER = PDB1;  
Session altered.
```

```
SQL> SHUTDOWN IMMEDIATE
```

Which two are true? (Choose two.)

- A. Uncommitted transactions in PDB1 have been rolled back.
- B. PDB1 is closed.
- C. Uncommitted transactions in CDB1 and PDB1 have been rolled back.
- D. CDB1 is shut down.
- E. CDB1 is in MOUNT state

**Answer: AB**

#### NEW QUESTION 101

Which three are true about monitoring waits for sessions and services? (Choose three.)

- A. V\$SESSION\_EVENT displays all waits for all past and existing sessions if the wait has occurred at least once for a session.
- B. V\$SERVICE\_EVENT displays all waits for all services if the wait has occurred at least once for a service.
- C. V\$SESSION\_WAIT\_CLASS displays waits broken down by wait class only for waiting sessions.
- D. V\$SESSION\_WAIT and V\$SESSION both contain details of the event on which a non-waiting session last waited.
- E. V\$SESSION\_EVENT displays all waits for all past sessions if the wait has occurred at least once for a session.
- F. V\$SESSION\_WAIT and V\$SESSION both contain details of the event on which a session is currently waiting.

**Answer: BDE**

#### NEW QUESTION 105

Which three are true about transporting databases across platforms usingRecovery Manager (RMAN) image copies? (Choose three.)

- A. By default, the transported database will use Oracle Managed Files (OMF)
- B. Data files can be converted on the destination system.
- C. Data files can be converted on the source system.
- D. A new DBIDis automatically created for the transported database.
- E. Databases can be transported between systems with different endian formats.
- F. The password file is automatically converted by RMAN.

**Answer: BCE**

#### Explanation:

Password file is automatically converted by RMAN.

#### NEW QUESTION 108

Which four are true about a Recovery Manager (RMAN)duplication without a TARGET connection? (Choose four.)

- A. The NOREDO clause must be used if the backups of the database being duplicated were taken when the database was in NOARCHIVELOG mode.
- B. The UNDO TABLESPACE clause is always required when no connection exists to the TARGET instance.
- C. RMAN “pushes” the backups of the database to be duplicated over the network to the auxiliary instance.
- D. The NOREDO clause can be used if the backups of the database being duplicated were taken when the database wasin ARCHIVELOG mode.
- E. RMAN SBT-based backups of the database to be duplicated can be used by the auxiliary instance.

- F. The UNDO TABLESPACE clause is always required when no connection exists to the recovery catalog and the TARGET database is closed.  
G. The UNDO TABLESPACE clause is always required when no connection exists to the recovery catalog and the TARGET database is opened.  
H. RMAN disk-based backups of the database to be duplicated can be used by the auxiliary instance.

**Answer:** ABGH

#### NEW QUESTION 112

Which three are true about the SQL Tuning Advisor? (Choose three.)

- A. It checks each query being analyzed for stale statistics.  
B. It checks each query being analyzed for missing statistics.  
C. It only recommends syntactic changes to SQL statements.  
D. It can recommend semantic changes to SQL statements.  
E. It considers all SQL statements being analyzed by the advisor task as a group.  
F. It builds SQL profiles for each poorly performing SQL statement to prevent regressions.

**Answer:** ABF

#### NEW QUESTION 117

You have configured RMAN SBT channels to write backups to media. You then take an RMAN backup by using this command:

```
RMAN> BACKUP AS COMPRESSED BACKUPSET  
        DATABASE  
        KEEP UNTIL TIME 'SYSDATE + 730'  
        RESTORE POINT 'OLD_CONFIGURATION';
```

Which three are true? (Choose three.)

- A. The restore point is a label for the system change number (SCN) that will be saved two years after the archival backup was taken.  
B. The data file backups in the self-contained archive backup are not considered obsolete for two years regardless of the retention policy.  
C. All archive logs created after this backup are kept for two years.  
D. The SPFILE is included in the self-contained archival backup.  
E. The control file is included in the self-contained archival backup.  
F. The restore point is a label for the system change number (SCN) before the archival backup was taken.

**Answer:** CDE

#### NEW QUESTION 120

Which two are true about the execution of operating system scripts starting from Oracle Database 19c? (Choose two.)

- A. oraInstRoot.sh can be executed automatically by the Database installer by using sudo or root credentials.  
B. root.sh can be executed automatically by the Database Installer only if it is provided with root credentials.  
C. The sudo password can be specified in a response file.  
D. root.sh can be executed automatically by the Database installer only by using sudo credentials.  
E. The sudo password must be specified in a response file.  
F. The root password cannot be specified in a response file.

**Answer:** AF

#### NEW QUESTION 122

While backing up to an SBT channel, you determine that the read phase of your compressed Recovery Manager (RMAN) incremental level 0 backup is a bottleneck.

FORCE LOGGING is enabled for the database.

Which two could improve read performance? (Choose two.)

- A. Increase the size of tape I/O buffers.  
B. Disable FORCE LOGGING for the database.  
C. Increase the size of the database buffer cache.  
D. Enable asynchronous disk I/O.  
E. Increase the level of RMAN multiplexing.

**Answer:** DE

#### NEW QUESTION 123

You are managing this configuration:

- CDB1 is a container database.
- PDB1 and PDB2 are two pluggable databases in CDB1.
- USER1.EMP is a table in PDB1 and USER2.DEPT is a table in PDB2.

CDB1 user SYS executes these commands after connecting successfully to PDB2:

```
SQL> ALTER SESSION SET CONTAINER=pdb1;
Session altered.

SQL> INSERT INTO user1.emp VALUES(100, 'Alan',1);
1 row created.

SQL> INSERT INTO user1.emp VALUES(101, 'Ben', 1);
1 row created.

SQL> ALTER SESSION SET CONTAINER=pdb2;
Session altered.

SQL> INSERT INTO user2.dept VALUES(1, 'IT');
```

Which two are true? (Choose two.)

- A. The inserts on USER1.EMP remain uncommitted when the session connected to PDB2.
- B. The inserts on USER1.EMP were committed when the session inserted a row into USER2.DEPT.
- C. The insert on USER2.DEPT fails because of the active transaction in the parent container.
- D. The insert on USER2.DEPT is a recursive autonomous transaction by the child session and is committed.
- E. The inserts on USER1.EMP were rolled back when the session connected to PDB2.
- F. The insert on USER2.DEPT is uncommitted.
- G. The inserts on USER1.EMP were committed when the session connected to PDB2.

**Answer:** FG

#### NEW QUESTION 126

You plan to install Oracle Grid Infrastructure for a Standalone Server and Oracle Database for the first time on a server. Examine this command and its outcome:

```
# id oracle
uid=54321 (oracle) gid=54321(oinstall) groups=54321(oinstall), 54322 (dba)
```

Which two are true? (Choose two.)

- A. oracle will be an owner of the Oracle Inventory.
- B. oracle must be the owner of every Oracle Database installation.
- C. oracle can own an OracleDatabase installation but not an Oracle Grid Infrastructure installation.
- D. oracle will be granted the SYSASM privilege when installing the Oracle Database software.
- E. The user account, oracle, and group, oinstall, can be used for all Oracle software installations.

**Answer:** CD

#### NEW QUESTION 129

Which two are true about creating RMAN backups for an Oracle container database? (Choose two.)

- A. Tablespaces from different PDBs with identical names must be backed up by connecting RMAN separately to each PDB to back up the tablespaces.
- B. The BACKUP DATABASE command will create a pluggable database (PDB) backup when RMAN is connected to a PDB.
- C. SPFILEbackups can be created while connected to an application root PDB.
- D. The BACKUP DATABASE PLUS ARCHIVELOG command will back up archive logs when RMAN is connected to a PDB.
- E. The BACKUP PLUGGABLE DATABASE command can be used to back up CDB\$ROOT.

**Answer:** AB

#### NEW QUESTION 130

Your container database, CDB1, has an application container, HR\_ROOT, with an application PDB, HR\_PDB1. You have the required privilege to clone HR\_PDB1 to container database CDB2, which does not contain HR\_ROOT. Which two are always true? (Choose two.)

- A. CDB1 and CDB2 must be in shared undo mode.
- B. A common user must exist in CDB2 with the CREATE PLUGGABLE DATABASE privilege.
- C. All transactions in HR\_PDB1 of CDB1 must commit before the cloning process starts.
- D. Cloning HR\_ROOT automatically clones HR\_PDB1.
- E. The HR\_PDB1 clone created in CDB2 will be in mount state when cloning ends.

**Answer:** BD

#### NEW QUESTION 135

.....

## Thank You for Trying Our Product

\* 100% Pass or Money Back

All our products come with a 90-day Money Back Guarantee.

\* One year free update

You can enjoy free update one year. 24x7 online support.

\* Trusted by Millions

We currently serve more than 30,000,000 customers.

\* Shop Securely

All transactions are protected by VeriSign!

**100% Pass Your 1z0-083 Exam with Our Prep Materials Via below:**

<https://www.certleader.com/1z0-083-dumps.html>