

Exam Questions 300-435

Automating and Programming Cisco Enterprise Solutions (ENAUTO)

<https://www.2passeasy.com/dumps/300-435/>



NEW QUESTION 1

What are two characteristics of RPC API calls? (Choose two.)

- A. They can be used only on network devices.
- B. They use only UDP for communications.
- C. Parameters can be passed to the calls.
- D. They must use SSL/TLS.
- E. They call a single function or service.

Answer: AC

NEW QUESTION 2

Which two actions do Python virtual environments allow users to perform? (Choose two.)

- A. Simplify the CI/CD pipeline when checking a project into a version control system, such as Git.
- B. Efficiently port code between different languages, such as JavaScript and Python.
- C. Run and simulate other operating systems within a development environment.
- D. Quickly create any Python environment for testing and debugging purposes.
- E. Quickly create an isolated Python environment with module dependencies.

Answer: DE

NEW QUESTION 3

Which two features are foundations of a software-defined network instead of a traditional network? (Choose two.)

- A. control plane and data plane are tightly coupled
- B. build upon a robust software stack
- C. requires device by device-level configurations
- D. automated through expressed intent to a software controller
- E. requires significant physical hardware resources

Answer: BD

NEW QUESTION 4

```
<rpc xmlns="urn:ietf:params:xml:ns:netconf:base:1.0" message-id="101">
  <get>
    <filter>
      <native xmlns="http://cisco.com/ns/yang/Cisco-IOS-XE-native">
        <ntp>
          <server xmlns="http://cisco.com/ns/yang/Cisco-IOS-XE-ntp">
            <server-list>
              <ip-address>10.11.10.65</ip-address>
            </server-list>
          <server>
        </ntp>
      </native>
      <ntp-oper-data xmlns="http://cisco.com/ns/yang/Cisco-IOS-XE-ntp-oper">
        <ntp-status-info>
          <ntp-associations>
            <peer-stratum/>
          </ntp-associations>
        </ntp-status-info>
      </ntp-oper-data>
    </filter>
  </get>
</rpc>
```

Refer to the exhibit. How many YANG models does the NETCONF <get> operation interact with?

- A. one
- B. two
- C. three
- D. four

Answer: A

NEW QUESTION 5

Which statement describe the difference between OpenConfig and native YANG data models?

- A. Native models are designed to be independent of the underlying platform and are developed by vendors and standards bodies, such as the IETF.
- B. Native models are developed by individual developers and designed to apply configurations on platforms.
- C. OpenConfig models are developed by vendors and designed to integrate to features or configurations that are relevant only to that platform.
- D. Native models are developed by vendors and designed to integrate to features or configurations that are relevant only to that platform.

Answer: A

NEW QUESTION 6

Which curl command is used to update the SNMP community of network ID "1234567" to read-only?

- A.
- ```
curl -L -H 'X-Cisco-Meraki-API-Key: <key>' \
-H 'Content-Type: application/json' \
-X PUT --data-binary '{ \
 "access": "users", \
 "communityString": "readonly"}' \
'https://api.meraki.com/api/v0/networks/1234567/snmpSettings'
```
- B.
- ```
curl -L -H 'X-Cisco-Meraki-API-Key: <key>' \
-H 'Content-Type: application/json' \
-X PUT --data-binary '{ \
  "access": "community", \
  "communityString": "readonly"}' \
'https://api.meraki.com/api/v0/networks/1234567/snmpSettings'
```
- C.
- ```
curl -L -H 'X-Cisco-Meraki-API-Key: <key>' \
-H 'Content-Type: application/json' \
-X PUT --data-binary '{ \
 "access": "users", \
 "username": "snmp", \
 "passphrase": "readonly"}' \
'https://api.meraki.com/api/v0/networks/1234567/snmpSettings'
```
- D.
- ```
curl -L -H 'X-Cisco-Meraki-API-Key: <key>' \
-H 'Content-Type: application/json' \
-X POST --data-binary '{ \
  "access": "community", \
  "communityString": "readonly"}' \
'https://api.meraki.com/api/v0/networks/1234567/snmpSettings'
```

A.

Answer: B

NEW QUESTION 7

```
module: ietf-ip
augment /if:interfaces/if:interface:
+--rw ipv4!
| +--rw enabled?      boolean
| +--rw forwarding?  boolean
| +--rw mtu?          uint16
| +--rw address* [ip]
| | +--rw ip          inet:ipv4-address-no-zone
| | +--rw (subnet)
| | | +--:(prefix-length)
| | | | +--rw prefix-length?      uint8
| | | | +--:(netmask)
| | | | +--rw netmask?            yang:dotted-guad (ipv4-non-contiguous-netmasks)?
| | +--ro origin?              ip-address-origin
| +--rw neighbor* [ip]
|   +--rw ip                  inet:ipv4-address-no-zone
|   +--rw link-layer-address  yang:phys-address
```

Refer to the exhibit. Which NETCONF statement type is represented by +--rw address* [ip]?

- A. list
- B. leaf-list
- C. container
- D. submodule

Answer: A

NEW QUESTION 8

Which two Netmiko methods are used to configure a device? (Choose two.)

- A. send_config()

- B. send_control_from_file()
- C. send_config_set()
- D. send_command()
- E. send_config_from_file()

Answer: CE

NEW QUESTION 9

DRAG DROP

Drag and drop the commands to the Ansible playbook that applies configuration to an interface on a Cisco IOS XE device. Not all options are used. Select and Place:

Answer Area

ioscmd	interface
parents	iosxe
iosconfig	ios_config

```
- name: configure interface settings
  [ ]:
    lines:
      -ip address 172.31.1.1 255.255.255.0
      -no shutdown
  [ ]: interface GigabitEthernet1/0
```

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

Answer Area

ioscmd	interface
parents	iosxe
iosconfig	ios_config

```
- name: configure interface settings
  ios_config:
    lines:
      -ip address 172.31.1.1 255.255.255.0
      -no shutdown
  parents: interface GigabitEthernet1/0
```

NEW QUESTION 10

```
<rpc message-id="101" xmlns="urn:ietf:params:xml:ns:netconf:base:1.0">
  <establish-subscription
    xmlns="urn:ietf:params:xml:ns:yang:ietf-event-notifications"
    xmlns:yp="urn:ietf:params:xml:ns:yang:ietf-yang-push">
    <stream>yp:yang-push</stream>
    <yp:xpath-filter>/mdt-oper:mdt-oper-data/mdt-subscriptions</yp:xpath-filter>
    <yp:[ ]>1000</yp:[ ] >
  </establish-subscription>
</rpc>
```

Refer to the exhibit. Which XML tag completes this NETCONF telemetry subscription with a Cisco IOS XE device?

- A. crontab
- B. cadence
- C. frequency
- D. period

Answer: D

NEW QUESTION 10

FILL BLANK

Fill in the blank to complete the statement.

is a solution for automating the configuration of a device when it is first powered on, using DHCP and TFTP.

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

Zero touch provisioning (ZTP)

NEW QUESTION 13

```
from ncclient import manager
with manager.connect(
    host='10.0.0.1',
    port=12022,
    username='cisco',
    password='cisco',
    hostkey_verify=False,
    allow_agent=False,
    look_for_keys=False,
    device_params={'name': 'iosxe'},
) as m:
```

Refer to the exhibit. What is the correct ncclient method to use to collect the running configuration of a Cisco IOS XE device that uses NETCONF?

- A. config=m.copy_config(source='running')
- B. config=m.get(source='running')
- C. config=m.collect_config(source='running')
- D. config=m.get_config(source='running')

Answer: A

NEW QUESTION 18

FILL BLANK

Fill in the blanks to complete this API request against the Cisco SD-WAN vManage Statistics API, which specified a deviceID of 260faff9-2d31-4312-cf96-143b46db0211, a local-color of biz-internet, and a remote-color of gold.

<https://vmanage-ip-address:8443/dataservice/device/app-route/statistics?> 260faff9-2d31-4312-cf96-143b46db0211 biz-internet gold

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

deviceID=, local-color, remote-color

NEW QUESTION 22

What does the command boot ipxe forever switch 1 perform when executed on a Cisco IOS XE device?

- A. It continuously sends DHCP requests for iPXE until the device boots with an image.
- B. It continuously sends DNS requests for iPXE until the device restarts.
- C. It continuously sends DNS requests for iPXE until the device boots with an image.
- D. It continuously sends DHCP requests for iPXE until the device restarts.

Answer: A

NEW QUESTION 26

The Cisco DNA Center Sites API must be used to add a device to a site, but only the site name is available. Which API call must be used to retrieve the site identifier so that the device can be properly added to the network?

- A. /dna/intent/api/site/siteId
- B. /dna/intent/api/site
- C. /dna/intent/api/v1/site
- D. /dna/intent/api/v1/site/siteName

Answer: C

NEW QUESTION 31

When a Grafana dashboard is built to receive network events from Cisco DNA Center, which integration bundle is enabled to send notifications?

- A. Basic ITSM CMDB Synchronization
- B. DNA Center Rest API
- C. Network Events for REST API Endpoint
- D. Network Issue Monitor and Enrichment for ITSM

Answer: B

NEW QUESTION 35

Which field must be completed in Cisco DNA Center when a network discovery is initiated?

- A. SNMP read community string
- B. Enable password
- C. NETCONF port
- D. Discovery type

Answer: D

NEW QUESTION 40

Webhook that are generated by Cisco DNA Center are REST calls with which properties?

- A. JSON payload delivered via PUT
- B. XML payload delivered via POST
- C. JSON payload delivered via POST
- D. XML payload delivered via PUT

Answer: A

NEW QUESTION 42

A network administrator must troubleshoot a network issue using Cisco DNA Center. Which API request helps to determine issue details, impacted hosts, or suggested actions for the resolution?

- A. /dna/intent/v1/issues
- B. /dna/intent/api/v1/issues
- C. /dna/intent/v1/issue-enrichment-details
- D. /dna/api/v1/client-health/issues

Answer: B

NEW QUESTION 45

Which two network assurance features are provided by the Cisco DNA Center API? (Choose two.)

- A. site health
- B. license compliance health
- C. client health
- D. Cisco APIC appliance health
- E. Cisco DNA Center appliance health

Answer: AC

NEW QUESTION 47

Which two features are characteristics of software-defined networks when compared to traditional infrastructure? (Choose two.)

- A. configured box-by-box
- B. changed manually
- C. use overlay networks
- D. designed to change
- E. require software development experience to manage

Answer: CD

NEW QUESTION 52

FILL BLANK

<https://vmanage-ip-address:8443/dataservice/device/action/reboot> 260faff9-2d31-4312-cf96-143b46db0211

Information about a rebooted device needs to be displayed with an ID of 260faff9-2d31-4312-cf96-143b46db0211 using the Cisco SD-WAN vManage Administration APIs. The API documentation states that deviceId is a required request parameter. Fill in the blank to create the REST call.

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:
"deviceid":

NEW QUESTION 54

What is the purpose of using the Cisco SD-WAN vManage Certificate Management API?

- A. to generate a CSR
- B. to allocate resources to the certificate server
- C. to request a certificate from the certificate server
- D. to enable vManage Center

Answer: A

NEW QUESTION 55

Which action allows for creating a Python script to pull inventory for Cisco SD-WAN Viptela devices using the Viptela library in the code?

- A. from urllib.request import Viptela
- B. from viptela.devices import Viptela
- C. from viptela.viptela import Viptela
- D. from viptela.library import Viptela

Answer: B

NEW QUESTION 59

FILL BLANK

Fill in the blank to complete the URL for the Cisco SD-WAN API that retrieves a list of users that are logged into a device.

http://<vmanage-ip-address>/dataservice/device/ deviceid=<deviceid>>

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:
interface?

NEW QUESTION 60

Which two API calls must be issued to attach a device template in Cisco SD-WAN? (Choose two.)

- A. "monitor device action status" GET API request with the device ID to display the status of the attach action
- B. "monitor device action status" GET API request with the process ID to display the status of the attach action
- C. PUT call to initiate the attach action
- D. POST call to initiate the attach action
- E. GET call to initiate the attach action

Answer: BD

NEW QUESTION 61

During a network outage, a network administrator used the Cisco SD-WAN vManage Troubleshooting Dashboard APIs to troubleshoot the cause of the issue. Which detail is captured during troubleshooting with these APIs?

- A. VPN health
- B. public cloud resources
- C. connections summary
- D. OMP connection health

Answer: C

NEW QUESTION 63

FILL BLANK

Fill in the blank to complete the URL for an API call to Cisco SD-WAN to display the history of the Bidirectional Forwarding Detection sessions that run on a vEdge router.

https://<vmanage-ip-address>/dataservice/device/ deviceid=<deviceid>

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

bfd/synced/sessions?

NEW QUESTION 66

```
{
  "id": "L_123456",
  "organizationId": 1357924,
  "name": "Long Island Office",
  "timeZone": "America/Los_Angeles",
  "tags": "tag1 tag2",
  "type": "combined",
  "disableMyMerakiCom": false
}
```

Refer to the exhibit. Which two parameters are mandatory when the Cisco Meraki API is used to create a network? (Choose two.)

- A. timezone
- B. disableMyMerakiCom
- C. type
- D. tags
- E. organizationId

Answer: AE

NEW QUESTION 69

.....

THANKS FOR TRYING THE DEMO OF OUR PRODUCT

Visit Our Site to Purchase the Full Set of Actual 300-435 Exam Questions With Answers.

We Also Provide Practice Exam Software That Simulates Real Exam Environment And Has Many Self-Assessment Features. Order the 300-435 Product From:

<https://www.2passeasy.com/dumps/300-435/>

Money Back Guarantee

300-435 Practice Exam Features:

- * 300-435 Questions and Answers Updated Frequently
- * 300-435 Practice Questions Verified by Expert Senior Certified Staff
- * 300-435 Most Realistic Questions that Guarantee you a Pass on Your FirstTry
- * 300-435 Practice Test Questions in Multiple Choice Formats and Updatesfor 1 Year