



**Cisco**

## **Exam Questions 200-901**

Developing Applications and Automating Workflows using Cisco Core Platforms (DEVASC)

### NEW QUESTION 1

Fill in the blanks to complete the python script to request a service ticket using the APIC-EM rest API for the user "devnetuser".

```
import requests
import json
controller = 'devnetapi.cisco.com/sandbox/apic_em'
url = "https://" + controller + "/api/va/ticket"
payload = { 'username': ' ', 'password': '371274739' }
header = { 'Content-type': 'application/json' }
response =  post(url, data=json.dumps(payload), \
headers= , verify=False)
r_json = response.json()
print(r_json)
ticket = r_json["response"]["serviceTicket"]
print(ticket)
```

- A. Mastered
- B. Not Mastered

Answer: A

### Explanation:

Solution as below

```
import requests
import json
controller = 'devnetapi.cisco.com/sandbox/apic_em'
url = "https://" + controller + "/api/va/ticket"
payload = { 'username': 'devnetuser', 'password': '371387657' }
header = { 'Content-type': 'application/json' }
response = requests.post(url, data=json.dumps(payload), \
headers=header, verify=False)
r_json = response.json()
print(r_json)
ticket = r_json["response"]["serviceTicket"]
print(ticket)
```

### NEW QUESTION 2

Refer to the exhibit.

```
---
- hosts: switch2960cx
  gather_facts: no

  tasks:
    - ios_12_interface:
      name: GigabitEthernet0/1
      state: unconfigured

    - ios_12_interface:
      name: GigabitEthernet0/1
      mode: trunk
      native_vlan: 1
      trunk_allowed_vlans: 6-8
      state: present

    - ios_vlan:
      vlan_id: 6
      name: guest-vlan
      interfaces:
        - GigabitEthernet0/2
        - GigabitEthernet0/3

    - ios_vlan:
      vlan_id: 7
      name: corporate-vlan
      interfaces:
        - GigabitEthernet0/4

    - ios_vlan:
      vlan_id: 8
      name: lot-vlan
      interfaces:
        - GigabitEthernet0/5
```

Which two statement describe the configuration of the Ansible script is run? (Choose two.)

- A. Traffic on port 0/2 and 0/3 is connected to port 0/6.
- B. Traffic from ports 0/2 to 0/5 can flow on port 0/1 due to the trunk.
- C. Traffic can flow between ports 0/2 to 0/5 due to the trunk on port 0/1.
- D. GigabitEthernet0/2 and GigabitEthernet0/3 are access ports for VLAN 6.
- E. GiabitEthernet0/1 is left unconfigured.

**Answer:** BD

### NEW QUESTION 3

Refer to the exhibit.

```

container ethernet {
  must "../if:location" {
    description
      "An ethernet interface must specify the physical location of the ethernet hardware.";
  }
  choice transmission-params {
    case auto {
      leaf auto-negotiate {
        type empty;
      }
    }
    case manual {
      leaf duplex {
        type enumeration {
          enum "half";
          enum "full";
        }
      }
      leaf speed {
        type enumeration {
          enum "10Mb";
          enum "100Mb";
          enum "1Gb";
          enum "10Gb";
        }
      }
    }
  }
  // other ethernet specific params...
}

```

What is represented in this YANG module?

- A. interface management
- B. topology
- C. BGP
- D. OpenFlow

**Answer:** A

### NEW QUESTION 4

Which two items are Cisco DevNet resources? (Choose two.)

- A. TAC support
- B. Bitbucket
- C. Sandbox
- D. Software research
- E. API Documentation

**Answer:** CE

### NEW QUESTION 5

Which way should be used to safely the API keys?

- A. In an environment variable unique to the system database
- B. Encrypted in a configuration file that is separate from the code
- C. Encrypted in the code in a function
- D. Plain text in the code as a constant

**Answer:** B

### NEW QUESTION 6

Refer to the exhibit.

```

#!/bin/bash
read ndir
while [ -d "$ndir" ]
do
  cd $ndir
done
mkdir $ndir

```


What is the action of the Bash script that is shown?

- A. The script waits until input is entered
- B. If the directory exists, the script goes into it until there is no directory with the same name, then it creates a new directory.
- C. The script goes into the directory called "\$ndir" and makes a new directory called "\$ndir"
- D. The script waits until input is entered, then it goes into the directory entered and creates a new directory with the same name.
- E. For all directories in the current folder
- F. The script goes into directory and makes a new directory.

**Answer:** A

#### NEW QUESTION 7

Drag and drop the network automation interfaces from the left onto the transport protocols that they support on the right.



- A. Mastered
- B. Not Mastered

**Answer:** A

#### Explanation:

gRPC = C, NETCONF = A, RESTCONF = B, D

#### NEW QUESTION 8

Which two NETCONF operations cover the RESTCONF GET operation? (Choose two.)

- A. <get>
- B. <edit>
- C. <get-update>
- D. <modify-config>
- E. <get-config>

**Answer:** AE

#### NEW QUESTION 9

Which description of a default gateway is true?

- A. It is a device that receives IP packets that have no explicit next-hop in the routing table.
- B. It is a feature that translates between public and private addresses.
- C. It is a security feature that denies certain traffic.
- D. It is a device that receives Layer 2 frames with an unknown destination address.

**Answer:** A

#### NEW QUESTION 10

Refer to the exhibit.



URL: https://<ASA\_IP>/api/access/global/rules

Method: POST

Payload:

```
{
  "destinationAddress": {
    "kind": "IPv4Address",
    "value": "10.1.1.1"
  },
  "remarks": [ ],
  "active": true,
  "permit": true,
  "sourceAddress": {
    "kind": "IPv4Address",
    "value": "192.168.1.1"
  }
}
```

Response Status Code: 400 Bad Request

```
{
  "messages": [
    {
      "level": "Error",
      "code": "JSON-PARSE-ERROR",
      "details": "Unexpected character ('\"' (code 34)):"
    }
  ]
}
```

What caused the error in this API request?

- A. The API resource does not support the POST operation.
- B. The API resource does not support JSON format payloads.
- C. The submitted JSON payload includes a field that is not supported by the API resources.
- D. The submitted JSON payload has a formatting issue.

Answer: D

#### NEW QUESTION 10

Drag and drop the functionalities from the left onto correct networking devices on the right.

ports are different broadcast domain by default	Firewall
ports can be in the same broadcast domain	Load Balancer
uses traffic inspection to make routing decisions	Router
blocks networks traffic by default	Switch

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

1 – D, 2 – C, 3 – A, 4 – B

#### NEW QUESTION 14

Which two statements describe the advantages of using a version control system? (Choose two.)

- A. It allows for branching and merging so that different tasks are worked on in isolation before they are merged into a feature or master branch.
- B. It allows multiple engineers to work against the same code and configuration files and manage differences and conflicts.
- C. It provides tooling to automate application builds and infrastructure provisioning.
- D. It allows developers to write effective unit tests.
- E. It provides a system to track User Stories and allocate to backlogs.

Answer: AB

#### NEW QUESTION 16


An application calls a REST API and expects a result set of more than 550 records, but each time the call is made, only 25 are returned. Which feature limits the amount of data that is returned by the API?

- A. pagination
- B. payload limit
- C. rate limiting
- D. service timeouts


Answer: A

#### NEW QUESTION 18

Refer to the exhibit.



Given the API documentation for the UCS SDK python class, UcsHandle, which code snippet creates a handle instance?



- A. Option A
- B. Option B
- C. Option C
- D. Option D

Answer: B

#### NEW QUESTION 23

Which Cisco DevNet resource allows access to products in a development lab to explore, learn, and build application that use Cisco APLs?

- A. DevNet communities
- B. DevNet code Exchange
- C. DevNet Automation Exchange

D. DevNet sandbox

**Answer:** D

#### NEW QUESTION 26

Refer to the exhibit.

```
def process_devices(dnac, token):  
    url = "https://(())/api/v1/network-device".format(dnac['host'])  
    headers["x-auth-token"] = token  
    response = requests.get(url, headers=headers, verify=False)  
    data = response.json()  
    for item in data['response']:  
        print(item["hostname"], " ", item["managementIpAddress"])
```

What is the function of the python script?

- A. Count and print the total number of available devices.
- B. Iterate over a list of network devices and write all device names and management IP addresses to an output file.
- C. Iterate over a list of network devices and write all device type and associated management IP address.
- D. For each device that is returned, display the device and, for each device, print the device name and management IP address.
- E. Loop through the returned list of network devices and, for each device, print the device name management IP address.

**Answer:** E

#### NEW QUESTION 28

Which action does the Git command git merge allow the development to perform?

- A. Combine multiple sequence of commits into one unified history.
- B. Push changes to the remote repository
- C. Switch between branches
- D. Create, list, rename, and delete branches

**Answer:** A

#### NEW QUESTION 29

Drag and drop the descriptions from the left onto correct application deployment models on the right.

provides a low-latency compute capability close to the data source	Public Cloud
environment where you pay only for the resources that you consume	
offers a self-service, elastic compute environment from a dedicated set of physical resources	Private Cloud
provides an approach for overflow traffic to burst out to meet peak demands	Hybrid Cloud
shared compute platform that is offered over the Internet	Edge Computing

- A. Mastered
- B. Not Mastered

**Answer:** A

#### Explanation:

1 – B, 2 – E, 3 – C, 4 – D, 5 – A

#### NEW QUESTION 30

Refer to the exhibit.



```
#!/bin/bash
<item 1>='date +%b-%d-%y'

<item 2>=/home/usr/path/backup-$BACKUPTIME.tar.gz

<item 3>=/home/usr/path/data_folder

tar -cpzf $DESTINATION $SOURCEFOLDER
```

Drag and drop the variables from the left onto the item numbers on the right that match the missing assignments in the exhibit.

BACKUPTIME	<item 1>
SOURCEFOLDER	<item 2>
DESTINATION	<item 3>

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:  
1 – A, 2 – C, 3 – B

NEW QUESTION 34

Which two descriptions can be given to an application that is interacting with a webhook? (Choose two.)

- A. Processor
- B. Codec
- C. Listener
- D. Receiver
- E. Transaction monitor

Answer: CD

NEW QUESTION 36

Which two encoding formats do YANG interfaces support?

- A. JSON
- B. XML
- C. XHTML
- D. Plain text
- E. BER

Answer: AB

NEW QUESTION 37

Fill in the blanks to complete the Python script to update the Webex Teams membership of a room using the Python requests library import requests

```
import requests
url = "https://api.ciscospark.com/v1/memberships/Y2lzY29zcGFiYzov371508156INISVAvOTJm2RkOWEiNjc1ZC00YTQxLTljNDEtMmFiZGY4OWY0NGY0QjExNzJkNmYwLTJlY2MtMTFiOS1iOWI3LWNmMjg3MTJhYTgzNw"

payload = [{"isModerator": true}]
headers = {
    'Authorization': 'Bearer ',
    'Content-Type': 'application/json'
}

response = requests. (PATCH url headers= , data = )
print(response.text.encode('utf8'))
```

- A. Mastered
- B. Not Mastered

Answer: A



**Explanation:**

request, headers , payload

**NEW QUESTION 42**

What are two advantages of the Model-view-controller software design pattern? (Choose two.)

- A. simplifies network automation
- B. allows for multiple views of the same model
- C. makes code easier to deploy using CI/CD pipelines
- D. reduces need for error handling
- E. separates responsibilities of the code, which makes future modifications easier

**Answer:** BE

**NEW QUESTION 45**

What are two security benefits of a Docker-based application?

- A. easier to patch because Docker containers include only dependencies that the application requires
- B. prevents information leakage that can occur when unhandled exceptions are returned in HTTP responses
- C. allows for separation of application that traditionally run in the same host
- D. natively secures access to secrets that are used by the running application
- E. guarantees container images are secured and free of vulnerabilities

**Answer:** AC

**NEW QUESTION 50**

A company has written a script that creates a log bundle from the Cisco DNA Center every day. The script runs without error and the bundles are produced. However, when the script is run during business hours, report poor voice quality of phones calls. What explains this behavior?

- A. The application is running in the Voice VLAN and causes delays and jitter in the subnet.
- B. The speed and duplex settings in Cisco DNA Center are sot incorrectly, which causes the transfer to be too slow.
- C. 9 The script is written in a low-level programming language where there is no memory safet
- D. This causes a buffer overflow and disruption on the network.
- E. Generating the logs causes the CPU on the network controller to spike, which causes delays m forwarding the voice IP packets.

**Answer:** D

**NEW QUESTION 53**

Fill in the blanks to complete the statement.

Given a username of “devnet” And a password “Cisco123”, applications must create a base64 encoding of the string”\_\_\_\_\_” when sanding HTTP requests to an API that uses \_\_\_\_\_ authentication.

Given a username of "devnet" and a password of "cisco123", applications must create a base64 encoding of the string \_\_\_\_\_ " when sending HTTP requests to an API that uses \_\_\_\_\_ authentication.

- A. Mastered
- B. Not Mastered

**Answer:** A

**Explanation:**

Given a username of "devnet" and a password of "cisco123", applications must create a base64 encoding of the string \_\_\_\_\_ " when sending HTTP requests to an API that uses \_\_\_\_\_ authentication.

**NEW QUESTION 58**

Which statement describes the benefit of using functions in programming?

- A. Functions allow problems to be split into simpler, smaller groups, and reduce code repetition, which makes the code easier to read.
- B. Functions ensure that a developer understands the inner logic contained before using them as part of a script or application.
- C. Functions create the implementation of secret and encrypted algorithms.
- D. Functions store mutable values within a script 01 application.

**Answer:** A

**NEW QUESTION 62**

Refer to the exhibit.

```
$ pyang -f tree Cisco-IOS-XE-native.yang
module: Cisco-IOS-XE-native
  +--rw native
    +--rw logging
      +--rw monitor|
        +--rw severity? logging-level-type

$ curl --insecure -v -X PATCH \
  "https://ios-xe-mgmt-latest.cisco.com:9443/restconf/data/Cisco-IOS-XE-native:native" \
  -H 'Authorization: Basic ZGV2ZWxvcGVyOklMxkZnVMTIzNDU=' -H 'Accept: application/yang-data+json' \
  -H 'Content-Type: application/yang-data+json' \
  -d '{ "Cisco-IOS-XE-native:native" : { "logging" : { "monitor" : { "severity" : "alerts" }} } }'
> ...
< ...
< HTTP/1.1 204 No Content
```

The definition of the YANG module and a RESTCONF query sent to a Cisco IOS XE device is shown. Which statement is correct if the RESTCONF interface responds with a 204 status code?

- A. The query failed at retrieving the logging severity level.
- B. The query failed to set the logging severity level due to an invalid path.
- C. The query retrieved the logging severity level.
- D. The query updated the logging severity level or created it if not present on the device.

**Answer:** D

#### NEW QUESTION 63

.....

## Thank You for Trying Our Product

### We offer two products:

1st - We have Practice Tests Software with Actual Exam Questions

2nd - Questions and Answers in PDF Format

### 200-901 Practice Exam Features:

- \* 200-901 Questions and Answers Updated Frequently
- \* 200-901 Practice Questions Verified by Expert Senior Certified Staff
- \* 200-901 Most Realistic Questions that Guarantee you a Pass on Your First Try
- \* 200-901 Practice Test Questions in Multiple Choice Formats and Updates for 1 Year

**100% Actual & Verified — Instant Download, Please Click**  
**[Order The 200-901 Practice Test Here](#)**