Fortinet

Exam Questions NSE7_SDW-7.0

Fortinet NSE 7 - SD-WAN 7.0

NEW QUESTION 1
Refer to the exhibit.

```
ike 0:T_INET_0_0:214: received informational request
ike 0:T_INET_0_0:214: processing notify type SHORTCUT_QUERY
ike 0:T_INET_0_0: recv shortcut-query 9065761962601467474
07409008f7fbd17e/0000000000000000 192.2.0.1 10.0.1.101->10.0.2.101 psk 64 ppk 0 ttl 32
nat 0 ver 2 mode 0
ike 0:T_INET_0: iif 20 10.0.1.101->10.0.2.101 route lookup oif 20 T_INET_0 gwy
10.201.1.1
ike 0:T_INET_0_1: forward shortcut-query 9065761962601467474
07409008f7fbd17e/0000000000000000 192.2.0.1 10.0.1.101->10.0.2.101 psk 64 ppk 0 ttl 31
ver 2 mode 0, ext-mapping 192.2.0.1:500
```

Which statement about the role of the ADVPN device in handling traffic is true?

A. This is a spoke that has received a query from a remote hub and has forwarded the response to its hub.
B. Two hubs, 10.0.1.101 and 10.0.2.101, are receiving and forwarding queries between each other.
C. This is a hub that has received a query from a spoke and has forwarded it to another spoke.
D. Two spokes, 192.2.0.1 and 10.0.2.101, forward their queries to their hubs.

Answer: C

NEW QUESTION 2
What does enabling the exchange-interface-ip setting enable FortiGate devices to exchange?

A. The gateway address of their IPsec interfaces
B. The tunnel ID of their IPsec interfaces
C. The IP address of their IPsec interfaces
D. The name of their IPsec interfaces

Answer: C

NEW QUESTION 3
Which two statements about SLA targets and SD-WAN rules are true? (Choose two.)

A. When configuring an SD-WAN rule, you can select multiple SLA targets of the same performance SLA.
B. SD-WAN rules use SLA targets to check if the preferred members meet the SLA requirements.
C. SLA targets are used only by SD-WAN rules that are configured with Lowest Cost (SLA) or Maximize Bandwidth (SLA) as strategy.
D. Member metrics are measured only if an SLA target is configured.

Answer: BC

NEW QUESTION 4
Which are three key routing principles in SD-WAN? (Choose three.)

A. FortiGate performs route lookups for new sessions only.
B. Regular policy routes have precedence over SD-WAN rules.
C. SD-WAN rules have precedence over ISDB routes.
D. By default, SD-WAN members are skipped if they do not have a valid route to the destination.
E. By default, SD-WAN rules are skipped if the best route to the destination is not an SD-WAN member.

Answer: BDE

NEW QUESTION 5
In the default SD-WAN minimum configuration, which two statements are correct when traffic matches the default implicit SD-WAN rule? (Choose two)

A. Traffic has matched none of the FortiGate policy routes.
B. Matched traffic failed RPF and was caught by the rule.
C. The FIB lookup resolved interface was the SD-WAN interface.
D. An absolute SD-WAN rule was defined and matched traffic.

Answer: AC

NEW QUESTION 6
Refer to the exhibit.

```
branch1_fgt # diagnose sys sdwan service 3

Service(3): Address Mode(IPV4) flags=0x200 use-shortcut-sla
  Gen(2), TOS(0x0/0x0), Protocol(0: 1->65535), Mode(priority), link-cost-factor(packet-
loss), link-cost-threshold(0), heath-check(VPN_PING)
  Members(3):
    1: Seq_num(3 T_INET_0_0), alive, packet loss: 2.000%, selected
    2: Seq_num(4 T_MPLS_0), alive, packet loss: 4.000%, selected
    3: Seq_num(5 T_INET_1_0), alive, packet loss: 12.000%, selected
  Src address(1):
        10.0.1.0-10.0.1.255

  Dst address(1):
        10.0.0.0-10.255.255.255

branch1_fgt (3) # show
config service
    edit 3
        set name "Corp"
        set mode priority
        set dst "Corp-net"
        set src "LAN-net"
        set health-check "VPN_PING"
        set link-cost-factor packet-loss
        set link-cost-threshold 0
        set priority-members 5 3 4
    next
end
```

The exhibit shows the SD-WAN rule status and configuration.
Based on the exhibit, which change in the measured packet loss will make T_INET_1_0 the new preferred member?

A. When all three members have the same packet loss.
B. When T_INET_0_0 has 4% packet loss.
C. When T_INET_0_0 has 12% packet loss.
D. When T_INET_1_0 has 4% packet loss.

Answer: A

NEW QUESTION 7
Which two statements are correct when traffic matches the implicit SD-WAN rule? (Choose two.)

A. The sdwan_service_id flag in the session information is 0.
B. All SD-WAN rules have the default setting enabled.
C. Traffic does not match any of the entries in the policy route table.
D. Traffic is load balanced using the algorithm set for the v4-ecmp-mode setting.

Answer: AC

Explanation:
sdwan_service_id is 0 = match SD-WAN implicit rule, study guide 7.0 page 120, 7.2 page 149 SD-WAN rules internally are interpreted as a Policy route, so when the traffic doesn't match with any policy route, it will be flowing by implict policy.

NEW QUESTION 8
Refer to the exhibit.

```
FortiGate # diagnose sys session list

session info: proto=1 proto_state=00 duration=25 expire=34 timeout=0 flags=00000000
socktype=0 sockport=0 av_idx=0 use=3
origin-shaper=
reply-shaper=
per_ip_shaper=
class_id=0 ha_id=0 policy_dir=0 tunnel=/ vlan_cos=0/255
state=dirty may_dirty
statistic(bytes/packets/allow_err): org=84/1/1 reply=84/1/1 tuples=2
tx speed(Bps/kbps): 0/0 rx speed(Bps/kbps): 0/0
orgin->sink: org pre->post, reply pre->post dev=5->4/4->5 gwy=192.168.73.2/10.0.1.10
hook=post dir=org act=snat 10.0.1.10:2246->8.8.8.8:8(192.168.73.132:62662)
hook=pre dir=reply act=dnat 8.8.8.8:62662->192.168.73.132:0(10.0.1.10:2246)
misc=0 policy_id=1 auth_info=0 chk_client_info=0 vd=0
serial=00000a2c tos=ff/ff app_list=0 app=0 url_cat=0
rpdb_link_id= 80000000 rpdb_svc_id=0 ngfwid=n/a
npu_state=0x040000
total session 1
```

Based on the exhibit, which statement about FortiGate re-evaluating traffic is true?

A. The type of traffic defined and allowed on firewall policy ID 1 is UDP.
B. FortiGate has terminated the session after a change on policy ID 1.
C. Changes have been made on firewall policy ID 1 on FortiGate.
D. Firewall policy ID 1 has source NAT disabled.

Answer: C

NEW QUESTION 9
Which two settings can you configure to speed up routing convergence in BGP? (Choose two.)

A. update-source
B. set-route-tag
C. holdtime-timer
D. link-down-failover

Answer: CD

NEW QUESTION 10
Which components make up the secure SD-WAN solution?

A. Application, antivirus, and URL, and SSL inspection
B. Datacenter, branch offices, and public cloud
C. FortiGate, FortiManager, FortiAnalyzer, and FortiDeploy
D. Telephone, ISDN, and telecom network.

Answer: C

NEW QUESTION 10
What are two reasons why FortiGate would be unable to complete the zero-touch provisioning process? (Choose two.)

A. The FortiGate cloud key has not been added to the FortiGate cloud portal.
B. FortiDeploy has connected with FortiGate and provided the initial configuration to contact FortiManager
C. The zero-touch provisioning process has completed internally, behind FortiGate.
D. FortiGate has obtained a configuration from the platform template in FortiGate cloud.
E. A factory reset performed on FortiGate.

Answer: AC

NEW QUESTION 13
Which two statements about the SD-WAN zone configuration are true? (Choose two.)

A. The service-sla-tie-break setting enables you to configure preferred member selection based on the best route to the destination.
B. You can delete the default zones.
C. The default zones are virtual-wan-link and SASE.
D. An SD-WAN member can belong to two or more zones.

Answer: AC

NEW QUESTION 14
Refer to the exhibit.

```
config system sdwan
    set fail-detect enable
    set fail-alert-interfaces "port5"
    config health-check
        edit "Level3_DNS"
            set update-cascade-interface enable
            set members 1 2
        next
        edit "HQ"
            set update-cascade-interface enable
            set members 3
        next
    end
end
```

Based on the exhibit, which action does FortiGate take?

A. FortiGate bounces port5 after it detects all SD-WAN members as dead.
B. FortiGate fails over to the secondary device after it detects all SD-WAN members as dead.
C. FortiGate brings up port5 after it detects all SD-WAN members as alive.
D. FortiGate brings down port5 after it detects all SD-WAN members as dead.

Answer: B

NEW QUESTION 15
Which two conclusions for traffic that matches the traffic shaper are true? (Choose two.)

```
# diagnose firewall shaper traffic-shaper list name VoIP_Shaper
name VoIP_Shaper
maximum-bandwidth 6250 KB/sec
guaranteed-bandwidth 2500 KB/sec
current-bandwidth 93 KB/sec
priority 2
overhead 0
tos ff
packets dropped 0
bytes dropped 0
```

A. The traffic shaper drops packets if the bandwidth is less than 2500 KBps.
B. The measured bandwidth is less than 100 KBps.
C. The traffic shaper drops packets if the bandwidth exceeds 6250 KBps.
D. The traffic shaper limits the bandwidth of each source IP to a maximum of 6250 KBps.

Answer: BC

NEW QUESTION 18
Two hub-and-spoke groups are connected through a site-to-site IPsec VPN between Hub 1 and Hub 2. The administrator configured ADVPN on both hub-and-spoke groups.

Which two outcomes are expected if a user in Toronto sends traffic to London? (Choose two.)

A. London generates an IKE information message that contains the Toronto public IP address.
B. Traffic from Toronto to London triggers the dynamic negotiation of a direct site-to-site VPN.
C. Toronto needs to establish a site-to-site tunnel with Hub 2 to bypass Hub 1.
D. The first packets from Toronto to London are routed through Hub 1 then to Hub 2.

Answer: BD

NEW QUESTION 23
Refer to the exhibit.

```
config system interface
    edit "port2"
        set vdom "root"
        set ip 192.2.0.9 255.255.255.248
        set allowaccess ping
        set type physical
        set role wan
        set snmp-index 2
        set preserve-session-route enable
    next
end
```

Based on the exhibit, which two actions does FortiGate perform on traffic passing through port2? (Choose two.)

A. FortiGate does not change the routing information on existing sessions that use a valid gateway, after a route change.
B. FortiGate performs routing lookups for new sessions only, after a route change.
C. FortiGate always blocks all traffic, after a route change.
D. FortiGate flushes all routing information from the session table, after a route change.

Answer: AB

NEW QUESTION 26
Which two statements about SD-WAN central management are true? (Choose two.)

A. The objects are saved in the ADOM common object database.
B. It does not support meta fields.
C. It uses templates to configure SD-WAN on managed devices.
D. It supports normalized interfaces for SD-WAN member configuration.

Answer: AC

Explanation:
Normalized interfaces are not supported for SD-WAN templates. You can create multiple SD-WAN zones and add interface members to the SD-WAN zones. You must bind the interface members by name to physical interfaces or VPN interfaces.https://docs.fortinet.com/document/fortigate/7.0.0/sd-wan-new-features/794804/new-sd-wan-template

NEW QUESTION 27
Refer to the exhibit.

```
id=20085 trace_id=847 func=print_pkt_detail line=5428 msg="vd-root:0 received a
packet(proto=6, 10.1.10.1:33920->74.125.195.93:443) from port3. flag [.], seq
2018554516, ack 4141536963, win 2238"
id=20085 trace_id=847 func=resolve_ip_tuple_fast line=5508 msg="Find an existing
session, id-000008c1, original direction"
id=20085 trace_id=847 func=shaper_handler line=821 msg="exceeded shaper limit, drop"
```

Which conclusion about the packet debug flow output is correct?

A. The original traffic exceeded the maximum packets per second of the outgoing interface, and the packet was dropped.
B. The reply traffic exceeded the maximum bandwidth configured in the traffic shaper, and the packet was dropped.
C. The original traffic exceeded the maximum bandwidth of the outgoing interface, and the packet was dropped.
D. The original traffic exceeded the maximum bandwidth configured in the traffic shaper, and the packet was dropped.

Answer: D

NEW QUESTION 31
Refer to the exhibits.

```
dc1_fgt # show vpn ipsec phase1-interface T_INET_1_0
config vpn ipsec phase1-interface
    edit "T_INET_1_0"
        set type dynamic
        set interface "port2"
        set ike-version 2
        set keylife 28800
        set peertype any
        set net-device disable
        set proposal aes128-sha256
        set add-route disable
        set psksecret ENC
GayzHJ/UhxCc9FYtwas5o4rkNCMjjNUEj4Q4fZNS6I65RIVF9zum6sJALsU9Cg+1jsXz3ZtIM+WNkHLsXkHqydgS
G/Zx8Vp9Rcht6zKHPectOcFVbaG+UeO3Rw41pmGP/Z3rIz3tdXJxfYSzKjRqggqahsmDovkrKRHTVFUlzA07Zt6W
iPL9co/Zf3cX+Qpnmm38MQ==
    next
end
```

```
dc1_fgt # diagnose vpn tunnel list name T_INET_1_0_0
list ipsec tunnel by names in vd 0
-----------------------------------------------------------
name=T_INET_1_0_0 ver=2 serial=7 100.64.1.9:0->192.2.0.9:0 tun_id=192.2.0.9 dst_mtu=0
dpd-link=on weight=1
bound_if=4 lgwy=static/1 tun=tunnel/255 mode=dial_inst/3 encap=none/8832
options[2280]=rgwy-chg frag-rfc  run_state=0 accept_traffic=1 overlay_id=0
parent=T_INET_1_0 index=0
proxyid_num=1 child_num=0 refcnt=6 ilast=17 olast=23464 ad=/0
stat: rxp=0 txp=0 rxb=0 txb=0
dpd: mode=on-demand on=1 idle=20000ms retry=3 count=0 seqno=1
natt: mode=none draft=0 interval=0 remote_port=0
proxyid=T_INET_1_0_0 proto=0 sa=1 ref=2 serial=1 add-route
   src: 0:0.0.0.0-255.255.255.255:0
   dst: 0:10.0.1.0-10.0.1.255:0
   SA:   ref=3 options=20683 type=00 soft=0 mtu=1280 expire=972/0B replaywin=2048
         seqno=1 esn=0 replaywin_lastseq=00000000 itn=0 qat=0 hash_search_len=1
   life: type=01 bytes=0/0 timeout=1790/1800
   dec: spi=02f9844e esp=aes key=16 7fb5011247248d3a45ac3d802d8c8d64
        ah=sha1 key=20 bb217ce87ae060f27823b0050005233811993a303
   enc: spi=ffc6576a esp=aes key=16 825bddbc5c995feb70411a773867c2d0
        ah=sha1 key=20 02db4176f7f21fae7d141526099a707f639893f1
   dec:pkts/bytes=0/0, enc:pkts/bytes=0/0
```

Which two statements about the IPsec VPN configuration and the status of the IPsec VPN tunnel are true? (Choose two.)

A. FortiGate does not install IPsec static routes for remote protected networks in the routing table.
B. The phase 1 configuration supports the network-overlay setting.
C. FortiGate facilitated the negotiation of the T_INET_1_0_0 ADVPN shortcut over T_INET_1_0.
D. Dead peer detection is disabled.

Answer: AB

NEW QUESTION 34
Refer to the exhibit.

```
branch1_fgt # diagnose sys sdwan service 1

Service(3): Address Mode(IPV4) flags=0x200 use-shortcut-sla
  Gen(6), TOS(0x0/0x0), Protocol(0: 1->65535), Mode(manual)
  Members(2):
     1: Seq_num(3 T_INET_0_0), alive, selected
     2: Seq_num(4 T_INET_1_0), alive, selected
  Src address(1):
        10.0.1.0-10.0.1.255

  Dst address(1):
        10.0.0.0-10.255.255.255


branch1_fgt # diagnose sys sdwan member | grep T_INET_
Member(3): interface: T_INET_0_0, flags=0x4 , gateway: 100.64.1.1, priority: 10 1024,
weight: 0
Member(4): interface: T_INET_1_0, flags=0x4 , gateway: 100.64.1.9, priority: 0 1024,
weight: 0

branch1_fgt # get router info routing-table all | grep T_INET_
S       10.0.0.0/8 [1/0] via T_INET_1_0 tunnel 100.64.1.9
```

An administrator is troubleshooting SD-WAN on FortiGate. A device behind branch1_fgt generates traffic to the 10.0.0.0/8 network. The administrator expects the traffic to match SD-WAN rule ID 1 and be routed over T_INET_0_0. However, the traffic is routed over T_INET_1_0.
Based on the output shown in the exhibit, which two reasons can cause the observed behavior? (Choose two.)

A. The traffic matches a regular policy route configured with T_INET_1_0 as the outgoing device.
B. T_INET_1_0 has a lower route priority value (higher priority) than T_INET_0_0.
C. T_INET_0_0 does not have a valid route to the destination.
D. T_INET_1_0 has a higher member configuration priority than T_INET_0_0.

Answer: AC

Explanation:
https://community.fortinet.com/t5/FortiGate/Technical-Tip-Assigning-Priority-to-SD-WAN-Members-for-Defau

---

NEW QUESTION 38
Which statement about using BGP for ADVPN is true?

A. IBGP is preferred over EBGP, because IBGP preserves next hop information.
B. You must use BGP to route traffic for both overlay and underlay links.
C. You must configure BGP communities.

D. You must configure AS path prepending.

Answer: A

NEW QUESTION 42
......