



# Amazon-Web-Services

## Exam Questions SOA-C02

AWS Certified SysOps Administrator - Associate (SOA-C02)

## About Exambible

*[Your Partner of IT Exam](#)*

## Found in 1998

Exambible is a company specialized on providing high quality IT exam practice study materials, especially Cisco CCNA, CCDA, CCNP, CCIE, Checkpoint CCSE, CompTIA A+, Network+ certification practice exams and so on. We guarantee that the candidates will not only pass any IT exam at the first attempt but also get profound understanding about the certificates they have got. There are so many alike companies in this industry, however, Exambible has its unique advantages that other companies could not achieve.

## Our Advances

### \* 99.9% Uptime

All examinations will be up to date.

### \* 24/7 Quality Support

We will provide service round the clock.

### \* 100% Pass Rate

Our guarantee that you will pass the exam.

### \* Unique Gurantee

If you do not pass the exam at the first time, we will not only arrange FULL REFUND for you, but also provide you another exam of your claim, ABSOLUTELY FREE!

### NEW QUESTION 1

- (Exam Topic 1)

An organization with a large IT department has decided to migrate to AWS. With different job functions in the IT department, it is not desirable to give all users access to all AWS resources. Currently, the organization handles access via LDAP group membership. What is the BEST method to allow access using current LDAP credentials?

- A. Create an AWS Directory Service Simple AD. Replicate the on-premises LDAP directory to Simple AD.
- B. Create a Lambda function to read LDAP groups and automate the creation of IAM users.
- C. Use AWS CloudFormation to create IAM roles. Deploy Direct Connect to allow access to the on-premises LDAP server.
- D. Federate the LDAP directory with IAM using SAML. Create different IAM roles to correspond to different LDAP groups to limit permissions.

**Answer: D**

### NEW QUESTION 2

- (Exam Topic 1)

A company has an application that is running on Amazon EC2 instances in a VPC. The application needs access to download software updates from the internet. The VPC has public subnets and private subnets. The company's security policy requires all EC2 instances to be deployed in private subnets. What should a SysOps administrator do to meet those requirements?

- A. Add an internet gateway to the VPC. In the route table for the private subnets, add a route to the internet gateway.
- B. Add a NAT gateway to a private subnet.
- C. In the route table for the private subnets, add a route to the NAT gateway.
- D. Add a NAT gateway to a public subnet. In the route table for the private subnets, add a route to the NAT gateway.
- E. Add two internet gateways to the VPC.
- F. In the route table for the private subnets and public subnets, add a route to each internet gateway.

**Answer: C**

### NEW QUESTION 3

- (Exam Topic 1)

A SysOps administrator needs to secure the credentials for an Amazon RDS database that is created by an AWS CloudFormation template. The solution must encrypt the credentials and must support automatic rotation. Which solution will meet these requirements?

- A. Create an `AWS::SecretsManager::Secret` resource in the CloudFormation template.
- B. Reference the credentials in the `AWS::RDS::DBInstance` resource by using the `resolve:secretsmanager` dynamic reference.
- C. Create an `AWS::SecretsManager::Secret` resource in the CloudFormation template.
- D. Reference the credentials in the `AWS::RDS::DBInstance` resource by using the `resolve:ssm-secure` dynamic reference.
- E. Create an `AWS::SSM::Parameter` resource in the CloudFormation template.
- F. Reference the credentials in the `AWS::RDS::DBInstance` resource by using the `resolve:ssm` dynamic reference.
- G. Create parameters for the database credentials in the CloudFormation template.
- H. Use the `Ref` intrinsic function to provide the credentials to the `AWS::RDS::DBInstance` resource.

**Answer: A**

### NEW QUESTION 4

- (Exam Topic 1)

A company updates its security policy to prohibit the public exposure of any data in Amazon S3 buckets in the company's account. What should a SysOps administrator do to meet this requirement?

- A. Turn on S3 Block Public Access from the account level.
- B. Create an Amazon EventBridge (Amazon CloudWatch Events) rule to enforce that all S3 objects are private.
- C. Use Amazon Inspector to search for S3 buckets and to automatically reset S3 ACLs if any public S3 buckets are found.
- D. Use S3 Object Lambda to examine S3 ACLs and to change any public S3 ACLs to private.

**Answer: A**

#### Explanation:

Using Amazon S3 Block Public Access

as a centralized way to limit public access. Block Public Access

settings override bucket policies and object permissions. Be sure to enable Block Public Access for all accounts and buckets that you don't want publicly accessible.

<https://aws.amazon.com/premiumsupport/knowledge-center/secure-s3-resources/#:~:text=Using%20Amazon%2>

### NEW QUESTION 5

- (Exam Topic 1)

A company creates a new member account by using AWS Organizations. A SysOps administrator needs to add AWS Business Support to the new account. Which combination of steps must the SysOps administrator take to meet this requirement? (Select TWO.)

- A. Sign in to the new account by using 1AM credential.
- B. Change the support plan.
- C. Sign in to the new account by using root user credential.
- D. Change the support plan.
- E. Use the AWS Support API to change the support plan.
- F. Reset the password of the account root user.
- G. Create an IAM user that has administrator privileges in the new account.

**Answer:** BE

**Explanation:**

The best combination of steps to meet this requirement is to sign in to the new account by using root user credentials and change the support plan, and to create an IAM user that has administrator privileges in the new account.

Signing in to the new account by using root user credentials will allow the SysOps administrator to access the account and change the support plan to AWS Business Support. Additionally, creating an IAM user that has administrator privileges in the new account will ensure that the SysOps administrator has the necessary access to manage the account and make changes to the support plan if necessary.

Reference:

[1] [https://docs.aws.amazon.com/organizations/latest/userguide/orgs\\_manage\\_accounts\\_access.html#orgs\\_ma](https://docs.aws.amazon.com/organizations/latest/userguide/orgs_manage_accounts_access.html#orgs_ma)

**NEW QUESTION 6**

- (Exam Topic 1)

A SysOps administrator is provisioning an Amazon Elastic File System (Amazon EFS) file system to provide shared storage across multiple Amazon EC2 instances. The instances all exist in the same VPC across multiple Availability Zones. There are two instances in each Availability Zone. The SysOps administrator must make the file system accessible to each instance with the lowest possible latency.

Which solution will meet these requirements?

- A. Create a mount target for the EFS file system in the VPC
- B. Use the mount target to mount the file system on each of the instances
- C. Create a mount target for the EFS file system in one Availability Zone of the VPC
- D. Use the mount target to mount the file system on the instances in that Availability Zone
- E. Share the directory with the other instances.
- F. Create a mount target for each instance
- G. Use each mount target to mount the EFS file system on each respective instance.
- H. Create a mount target in each Availability Zone of the VPC. Use the mount target to mount the EFS file system on the instances in the respective Availability Zone.

**Answer:** D

**Explanation:**

A mount target provides an IP address for an NFSv4 endpoint at which you can mount an Amazon EFS file system. You mount your file system using its Domain Name Service (DNS) name, which resolves to the IP address of the EFS mount target in the same Availability Zone as your EC2 instance. You can create one mount target in each Availability Zone in an AWS Region. If there are multiple subnets in an Availability Zone in your VPC, you create a mount target in one of the subnets. Then all EC2 instances in that Availability Zone share that mount target. <https://docs.aws.amazon.com/efs/latest/ug/how-it-works.html>

**NEW QUESTION 7**

- (Exam Topic 1)

An application team uses an Amazon Aurora MySQL DB cluster with one Aurora Replica. The application team notices that the application read performance degrades when user connections exceed 200. The number of user connections is typically consistent around 180, with occasional sudden increases above 200 connections. The application team wants the application to automatically scale as user demand increases or decreases.

Which solution will meet these requirements?

- A. Migrate to a new Aurora multi-master DB cluster
- B. Modify the application database connection string.
- C. Modify the DB cluster by changing to serverless mode whenever user connections exceed 200.
- D. Create an auto scaling policy with a target metric of 195 DatabaseConnections
- E. Modify the DB cluster by increasing the Aurora Replica instance size.

**Answer:** C

**NEW QUESTION 8**

- (Exam Topic 1)

A company has a policy that requires all Amazon EC2 instances to have a specific set of tags. If an EC2 instance does not have the required tags, the noncompliant instance should be terminated.

What is the MOST operationally efficient solution that meets these requirements?

- A. Create an Amazon EventBridge (Amazon CloudWatch Events) rule to send all EC2 instance state changes to an AWS Lambda function to determine if each instance is compliant
- B. Terminate any noncompliant instances.
- C. Create an IAM policy that enforces all EC2 instance tag requirement
- D. If the required tags are not in place for an instance, the policy will terminate noncompliant instance.
- E. Create an AWS Lambda function to determine if each EC2 instance is compliant and terminate an instance if it is noncompliant
- F. Schedule the Lambda function to invoke every 5 minutes.
- G. Create an AWS Config rule to check if the required tags are present
- H. If an EC2 instance is noncompliant, invoke an AWS Systems Manager Automation document to terminate the instance.

**Answer:** D

**Explanation:**

<https://docs.aws.amazon.com/systems-manager/latest/userguide/systems-manager-automation.html>

**NEW QUESTION 9**

- (Exam Topic 1)

A company needs to archive all audit logs for 10 years. The company must protect the logs from any future edits.

Which solution will meet these requirements?

- A. Store the data in an Amazon Elastic Block Store (Amazon EBS) volume
- B. Configure AWS Key Management Service (AWS KMS) encryption.

- C. Store the data in an Amazon S3 Glacier vault
- D. Configure a vault lock policy for write-once, read-many (WORM) access.
- E. Store the data in Amazon S3 Standard-Infrequent Access (S3 Standard-IA). Configure server-side encryption.
- F. Store the data in Amazon S3 Standard-Infrequent Access (S3 Standard-IA). Configure multi-factor authentication (MFA).

**Answer:** B

**Explanation:**

To meet the requirements of the workload, a company should store the data in an Amazon S3 Glacier vault and configure a vault lock policy for write-once, read-many (WORM) access. This will ensure that the data is stored securely and cannot be edited in the future. The other solutions (storing the data in an Amazon Elastic Block Store (Amazon EBS) volume and configuring AWS Key Management Service (AWS KMS) encryption, storing the data in Amazon S3 Standard-Infrequent Access (S3 Standard-IA) and configuring server-side encryption, or storing the data in Amazon S3 Standard-Infrequent Access (S3 Standard-IA) and configuring multi-factor authentication (MFA)) will not meet the requirements, as they do not provide a way to protect the audit logs from future edits.

[https://docs.aws.amazon.com/zh\\_tw/AmazonS3/latest/userguide/object-lock.html](https://docs.aws.amazon.com/zh_tw/AmazonS3/latest/userguide/object-lock.html)

**NEW QUESTION 10**

- (Exam Topic 1)

A company website contains a web tier and a database tier on AWS. The web tier consists of Amazon EC2 instances that run in an Auto Scaling group across two Availability Zones. The database tier runs on an Amazon RDS for MySQL Multi-AZ DB instance. The database subnet network ACLs are restricted to only the web subnets that need access to the database. The web subnets use the default network ACL with the default rules.

The company's operations team has added a third subnet to the Auto Scaling group configuration. After an Auto Scaling event occurs, some users report that they intermittently receive an error message. The error message states that the server cannot connect to the database. The operations team has confirmed that the route tables are correct and that the required ports are open on all security groups.

Which combination of actions should a SysOps administrator take so that the web servers can communicate with the DB instance? (Select TWO.)

- A. On the default ACL
- B. create inbound Allow rules of type TCP with the ephemeral port range and the source as the database subnets.
- C. On the default ACL, create outbound Allow rules of type MySQL/Aurora (3306). Specify the destinations as the database subnets.
- D. On the network ACLs for the database subnets, create an inbound Allow rule of type MySQL/Aurora (3306). Specify the source as the third web subnet.
- E. On the network ACLs for the database subnets, create an outbound Allow rule of type TCP with the ephemeral port range and the destination as the third web subnet.
- F. On the network ACLs for the database subnets, create an outbound Allow rule of type MySQL/Aurora (3306). Specify the destination as the third web subnet.

**Answer:** CD

**NEW QUESTION 10**

- (Exam Topic 1)

The security team is concerned because the number of AWS Identity and Access Management (IAM) policies being used in the environment is increasing. The team tasked a SysOps administrator to report on the current number of IAM policies in use and the total available IAM policies.

Which AWS service should the administrator use to check how current IAM policy usage compares to current service limits?

- A. AWS Trusted Advisor
- B. Amazon Inspector
- C. AWS Config
- D. AWS Organizations

**Answer:** A

**NEW QUESTION 13**

- (Exam Topic 1)

A company has multiple AWS Site-to-Site VPN connections between a VPC and its branch offices. The company manages an Amazon Elasticsearch Service (Amazon ES) domain that is configured with public

access. The Amazon ES domain has an open domain access policy. A SysOps administrator needs to ensure that Amazon ES can be accessed only from the branch offices while preserving existing data.

Which solution will meet these requirements?

- A. Configure an identity-based access policy on Amazon E
- B. Add an allow statement to the policy that includes the Amazon Resource Name (ARN) for each branch office VPN connection.
- C. Configure an IP-based domain access policy on Amazon E
- D. Add an allow statement to the policy that includes the private IP CIDR blocks from each branch office network.
- E. Deploy a new Amazon ES domain in private subnets in a VPC, and import a snapshot from the old domain
- F. Create a security group that allows inbound traffic from the branch office CIDR blocks.
- G. Reconfigure the Amazon ES domain in private subnets in a VPC
- H. Create a security group that allows inbound traffic from the branch office CIDR blocks.

**Answer:** B

**NEW QUESTION 15**

- (Exam Topic 1)

A company is partnering with an external vendor to provide data processing services. For this integration, the vendor must host the company's data in an Amazon S3 bucket in the vendor's AWS account. The vendor is allowing the company to provide an AWS Key Management Service (AWS KMS) key to encrypt the company's data. The vendor has provided an IAM role Amazon Resource Name (ARN) to the company for this integration.

What should a SysOps administrator do to configure this integration?

- A. Create a new KMS key
- B. Add the vendor's IAM role ARN to the KMS key policy
- C. Provide the new KMS key ARN to the vendor.
- D. Create a new KMS key
- E. Create a new IAM user



- F. Add the vendor's IAM role ARN to an inline policy that is attached to the IAM use
- G. Provide the new IAM user ARN to the vendor.
- H. Configure encryption using the KMS managed S3 ke
- I. Add the vendor's IAM role ARN to the KMS managed S3 key polic
- J. Provide the KMS managed S3 key ARN to the vendor.
- K. Configure encryption using the KMS managed S3 ke
- L. Create an S3 bucke
- M. Add the vendor's IAM role ARN to the S3 bucket polic
- N. Provide the S3 bucket ARN to the vendor.

**Answer:** C

#### NEW QUESTION 16

- (Exam Topic 1)

A SysOps administrator recently configured Amazon S3 Cross-Region Replication on an S3 bucket Which of the following does this feature replicate to the destination S3 bucket by default?

- A. Objects in the source S3 bucket for which the bucket owner does not have permissions
- B. Objects that are stored in S3 Glacier
- C. Objects that existed before replication was configured
- D. Object metadata

**Answer:** B

#### NEW QUESTION 20

- (Exam Topic 1)

A SysOps administrator needs to develop a solution that provides email notification and inserts a record into a database every time a file is put into an Amazon S3 bucket.

What is the MOST operationally efficient solution that meets these requirements?

- A. Set up an S3 event notification that targets an Amazon Simple Notification Service (Amazon SNS) topic Create two subscriptions for the SNS topic Use one subscription to send the email notification Use the other subscription to invoke an AWS Lambda function that inserts the record into the database
- B. Set up an Amazon CloudWatch alarm that enters ALARM state whenever an object is created in the S3 bucket Configure the alarm to invoke an AWS Lambda (unction that sends the email notification and inserts the record into the database
- C. Create an AWS Lambda function to send the email notification and insert the record into the database whenever a new object is detected in the S3 bucket invoke the function every minute with an Amazon EventBridge (Amazon CloudWatch Events) scheduled rule.
- D. Set up two S3 event notifications Target a separate AWS Lambda function with each notification Configure one function to send the email notification Configure the other function to insert the record into the database

**Answer:** C

#### NEW QUESTION 24

- (Exam Topic 1)

A company has two VPC networks named VPC A and VPC B. The VPC A CIDR block is 10.0.0.0/16 and the VPC B CIDR block is 172.31.0.0/16. The company wants to establish a VPC peering connection named pcx-12345 between both VPCs.

Which rules should appear in the route table of VPC A after configuration? (Select TWO.)

- A. Destination: 10.0.0.0/16, Target: Local
- B. Destination: 172.31.0.0/16, Target: Local
- C. Destination: 10.0.0.0/16, Target: pcx-12345
- D. Destination: 172.31.0.0/16, Target: pcx-12345
- E. Destination: 10.0.0.0/16. Target: 172.31.0.0/16

**Answer:** AD

#### Explanation:

<https://docs.aws.amazon.com/vpc/latest/peering/vpc-peering-routing.html>

#### NEW QUESTION 25

- (Exam Topic 1)

A SysOps administrator is reviewing AWS Trusted Advisor recommendations. The SysOps administrator notices that all the application servers for a finance application are listed in the Low Utilization Amazon EC2 Instances check. The application runs on three instances across three Availability Zones. The SysOps administrator must reduce the cost of running the application without affecting the application's availability or design.

Which solution will meet these requirements?

- A. Reduce the number of application servers.
- B. Apply rightsizing recommendations from AWS Cost Explorer to reduce the instance size.
- C. Provision an Application Load Balancer in front of the instances.
- D. Scale up the instance size of the application servers.

**Answer:** C

#### NEW QUESTION 27

- (Exam Topic 1)

A SysOps administrator needs to create alerts that are based on the read and write metrics of Amazon Elastic Block Store (Amazon EBS) volumes that are attached to an Amazon EC2 instance. The SysOps administrator creates and enables Amazon CloudWatch alarms for the DiskReadBytes metric and the DiskWriteBytes metric.

A custom monitoring tool that is installed on the EC2 instance with the same alarm configuration indicates that the volume metrics have exceeded the threshold. However, the CloudWatch alarms were not in ALARM state.

Which action will ensure that the CloudWatch alarms function correctly?

- A. Install and configure the CloudWatch agent on the EC2 instance to capture the desired metrics.
- B. Install and configure AWS Systems Manager Agent on the EC2 instance to capture the desired metrics.
- C. Reconfigure the CloudWatch alarms to use the VolumeReadBytes metric and the VolumeWriteBytes metric for the EBS volumes.
- D. Reconfigure the CloudWatch alarms to use the VolumeReadBytes metric and the VolumeWriteBytes metric for the EC2 instance.

**Answer:** A

#### NEW QUESTION 28

- (Exam Topic 1)

A global gaming company is preparing to launch a new game on AWS. The game runs in multiple AWS Regions on a fleet of Amazon EC2 instances. The instances are in an Auto Scaling group behind an

Application Load Balancer (ALB) in each Region. The company plans to use Amazon Route 53 for DNS services. The DNS configuration must direct users to the Region that is closest to them and must provide automated failover.

Which combination of steps should a SysOps administrator take to configure Route 53 to meet these requirements? (Select TWO.)

- A. Create Amazon CloudWatch alarms that monitor the health of the ALB in each Region. Configure Route 53 DNS failover by using a health check that monitors the alarms.
- B. Create Amazon CloudWatch alarms that monitor the health of the EC2 instances in each Region. Configure Route 53 DNS failover by using a health check that monitors the alarms.
- C. Configure Route 53 DNS failover by using a health check that monitors the private address of an EC2 instance in each Region.
- D. Configure Route 53 geoproximity routing. Specify the Regions that are used for the infrastructure.
- E. Configure Route 53 simple routing. Specify the continent, country, and state or province that are used for the infrastructure.

**Answer:** A

#### NEW QUESTION 33

- (Exam Topic 1)

A SysOps administrator wants to manage a web server application with AWS Elastic Beanstalk. The Elastic Beanstalk service must maintain full capacity for new deployments at all times.

Which deployment policies satisfy this requirement? (Select TWO.)

- A. All at once
- B. Immutable
- C. Rebuild
- D. Rolling
- E. Rolling with additional batch

**Answer:** BE

**Explanation:**

<https://docs.aws.amazon.com/elasticbeanstalk/latest/dg/using-features.rolling-version-deploy.html>

#### NEW QUESTION 34

- (Exam Topic 1)

A company needs to implement a managed file system to host Windows file shares for users on premises. Resources in the AWS Cloud also need access to the data on these file shares. A SysOps administrator needs to present the user file shares on premises and make the user file shares available on AWS with minimum latency.

What should the SysOps administrator do to meet these requirements?

- A. Set up an Amazon S3 File Gateway.
- B. Set up an AWS Direct Connect connection.
- C. Use AWS DataSync to automate data transfers between the existing file servers and AWS.
- D. Set up an Amazon FSx File Gateway.

**Answer:** D

**Explanation:**

Amazon FSx provides a fully managed file system that is optimized for Windows-based workloads and can be used to create file shares that can be accessed both on premises and in the AWS Cloud. The file shares that are created in Amazon FSx are highly available and can be accessed with low latency. Additionally, Amazon FSx supports Windows-based authentication, making it easy to integrate with existing Windows user accounts.

References:

[1] <https://aws.amazon.com/fsx/>

[2] <https://aws.amazon.com/storage/file-storage/>

[3] <https://docs.aws.a>

#### NEW QUESTION 35

- (Exam Topic 1)

A SysOps administrator must create an IAM policy for a developer who needs access to specific AWS services. Based on the requirements, the SysOps administrator creates the following policy:

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Action": [
        "storagegateway:Describe*",
        "elasticloadbalancing:*",
        "lambda:*",
        "sqs:List*"
      ],
      "Effect": "Allow",
      "Resource": "*"
    }
  ]
}
```

Which actions does this policy allow? (Select TWO.)

- A. Create an AWS Storage Gateway.
- B. Create an IAM role for an AWS Lambda function.
- C. Delete an Amazon Simple Queue Service (Amazon SQS) queue.
- D. Describe AWS load balancers.
- E. Invoke an AWS Lambda function.

**Answer:** DE

#### NEW QUESTION 40

- (Exam Topic 1)

A company uses AWS Organizations to manage its AWS accounts. A SysOps administrator must create a backup strategy for all Amazon EC2 instances across all the company's AWS accounts.

Which solution will meet these requirements In the MOST operationally efficient way?

- A. Deploy an AWS Lambda function to each account to run EC2 instance snapshots on a scheduled basis.
- B. Create an AWS CloudFormation stack set in the management account to add an AutoBackup=True tag to every EC2 instance
- C. Use AWS Backup In the management account to deploy policies for all accounts and resources.
- D. Use a service control policy (SCP) to run EC2 instance snapshots on a scheduled basis in each account.

**Answer:** B

#### NEW QUESTION 44

- (Exam Topic 1)

A company has an internal web application that runs on Amazon EC2 instances behind an Application Load

Balancer. The instances run in an Amazon EC2 Auto Scaling group in a single Availability Zone. A SysOps administrator must make the application highly available.

Which action should the SysOps administrator take to meet this requirement?

- A. Increase the maximum number of instances in the Auto Scaling group to meet the capacity that is required at peak usage.
- B. Increase the minimum number of instances in the Auto Scaling group to meet the capacity that is required at peak usage.
- C. Update the Auto Scaling group to launch new instances in a second Availability Zone in the same AWS Region.
- D. Update the Auto Scaling group to launch new instances in an Availability Zone in a second AWS Region.

**Answer:** C

#### NEW QUESTION 45

- (Exam Topic 1)

A company is running an application on premises and wants to use AWS for data backup All of the data must be available locally The backup application can write only to block-based storage that is compatible with the Portable Operating System Interface (POSIX)

Which backup solution will meet these requirements?

- A. Configure the backup software to use Amazon S3 as the target for the data backups
- B. Configure the backup software to use Amazon S3 Glacier as the target for the data backups
- C. Use AWS Storage Gateway, and configure it to use gateway-cached volumes
- D. Use AWS Storage Gateway, and configure it to use gateway-stored volumes

**Answer:** D

#### Explanation:

<https://docs.aws.amazon.com/storagegateway/latest/userguide/StorageGatewayConcepts.html>

#### NEW QUESTION 48

- (Exam Topic 1)

A gaming application is deployed on four Amazon EC2 instances in a default VPC. The SysOps administrator has noticed consistently high latency in responses as data is transferred among the four instances. There is no way for the administrator to alter the application code.

The MOST effective way to reduce latency is to relaunch the EC2 instances in:

- A. a dedicated VPC.



- B. a single subnet inside the VPC.
- C. a placement group.
- D. a single Availability Zone.

**Answer:** C

#### NEW QUESTION 49

- (Exam Topic 1)

A company with multiple AWS accounts needs to obtain recommendations for AWS Lambda functions and identify optimal resource configurations for each Lambda function. How should a SysOps administrator provide these recommendations?

- A. Create an AWS Serverless Application Repository and export the Lambda function recommendations.
- B. Enable AWS Compute Optimizer and export the Lambda function recommendations
- C. Enable all features of AWS Organization and export the recommendations from AWS CloudTrailInsights.
- D. Run AWS Trusted Advisor and export the Lambda function recommendations

**Answer:** B

#### NEW QUESTION 54

- (Exam Topic 1)

A company's financial department needs to view the cost details of each project in an AWS account A SysOps administrator must perform the initial configuration that is required to view cost for each project in Cost Explorer Which solution will meet this requirement?

- A. Activate cost allocation tags Add a project tag to the appropriate resources
- B. Configure consolidated billing Create AWS Cost and Usage Reports
- C. Use AWS Budgets Create AWS Budgets reports
- D. Use cost categories to define custom groups that are based on AWS cost and usage dimensions

**Answer:** A

#### NEW QUESTION 55

- (Exam Topic 1)

A company is hosting applications on Amazon EC2 instances. The company is hosting a database on an Amazon RDS for PostgreSQL DB instance. The company requires all connections to the DB instance to be encrypted. What should a SysOps administrator do to meet this requirement?

- A. Allow SSL connections to the database by using an inbound security group rule.
- B. Encrypt the database by using an AWS Key Management Service (AWS KMS) encryption key.
- C. Enforce SSL connections to the database by using a custom parameter group.
- D. Patch the database with SSL/TLS by using a custom PostgreSQL extension.

**Answer:** C

#### Explanation:

<https://docs.aws.amazon.com/AmazonRDS/latest/UserGuide/PostgreSQL.Concepts.General.SSL.htm> Amazon RDS supports SSL/TLS encryption for connections to the database, and this can be enabled by creating a custom parameter group and setting the `rds.force_ssl` parameter to 1. This will ensure that all connections to the database are encrypted, protecting the data and maintaining compliance with the company's requirements.

#### NEW QUESTION 58

- (Exam Topic 1)

A SysOps administrator is troubleshooting connection timeouts to an Amazon EC2 instance that has a public IP address. The instance has a private IP address of 172.31.16.139. When the SysOps administrator tries to ping the instance's public IP address from the remote IP address 203.0.113.12, the response is "request timed out." The flow logs contain the following information:

```
2 123456789010 eni-1235b8ca123456789 203.0.113.12 172.31.16.139 0 0 1 4 336 1432917027 1432917142 ACCEPT OK
2 123456789010 eni-1235b8ca123456789 172.31.16.139 203.0.113.12 0 0 1 4 336 1432917094 1432917142 REJECT OK
```

What is one cause of the problem?

- A. Inbound security group deny rule
- B. Outbound security group deny rule
- C. Network ACL inbound rules
- D. Network ACL outbound rules

**Answer:** D

#### NEW QUESTION 59

- (Exam Topic 1)

A SysOps administrator wants to upload a file that is 1 TB in size from on-premises to an Amazon S3 bucket using multipart uploads. What should the SysOps administrator do to meet this requirement?

- A. Upload the file using the S3 console.
- B. Use the `s3api copy-object` command.
- C. Use the `s3api put-object` command.

D. Use the s3 cp command.

**Answer:** D

**Explanation:**

It's a best practice to use aws s3 commands (such as aws s3 cp) for multipart uploads and downloads, because these aws s3 commands automatically perform multipart uploading and downloading based on the file size. By comparison, aws s3api commands, such as aws s3api create-multipart-upload, should be used only when aws s3 commands don't support a specific upload need, such as when the multipart upload involves multiple servers, a multipart upload is manually stopped and resumed later, or when the aws s3 command doesn't support a required request parameter.  
<https://aws.amazon.com/premiumsupport/knowledge-center/s3-multipart-upload-cli/>

**NEW QUESTION 61**

- (Exam Topic 1)

A development team recently deployed a new version of a web application to production. After the release, penetration testing revealed a cross-site scripting vulnerability that could expose user data. Which AWS service will mitigate this issue?

- A. AWS Shield Standard
- B. AWS WAF
- C. Elastic Load Balancing
- D. Amazon Cognito

**Answer:** B

**Explanation:**

<https://www.imperva.com/learn/application-security/cross-site-scripting-xss-attacks/>

**NEW QUESTION 62**

- (Exam Topic 1)

A SysOps administrator is setting up an automated process to recover an Amazon EC2 instance in the event of an underlying hardware failure. The recovered instance must have the same private IP address and the same Elastic IP address that the original instance had. The SysOps team must receive an email notification when the recovery process is initiated. Which solution will meet these requirements?

- A. Create an Amazon CloudWatch alarm for the EC2 instance, and specify the StatusCheckFailed\_Instance metric.
- B. Add an EC2 action to the alarm to recover the instance.
- C. Add an alarm notification to publish a message to an Amazon Simple Notification Service (Amazon SNS) topic.
- D. Subscribe the SysOps team email address to the SNS topic.
- E. Create an Amazon CloudWatch alarm for the EC2 instance, and specify the StatusCheckFailed\_System metric.
- F. Add an EC2 action to the alarm to recover the instance.
- G. Add an alarm notification to publish a message to an Amazon Simple Notification Service (Amazon SNS) topic.
- H. Subscribe the SysOps team email address to the SNS topic.
- I. Create an Auto Scaling group across three different subnets in the same Availability Zone with a minimum, maximum, and desired size of 1. Configure the Auto Scaling group to use a launch template that specifies the private IP address and the Elastic IP address.
- J. Add an activity notification for the Auto Scaling group to send an email message to the SysOps team through Amazon Simple Email Service (Amazon SES).
- K. Create an Auto Scaling group across three Availability Zones with a minimum, maximum, and desired size of 1. Configure the Auto Scaling group to use a launch template that specifies the private IP address and the Elastic IP address.
- L. Add an activity notification for the Auto Scaling group to publish a message to an Amazon Simple Notification Service (Amazon SNS) topic.
- M. Subscribe the SysOps team email address to the SNS topic.

**Answer:** B

**Explanation:**

You can create an Amazon CloudWatch alarm that monitors an Amazon EC2 instance and automatically recovers the instance if it becomes impaired due to an underlying hardware failure or a problem that requires AWS involvement to repair. Terminated instances cannot be recovered. A recovered instance is identical to the original instance, including the instance ID, private IP addresses, Elastic IP addresses, and all instance metadata. If the impaired instance has a public IPv4 address, the instance retains the public IPv4 address after recovery. If the impaired instance is in a placement group, the recovered instance runs in the placement group. When the StatusCheckFailed\_System alarm is triggered, and the recover action is initiated, you will be notified by the Amazon SNS topic that you selected when you created the alarm and associated the recover action. <https://docs.aws.amazon.com/AWSEC2/latest/UserGuide/ec2-instance-recover.html>

**NEW QUESTION 66**

- (Exam Topic 1)

A company is attempting to manage its costs in the AWS Cloud. A SysOps administrator needs specific company-defined tags that are assigned to resources to appear on the billing report. What should the SysOps administrator do to meet this requirement?

- A. Activate the tags as AWS generated cost allocation tags.
- B. Activate the tags as user-defined cost allocation tags.
- C. Create a new cost category.
- D. Select the account billing dimension.
- E. Create a new AWS Cost and Usage Report.
- F. Include the resource IDs.

**Answer:** B

**Explanation:**

<https://docs.aws.amazon.com/awsaccountbilling/latest/aboutv2/custom-tags.html> "User-defined tags are tags that you define, create, and apply to resources. After you have created and applied the user-defined tags, you can activate them by using the Billing and Cost Management console for cost allocation tracking." To meet this requirement, the SysOps administrator should activate the company-defined tags as user-defined cost allocation tags. This will ensure that the tags appear on the billing report and that the resources can be tracked with the specific tags. The other options (activating the tags as AWS generated cost allocation

tags, creating a new cost category and selecting the account billing dimension, and creating a new AWS Cost and Usage Report and including the resource IDs) will not meet the requirements and are not the correct solutions for this issue.

#### NEW QUESTION 70

- (Exam Topic 1)

A SysOps administrator notices a scale-up event for an Amazon EC2 Auto Scaling group. Amazon CloudWatch shows a spike in the RequestCount metric for the associated Application Load Balancer. The administrator would like to know the IP addresses for the source of the requests. Where can the administrator find this information?

- A. Auto Scaling logs
- B. AWS CloudTrail logs
- C. EC2 instance logs
- D. Elastic Load Balancer access logs

**Answer:** D

#### Explanation:

Elastic Load Balancing provides access logs that capture detailed information about requests sent to your load balancer. Each log contains information such as the time the request was received, the client's IP address, latencies, request paths, and server responses. You can use these access logs to analyze traffic patterns and troubleshoot issues.

<https://docs.aws.amazon.com/elasticloadbalancing/latest/application/load-balancer-access-logs.html>

#### NEW QUESTION 75

- (Exam Topic 1)

A SysOps administrator launches an Amazon EC2 Linux instance in a public subnet. When the instance is running, the SysOps administrator obtains the public IP address and attempts to remotely connect to the instance multiple times. However, the SysOps administrator always receives a timeout error. Which action will allow the SysOps administrator to remotely connect to the instance?

- A. Add a route table entry in the public subnet for the SysOps administrator's IP address.
- B. Add an outbound network ACL rule to allow TCP port 22 for the SysOps administrator's IP address.
- C. Modify the instance security group to allow inbound SSH traffic from the SysOps administrator's IP address.
- D. Modify the instance security group to allow outbound SSH traffic to the SysOps administrator's IP address.

**Answer:** C

#### NEW QUESTION 78

- (Exam Topic 1)

A SysOps administrator is unable to authenticate an AWS CLI call to an AWS service. Which of the following is the cause of this issue?

- A. The IAM password is incorrect.
- B. The server certificate is missing.
- C. The SSH key pair is incorrect.
- D. There is no access key.

**Answer:** C

#### NEW QUESTION 79

- (Exam Topic 1)

A company has an AWS CloudFormation template that creates an Amazon S3 bucket. A user authenticates to the corporate AWS account with their Active Directory credentials and attempts to deploy the CloudFormation template. However, the stack creation fails. Which factors could cause this failure? (Select TWO.)

- A. The user's IAM policy does not allow the cloudformation:CreateStack action.
- B. The user's IAM policy does not allow the cloudformation:CreateStackSet action.
- C. The user's IAM policy does not allow the s3:CreateBucket action.
- D. The user's IAM policy explicitly denies the s3:ListBucket action.
- E. The user's IAM policy explicitly denies the s3:PutObject action.

**Answer:** AC

#### NEW QUESTION 82

- (Exam Topic 1)

A company's reporting job that used to run in 15 minutes is now taking an hour to run. An application generates the reports. The application runs on Amazon EC2 instances and extracts data from an Amazon RDS for MySQL database.

A SysOps administrator checks the Amazon CloudWatch dashboard for the RDS instance and notices that the Read IOPS metrics are high, even when the reports are not running. The SysOps administrator needs to improve the performance and the availability of the RDS instance. Which solution will meet these requirements?

- A. Configure an Amazon ElastiCache cluster in front of the RDS instance.
- B. Update the reporting job to query the ElastiCache cluster.
- C. Deploy an RDS read replica.
- D. Update the reporting job to query the reader endpoint.
- E. Create an Amazon CloudFront distribution.
- F. Set the RDS instance as the origin.
- G. Update the reporting job to query the CloudFront distribution.
- H. Increase the size of the RDS instance.

**Answer:** B

**Explanation:**

Using an RDS read replica will improve the performance and availability of the RDS instance by offloading read queries to the replica. This will also ensure that the reporting job completes in a timely manner and does not affect the performance of other queries that might be running on the RDS instance. Additionally, updating the reporting job to query the reader endpoint will ensure that all read queries are directed to the read replica.

Reference: [1] [https://docs.aws.amazon.com/AmazonRDS/latest/UserGuide/USER\\_ReadRepl.html](https://docs.aws.amazon.com/AmazonRDS/latest/UserGuide/USER_ReadRepl.html)

**NEW QUESTION 85**

- (Exam Topic 1)

A SysOps administrator is testing an application that is hosted on five Amazon EC2 instances. The instances run in an Auto Scaling group behind an Application Load Balancer (ALB). High CPU utilization during load testing is causing the Auto Scaling group to scale out. The SysOps administrator must troubleshoot to find the root cause of the high CPU utilization before the Auto Scaling group scales out.

Which action should the SysOps administrator take to meet these requirements?

- A. Enable instance scale-in protection.
- B. Place the instance into the Standby state.
- C. Remove the listener from the ALB.
- D. Suspend the Launch and Terminate process types.

**Answer:** A

**NEW QUESTION 87**

- (Exam Topic 1)

A company has a stateless application that is hosted on a fleet of 10 Amazon EC2 On-Demand Instances in an Auto Scaling group. A minimum of 6 instances are needed to meet service requirements.

Which action will maintain uptime for the application MOST cost-effectively?

- A. Use a Spot Fleet with an On-Demand capacity of 6 instances.
- B. Update the Auto Scaling group with a minimum of 6 On-Demand Instances and a maximum of 10 On-Demand Instances.
- C. Update the Auto Scaling group with a minimum of 1 On-Demand Instance and a maximum of 6 On-Demand Instances.
- D. Use a Spot Fleet with a target capacity of 6 instances.

**Answer:** A

**NEW QUESTION 91**

- (Exam Topic 1)

A large company is using AWS Organizations to manage its multi-account AWS environment. According to company policy, all users should have read-level access to a particular Amazon S3 bucket in a central account. The S3 bucket data should not be available outside the organization. A SysOps administrator must set up the permissions and add a bucket policy to the S3 bucket.

Which parameters should be specified to accomplish this in the MOST efficient manner?

- A. Specify "" as the principal and PrincipalOrgId as a condition.
- B. Specify all account numbers as the principal.
- C. Specify PrincipalOrgId as the principal.
- D. Specify the organization's management account as the principal.

**Answer:** A

**Explanation:**

<https://aws.amazon.com/blogs/security/control-access-to-aws-resources-by-using-the-aws-organization-of-iam-p>

**NEW QUESTION 93**

- (Exam Topic 1)

A company must ensure that any objects uploaded to an S3 bucket are encrypted. Which of the following actions will meet this requirement? (Choose two.)

- A. Implement AWS Shield to protect against unencrypted objects stored in S3 buckets.
- B. Implement Object access control list (ACL) to deny unencrypted objects from being uploaded to the S3 bucket.
- C. Implement Amazon S3 default encryption to make sure that any object being uploaded is encrypted before it is stored.
- D. Implement Amazon Inspector to inspect objects uploaded to the S3 bucket to make sure that they are encrypted.
- E. Implement S3 bucket policies to deny unencrypted objects from being uploaded to the buckets.

**Answer:** CE

**Explanation:**

<https://docs.aws.amazon.com/AmazonS3/latest/userguide/default-bucket-encryption.html>

You can set the default encryption behavior on an Amazon S3 bucket so that all objects are encrypted when they are stored in the bucket. The objects are encrypted using server-side encryption with either Amazon S3-managed keys (SSE-S3) or AWS Key Management Service (AWS KMS) customer master keys (CMKs).

<https://aws.amazon.com/blogs/security/how-to-prevent-uploads-of-unencrypted-objects-to-amazon-s3/> How to Prevent Uploads of Unencrypted Objects to Amazon S3#

By using an S3 bucket policy, you can enforce the encryption requirement when users upload objects, instead of assigning a restrictive IAM policy to all users.

**NEW QUESTION 96**

- (Exam Topic 1)

A company has multiple Amazon EC2 instances that run a resource-intensive application in a development environment. A SysOps administrator is implementing a solution to stop these EC2 instances when they are not in use.

Which solution will meet this requirement?

- A. Assess AWS CloudTrail logs to verify that there is no EC2 API activity.



- B. Invoke an AWS Lambda function to stop the EC2 instances.
- C. Create an Amazon CloudWatch alarm to stop the EC2 instances when the average CPU utilization is lower than 5% for a 30-minute period.
- D. Create an Amazon CloudWatch metric to stop the EC2 instances when the VolumeReadBytes metric is lower than 500 for a 30-minute period.
- E. Use AWS Config to invoke an AWS Lambda function to stop the EC2 instances based on resource configuration changes.

**Answer:** B

**Explanation:**

<https://docs.aws.amazon.com/AmazonCloudWatch/latest/monitoring/UsingAlarmActions.html#AddingStopActi>

#### NEW QUESTION 100

- (Exam Topic 1)

A company is using Amazon Elastic File System (Amazon EFS) to share a file system among several Amazon EC2 instances. As usage increases, users report that file retrieval from the EFS file system is slower than normal.

Which action should a SysOps administrator take to improve the performance of the file system?

- A. Configure the file system for Provisioned Throughput.
- B. Enable encryption in transit on the file system.
- C. Identify any unused files in the file system, and remove the unused files.
- D. Resize the Amazon Elastic Block Store (Amazon EBS) volume of each of the EC2 instances.

**Answer:** A

#### NEW QUESTION 105

- (Exam Topic 1)

A company has deployed a web application in a VPC that has subnets in three Availability Zones. The company launches three Amazon EC2 instances from an EC2 Auto Scaling group behind an Application Load Balancer (ALB).

A SysOps administrator notices that two of the EC2 instances are in the same Availability Zone, rather than being distributed evenly across all three Availability Zones. There are no errors in the Auto Scaling group's activity history.

What is the MOST likely reason for the unexpected placement of EC2 instances?

- A. One Availability Zone did not have sufficient capacity for the requested EC2 instance type.
- B. The ALB was configured for only two Availability Zones.
- C. The Auto Scaling group was configured for only two Availability Zones.
- D. Amazon EC2 Auto Scaling randomly placed the instances in Availability Zones.

**Answer:** C

**Explanation:**

the autoscaling group is responsible to add the instances in the subnets

#### NEW QUESTION 109

- (Exam Topic 1)

A company's application currently uses an IAM role that allows all access to all AWS services. A SysOps administrator must ensure that the company's IAM policies allow only the permissions that the application requires.

How can the SysOps administrator create a policy to meet this requirement?

- A. Turn on AWS CloudTrail
- B. Generate a policy by using AWS Security Hub.
- C. Turn on Amazon EventBridge (Amazon CloudWatch Events). Generate a policy by using AWS Identity and Access Management Access Analyzer.
- D. Use the AWS CLI to run the get-generated-policy command in AWS Identity and Access Management Access Analyzer.
- E. Turn on AWS CloudTrail
- F. Generate a policy by using AWS Identity and Access Management Access Analyzer.

**Answer:** D

**Explanation:**

Generate a policy by using AWS Identity and Access Management Access Analyzer. AWS CloudTrail is a service that records all API calls made on your account. You can use this data to generate a policy with AWS Identity and Access Management Access Analyzer that only allows the permissions that the application requires. This will ensure that the application only has the necessary permissions and will protect the company from any unauthorized access.

<https://docs.aws.amazon.com/IAM/latest/UserGuide/what-is-access-analyzer.html#what-is-access-analyzer-poli>

#### NEW QUESTION 112

- (Exam Topic 1)

A Sysops administrator has created an Amazon EC2 instance using an AWS CloudFormation template in the us-east-1 Region. The administrator finds that this template has failed to create an EC2 instance in the us-west-2 Region. What is one cause for this failure?

- A. Resource tags defined in the CloudFormation template are specific to the us-east-1 Region.
- B. The Amazon Machine Image (AMI) ID referenced in the CloudFormation template could not be found in the us-west-2 Region.
- C. The cfn-init script did not run during resource provisioning in the us-west-2 Region.
- D. The IAM user was not created in the specified Region.

**Answer:** B

**Explanation:**

One possible cause for the failure of the CloudFormation template to create an EC2 instance in the us-west-2 Region is that the Amazon Machine Image (AMI) ID referenced in the template could not be found in the us-west-2 Region. This could be due to the fact that the AMI is not available in that region, or the credentials used to access the AMI were not configured properly. The other options (resource tags defined in the CloudFormation template are specific to the us-east-1 Region, the cfn-init script did not run during resource provisioning in the us-west-2 Region, and the IAM user was not created in the specified Region) are not valid



causes for this failure.

#### NEW QUESTION 117

- (Exam Topic 1)

An ecommerce company uses an Amazon ElastiCache for Memcached cluster for in-memory caching of popular product queries on the shopping site. When viewing recent Amazon CloudWatch metrics data for the ElastiCache cluster, the SysOps administrator notices a large number of evictions.

Which of the following actions will reduce these evictions? (Choose two.)

- A. Add an additional node to the ElastiCache cluster.
- B. Increase the ElastiCache time to live (TTL).
- C. Increase the individual node size inside the ElastiCache cluster.
- D. Put an Elastic Load Balancer in front of the ElastiCache cluster.
- E. Use Amazon Simple Queue Service (Amazon SQS) to decouple the ElastiCache cluster.

**Answer:** AC

#### Explanation:

<https://d1.awsstatic.com/training-and-certification/docs-sysops-associate/AWS-Certified-SysOps-Administrator>

#### NEW QUESTION 122

- (Exam Topic 1)

A company manages an application that uses Amazon ElastiCache for Redis with two extra-large nodes spread across two different Availability Zones. The company's IT team discovers that the ElastiCache for Redis cluster has 75% freeable memory. The application must maintain high availability.

What is the MOST cost-effective way to resize the cluster?

- A. Decrease the number of nodes in the ElastiCache for Redis cluster from 2 to 1.
- B. Deploy a new ElastiCache for Redis cluster that uses large node type
- C. Migrate the data from the original cluster to the new cluster
- D. After the process is complete, shut down the original cluster.
- E. Deploy a new ElastiCache for Redis cluster that uses large node type
- F. Take a backup from the original cluster, and restore the backup in the new cluster
- G. After the process is complete, shut down the original cluster.
- H. Perform an online resizing for the ElastiCache for Redis cluster
- I. Change the node types from extra-large nodes to large nodes.

**Answer:** D

#### Explanation:

<https://docs.aws.amazon.com/AmazonElastiCache/latest/red-ug/scaling-redis-cluster-mode-enabled.html> As demand on your clusters changes, you might decide to improve performance or reduce costs by changing the number of shards in your Redis (cluster mode enabled) cluster. We recommend using online horizontal scaling to do so, because it allows your cluster to continue serving requests during the scaling process.

<https://docs.aws.amazon.com/AmazonElastiCache/latest/red-ug/redis-cluster-vertical-scaling-scaling-down.html>

#### NEW QUESTION 125

- (Exam Topic 1)

A company has an application that customers use to search for records on a website. The application's data is stored in an Amazon Aurora DB cluster. The application's usage varies by season and by day of the week.

The website's popularity is increasing, and the website is experiencing slower performance because of increased load on the DB cluster during periods of peak activity. The application logs show that the performance issues occur when users are searching for information. The same search is rarely performed multiple times.

A SysOps administrator must improve the performance of the platform by using a solution that maximizes resource efficiency.

Which solution will meet these requirements?

- A. Deploy an Amazon ElastiCache for Redis cluster in front of the DB cluster
- B. Modify the application to check the cache before the application issues new queries to the database
- C. Add the results of any queries to the cache.
- D. Deploy an Aurora Replica for the DB cluster
- E. Modify the application to use the reader endpoint for search operation
- F. Use Aurora Auto Scaling to scale the number of replicas based on load
- G. Most Voted
- H. Use Provisioned IOPS on the storage volumes that support the DB cluster to improve performance sufficiently to support the peak load on the application.
- I. Increase the instance size in the DB cluster to a size that is sufficient to support the peak load on the application
- J. Use Aurora Auto Scaling to scale the instance size based on load.

**Answer:** B

#### Explanation:

[https://docs.amazonaws.cn/en\\_us/AmazonRDS/latest/AuroraUserGuide/aurora-replicas-adding.html](https://docs.amazonaws.cn/en_us/AmazonRDS/latest/AuroraUserGuide/aurora-replicas-adding.html)

#### NEW QUESTION 130

- (Exam Topic 1)

A company uploaded its website files to an Amazon S3 bucket that has S3 Versioning enabled. The company uses an Amazon CloudFront distribution with the S3 bucket as the origin. The company recently modified the files, but the object names remained the same. Users report that old content is still appearing on the website.

How should a SysOps administrator remediate this issue?

- A. Create a CloudFront invalidation, and add the path of the updated files.
- B. Create a CloudFront signed URL to update each object immediately.
- C. Configure an S3 origin access identity (OAI) to display only the updated files to users.

D. Disable S3 Versioning on the S3 bucket so that the updated files can replace the old files.

**Answer:** A

#### NEW QUESTION 132

- (Exam Topic 1)

A SysOps administrator is maintaining a web application using an Amazon CloudFront web distribution, an Application Load Balancer (ALB), Amazon RDS, and Amazon EC2 in a VPC. All services have logging enabled. The administrator needs to investigate HTTP Layer 7 status codes from the web application.

Which log sources contain the status codes? (Choose two.)

- A. VPC Flow Logs
- B. AWS CloudTrail logs
- C. ALB access logs
- D. CloudFront access logs
- E. RDS logs

**Answer:** CD

#### Explanation:

"C" because Elastic Load Balancing provides access logs that capture detailed information about requests sent to your load balancer

<https://docs.aws.amazon.com/elasticloadbalancing/latest/application/load-balancer-access-logs.html>

"D" because "you can configure CloudFront to create log files that contain detailed information about every user request that CloudFront receives"

<https://docs.aws.amazon.com/AmazonCloudFront/latest/DeveloperGuide/AccessLogs.html>

#### NEW QUESTION 133

- (Exam Topic 1)

A company stores critical data in Amazon S3 buckets. A SysOps administrator must build a solution to record all S3 API activity. Which action will meet this requirement?

- A. Configure S3 bucket metrics to record object access logs
- B. Create an AWS CloudTrail trail to log data events for all S3 objects
- C. Enable S3 server access logging for each S3 bucket
- D. Use AWS IAM Access Analyzer for Amazon S3 to store object access logs.

**Answer:** B

#### NEW QUESTION 136

- (Exam Topic 1)

A company's IT department noticed an increase in the spend of their developer AWS account. There are over 50 developers using the account, and the finance team wants to determine the service costs incurred by each developer.

What should a SysOps administrator do to collect this information? (Select TWO.)

- A. Activate the createdBy tag in the account.
- B. Analyze the usage with Amazon CloudWatch dashboards.
- C. Analyze the usage with Cost Explorer.
- D. Configure AWS Trusted Advisor to track resource usage.
- E. Create a billing alarm in AWS Budgets.

**Answer:** AC

#### NEW QUESTION 138

- (Exam Topic 1)

A company hosts a database on an Amazon RDS Multi-AZ DB instance. The database is not encrypted. The company's new security policy requires all AWS resources to be encrypted at rest and in transit.

What should a SysOps administrator do to encrypt the database?

- A. Configure encryption on the existing DB instance.
- B. Take a snapshot of the DB instance
- C. Encrypt the snapshot
- D. Restore the snapshot to the same DB instance.
- E. Encrypt the standby replica in a secondary Availability Zone
- F. Promote the standby replica to the primary DB instance.
- G. Take a snapshot of the DB instance
- H. Copy and encrypt the snapshot
- I. Create a new DB instance by restoring the encrypted copy.

**Answer:** B

#### NEW QUESTION 143

- (Exam Topic 1)

A SysOps administrator needs to configure a solution that will deliver digital content to a set of authorized users through Amazon CloudFront. Unauthorized users must be restricted from access. Which solution will meet these requirements?

- A. Store the digital content in an Amazon S3 bucket that does not have public access blocked
- B. Use signed URLs to access the S3 bucket through CloudFront.
- C. Store the digital content in an Amazon S3 bucket that has public access blocked
- D. Use an origin access identity (OAI) to deliver the content through CloudFront

- E. Restrict S3 bucket access with signed URLs in CloudFront.
- F. Store the digital content in an Amazon S3 bucket that has public access blocked.
- G. Use an origin access identity (OAI) to deliver the content through CloudFront.
- H. Enable field-level encryption.
- I. Store the digital content in an Amazon S3 bucket that does not have public access blocked.
- J. Use signed cookies for restricted delivery of the content through CloudFront.

**Answer: B**

#### NEW QUESTION 148

- (Exam Topic 1)

A company has a public website that recently experienced problems. Some links led to missing webpages, and other links rendered incorrect webpages. The application infrastructure was running properly, and all the provisioned resources were healthy. Application logs and dashboards did not show any errors, and no monitoring alarms were raised. Systems administrators were not aware of any problems until end users reported the issues.

The company needs to proactively monitor the website for such issues in the future and must implement a solution as soon as possible.

Which solution will meet these requirements with the LEAST operational overhead?

- A. Rewrite the application to surface a custom error to the application log when issues occur. Automatically parse logs for error.
- B. Create an Amazon CloudWatch alarm to provide alerts when issues are detected.
- C. Create an AWS Lambda function to test the website.
- D. Configure the Lambda function to emit an Amazon CloudWatch custom metric when errors are detected.
- E. Configure a CloudWatch alarm to provide alerts when issues are detected.
- F. Create an Amazon CloudWatch Synthetic canary.
- G. Use the CloudWatch Synthetic Recorder plugin to generate the script for the canary run.
- H. Configure the canary in line with requirements.
- I. Create an alarm to provide alerts when issues are detected.

**Answer: A**

#### NEW QUESTION 152

- (Exam Topic 1)

A company runs its infrastructure on Amazon EC2 instances that run in an Auto Scaling group. Recently, the company promoted faulty code to the entire EC2 fleet. This faulty code caused the Auto Scaling group to scale the instances before any of the application logs could be retrieved.

What should a SysOps administrator do to retain the application logs after instances are terminated?

- A. Configure an Auto Scaling lifecycle hook to create a snapshot of the ephemeral storage upon termination of the instances.
- B. Create a new Amazon Machine Image (AMI) that has the Amazon CloudWatch agent installed and configured to send logs to Amazon CloudWatch Log.
- C. Update the launch template to use the new AMI.
- D. Create a new Amazon Machine Image (AMI) that has a custom script configured to send logs to AWS CloudTrail.
- E. Update the launch template to use the new AMI.
- F. Install the Amazon CloudWatch agent on the Amazon Machine Image (AMI) that is defined in the launch template.
- G. Configure the CloudWatch agent to back up the logs to ephemeral storage.

**Answer: B**

#### NEW QUESTION 154

- (Exam Topic 1)

A company wants to archive sensitive data on Amazon S3 Glacier. The company's regulatory and compliance requirements do not allow any modifications to the data by any account.

Which solution meets these requirements?

- A. Attach a vault lock policy to an S3 Glacier vault that contains the archived data.
- B. Use the lock ID to validate the vault lock policy after 24 hours.
- C. Attach a vault lock policy to an S3 Glacier vault that contains the archived data.
- D. Use the lock ID to validate the vault lock policy within 24 hours.
- E. Configure S3 Object Lock in governance mode.
- F. Upload all files after 24 hours.
- G. Configure S3 Object Lock in governance mode.
- H. Upload all files within 24 hours.

**Answer: B**

#### NEW QUESTION 157

- (Exam Topic 1)

A SysOps administrator is setting up a fleet of Amazon EC2 instances in an Auto Scaling group for an application. The fleet should have 50% CPU available at that times to accommodate bursts of traffic. The load will increase significantly between the hours of 09:00 and 17:00, 7 days a week.

How should the SysOps administrator configure the scaling of the EC2 instances to meet these requirements?

- A. Create a target tracking scaling policy that runs when the CPU utilization is higher than 90%.
- B. Create a target tracking scaling policy that runs when the CPU utilization is higher than 50%. Create a scheduled scaling policy that ensures that the fleet is available at 09:00. Create a second scheduled scaling policy that scales in the fleet at 17:00.
- C. Set the Auto Scaling group to start with 2 instances by setting the desired instances, maximum instances, and minimum instances to 2. Create a scheduled scaling policy that ensures that the fleet is available at 09:00.
- D. Create a scheduled scaling policy that ensures that the fleet is available at 09:00. Create a second scheduled scaling policy that scales in the fleet at 17:00.

**Answer: B**

#### NEW QUESTION 160

- (Exam Topic 1)

A company is implementing a monitoring solution that is based on machine learning. The monitoring solution consumes Amazon EventBridge (Amazon CloudWatch Events) events that are generated by Amazon EC2 Auto Scaling. The monitoring solution provides detection of anomalous behavior such as unanticipated scaling events and is configured as an EventBridge (CloudWatch Events) API destination. During initial testing, the company discovers that the monitoring solution is not receiving events. However, Amazon CloudWatch is showing that the EventBridge (CloudWatch Events) rule is being invoked. A SysOps administrator must implement a solution to retrieve client error details to help resolve this issue. Which solution will meet these requirements with the LEAST operational effort?

- A. Create an EventBridge (CloudWatch Events) archive for the event pattern to replay the event
- B. Increase the logging on the monitoring solutio
- C. Use replay to invoke the monitoring solutio
- D. Examine the error details.
- E. Add an Amazon Simple Queue Service (Amazon SQS) standard queue as a dead-letter queue for the targe
- F. Process the messages in the dead-letter queue to retrieve error details.
- G. Create a second EventBridge (CloudWatch Events) rule for the same event pattern to target an AWS Lambda functio
- H. Configure the Lambda function to invoke the monitoring solution and to record the results to Amazon CloudWatch Log
- I. Examine the errors in the logs.
- J. Configure the EventBridge (CloudWatch Events) rule to send error messages to an Amazon Simple Notification Service (Amazon SNS) topic.

**Answer:** A

**Explanation:**

"In EventBridge, you can create an archive of events so that you can easily replay them at a later time. For example, you might want to replay events to recover from errors or to validate new functionality in your application." <https://docs.aws.amazon.com/eventbridge/latest/userguide/eb-archive.html>

**NEW QUESTION 163**

- (Exam Topic 1)

A company has a critical serverless application that uses multiple AWS Lambda functions. Each Lambda function generates 1 GB of log data daily in its own Amazon CloudWatch Logs log group. The company's security team asks for a count of application errors, grouped by type, across all of the log groups. What should a SysOps administrator do to meet this requirement?

- A. Perform a CloudWatch Logs Insights query that uses the stats command and count function.
- B. Perform a CloudWatch Logs search that uses the groupby keyword and count function.
- C. Perform an Amazon Athena query that uses the SELECT and GROUP BY keywords.
- D. Perform an Amazon RDS query that uses the SELECT and GROUP BY keywords.

**Answer:** A

**NEW QUESTION 167**

- (Exam Topic 1)

A company is using an AWS KMS customer master key (CMK) with imported key material. The company references the CMK by its alias in the Java application to encrypt data. The CMK must be rotated every 6 months. What is the process to rotate the key?

- A. Enable automatic key rotation for the CMK and specify a period of 6 months.
- B. Create a new CMK with new imported material, and update the key alias to point to the new CMK.
- C. Delete the current key material, and import new material into the existing CMK.
- D. Import a copy of the existing key material into a new CMK as a backup, and set the rotation schedule for 6 months.

**Answer:** B

**NEW QUESTION 168**

- (Exam Topic 1)

A SysOps administrator is investigating why a user has been unable to use RDP to connect over the internet from their home computer to a bastion server running on an Amazon EC2 Windows instance. Which of the following are possible causes of this issue? (Choose two.)

- A. A network ACL associated with the bastion's subnet is blocking the network traffic.
- B. The instance does not have a private IP address.
- C. The route table associated with the bastion's subnet does not have a route to the internet gateway.
- D. The security group for the instance does not have an inbound rule on port 22.
- E. The security group for the instance does not have an outbound rule on port 3389.

**Answer:** AC

**NEW QUESTION 170**

- (Exam Topic 1)

A company is undergoing an external audit of its systems, which run wholly on AWS. A SysOps administrator must supply documentation of Payment Card Industry Data Security Standard (PCI DSS) compliance for the infrastructure managed by AWS. Which set of action should the SysOps administrator take to meet this requirement?

- A. Download the applicable reports from the AWS Artifact portal and supply these to the auditors.
- B. Download complete copies of the AWS CloudTrail log files and supply these to the auditors.
- C. Download complete copies of the AWS CloudWatch logs and supply these to the auditors.
- D. Provide the auditors with administrative access to the production AWS account so that the auditors can determine compliance.

**Answer:** A



#### NEW QUESTION 174

- (Exam Topic 1)

A SysOps administrator noticed that a large number of Elastic IP addresses are being created on the company's AWS account, but they are not being associated with Amazon EC2 instances, and are incurring Elastic IP address charges in the monthly bill.

How can the administrator identify who is creating the Elastic IP addresses?

- A. Attach a cost-allocation tag to each requested Elastic IP address with the IAM user name of the developer who creates it.
- B. Query AWS CloudTrail logs by using Amazon Athena to search for Elastic IP address events.
- C. Create a CloudWatch alarm on the EIPCreated metric and send an Amazon SNS notification when the alarm triggers.
- D. Use Amazon Inspector to get a report of all Elastic IP addresses created in the last 30 days.

**Answer: B**

#### NEW QUESTION 177

- (Exam Topic 1)

A large company is using AWS Organizations to manage its multi-account AWS environment. According to company policy, all users should have read-level access to a particular Amazon S3 bucket in a central account. The S3 bucket data should not be available outside the organization. A SysOps administrator must set up the permissions and add a bucket policy to the S3 bucket.

Which parameters should be specified to accomplish this in the MOST efficient manner?

- A. Specify '\*' as the principal and PrincipalOrgId as a condition.
- B. Specify all account numbers as the principal.
- C. Specify PrincipalOrgId as the principal.
- D. Specify the organization's management account as the principal.

**Answer: C**

#### NEW QUESTION 180

- (Exam Topic 1)

A company requires that all IAM user accounts that have not been used for 90 days or more must have their access keys and passwords immediately disabled. A SysOps administrator must automate the process of disabling unused keys using the MOST operationally efficient method.

How should the SysOps administrator implement this solution?

- A. Create an AWS Step Functions workflow to identify IAM users that have not been active for 90 days. Run an AWS Lambda function when a scheduled Amazon EventBridge (Amazon CloudWatch Events) rule is invoked to automatically remove the AWS access keys and passwords for these IAM users.
- B. Configure an AWS Config rule to identify IAM users that have not been active for 90 days. Set up an automatic weekly batch process on an Amazon EC2 instance to disable the AWS access keys and passwords for these IAM users.
- C. Develop and run a Python script on an Amazon EC2 instance to programmatically identify IAM users that have not been active for 90 days. Automatically delete these IAM users.
- D. Set up an AWS Config managed rule to identify IAM users that have not been active for 90 days. Set up an AWS Systems Manager automation runbook to disable the AWS access keys for these IAM users.

**Answer: D**

#### NEW QUESTION 183

- (Exam Topic 1)

A large company is using AWS Organizations to manage hundreds of AWS accounts across multiple AWS Regions. The company has turned on AWS Config throughout the organization.

The company requires all Amazon S3 buckets to block public read access. A SysOps administrator must generate a monthly report that shows all the S3 buckets and whether they comply with this requirement.

Which combination of steps should the SysOps administrator take to collect this data? (Select TWO).

- A. Create an AWS Config aggregator in an aggregator account.
- B. Use the organization as the source. Retrieve the compliance data from the aggregator.
- C. Create an AWS Config aggregator in each account.
- D. Use an S3 bucket in an aggregator account as the destination.
- E. Retrieve the compliance data from the S3 bucket.
- F. Edit the AWS Config policy in AWS Organization.
- G. Use the organization's management account to turn on the s3-bucket-public-read-prohibited rule for the entire organization.
- H. Use the AWS Config compliance report from the organization's management account.
- I. Filter the results by resource, and select Amazon S3.
- J. Use the AWS Config API to apply the s3-bucket-public-read-prohibited rule in all accounts for all available Regions.

**Answer: CD**

#### NEW QUESTION 188

- (Exam Topic 1)

A company runs a web application on three Amazon EC2 instances behind an Application Load Balancer (ALB). The company notices that random periods of increased traffic cause a degradation in the application's performance. A SysOps administrator must scale the application to meet the increased traffic. Which solution meets these requirements?

- A. Create an Amazon CloudWatch alarm to monitor application latency and increase the size of each EC2 instance if the desired threshold is reached.
- B. Create an Amazon EventBridge (Amazon CloudWatch Events) rule to monitor application latency and add an EC2 instance to the ALB if the desired threshold is reached.
- C. Deploy the application to an Auto Scaling group of EC2 instances with a target tracking scaling policy. Attach the ALB to the Auto Scaling group.
- D. Deploy the application to an Auto Scaling group of EC2 instances with a scheduled scaling policy. Attach the ALB to the Auto Scaling group.

**Answer: C**



#### NEW QUESTION 190

- (Exam Topic 1)

A company recently purchased Savings Plans. The company wants to receive email notification when the company's utilization drops below 90% for a given day. Which solution will meet this requirement?

- A. Create an Amazon CloudWatch alarm to monitor the Savings Plan check in AWS Trusted Advisor. Configure an Amazon Simple Queue Service (Amazon SQS) queue for email notification when the utilization drops below 90% for a given day.
- B. Create an Amazon CloudWatch alarm to monitor the SavingsPlansUtilization metric under the AWS/SavingsPlans namespace in CloudWatc
- C. Configure an Amazon Simple Queue Service (Amazon SQS) queue for email notification when the utilization drops below 90% for a given day.
- D. Create a Savings Plans alert to monitor the daily utilization of the Savings Plan
- E. Configure an Amazon Simple Notification Service (Amazon SNS) topic for email notification when the utilization drops below 90% for a given day.
- F. Use AWS Budgets to create a Savings Plans budget to track the daily utilization of the Savings Plans. Configure an Amazon Simple Notification Service (Amazon SNS) topic for email notification when the utilization drops below 90% for a given day.

**Answer:** D

#### Explanation:

AWS Budgets can be used to create a Savings Plans budget and track the daily utilization of the company's Savings Plans. By creating a budget, it will trigger an action when the utilization drops below 90%, which in this case will be to send an email notification via an Amazon SNS topic. This will ensure that the company is notified when their Savings Plans utilization drops below 90%, allowing them to take action if necessary.

Reference: [1] <https://docs.aws.amazon.com/savingsplans/latest/userguide/sp-usingBudgets.html>

#### NEW QUESTION 192

- (Exam Topic 1)

An application accesses data through a file system interface. The application runs on Amazon EC2 instances in multiple Availability Zones, all of which must share the same data. While the amount of data is currently small, the company anticipates that it will grow to tens of terabytes over the lifetime of the application.

What is the MOST scalable storage solution to fulfill this requirement?

- A. Connect a large Amazon EBS volume to multiple instances and schedule snapshots.
- B. Deploy Amazon EFS in the VPC and create mount targets in multiple subnets.
- C. Launch an EC2 instance and share data using SMB/CIFS or NFS.
- D. Deploy an AWS Storage Gateway cached volume on Amazon EC2.

**Answer:** B

#### NEW QUESTION 193

- (Exam Topic 1)

A SysOps administrator trust manage the security of An AWS account Recently an IAM users access key was mistakenly uploaded to a public code repository. The SysOps administrator must identity anything that was changed by using this access key.

- A. Create an Amazon EventBridge (Amazon CloudWatch Events) rule to send all IAM events lo an AWS Lambda function for analysis
- B. Query Amazon EC2 togs by using Amazon CloudWatch Logs Insights for all events Heated with the compromised access key within the suspected timeframe
- C. Search AWS CloudTrail event history tor all events initiated with the compromised access key within the suspected timeframe
- D. Search VPC Flow Logs foe all events initiated with the compromised access key within the suspected Timeframe.

**Answer:** C

#### NEW QUESTION 198

- (Exam Topic 1)

A company is tunning a website on Amazon EC2 instances thai are in an Auto Scaling group When the website traffic increases, additional instances lake several minutes to become available because ot a

long-running user data script that installs software A SysOps administrator must decrease the time that is required (or new instances to become available

Which action should the SysOps administrator take to meet this requirement?

- A. Reduce the scaling thresholds so that instances are added before traffic increases
- B. Purchase Reserved Instances to cover 100% of the maximum capacity of the Auto Scaling group
- C. Update the Auto Scaling group to launch instances that have a storage optimized instance type
- D. Use EC2 Image Builder to prepare an Amazon Machine Image (AMI) that has pre-installed software

**Answer:** D

#### Explanation:

automated way to update your image. Have a pipeline to update your image. When you boot from your AMI updates = scrits are already pre-installed, so no need to complete boot scripts in boot process. <https://aws.amazon.com/image-builder/>

#### NEW QUESTION 201

- (Exam Topic 1)

A SysOps administrator has launched a large general purpose Amazon EC2 instance to regularly process large data files. The instance has an attached 1 TB General Purpose SSD (gp2) Amazon Elastic Block Store (Amazon EBS) volume. The instance also is EBS-optimized. To save costs, the SysOps administrator stops the instance each evening and restarts the instance each morning.

When data processing is active, Amazon CloudWatch metrics on the instance show a consistent 3.000 VolumeReadOps. The SysOps administrator must improve the I/O performance while ensuring data integrity.

Which action will meet these requirements?

- A. Change the instance type to a large, burstable, general purpose instance.
- B. Change the instance type to an extra large general purpose instance.
- C. Increase the EBS volume to a 2 TB General Purpose SSD (gp2) volume.
- D. Move the data that resides on the EBS volume to the instance store.

**Answer:** C

#### NEW QUESTION 203

- (Exam Topic 1)

A SysOps administrator has Nocked public access to all company Amazon S3 buckets. The SysOps administrator wants to be notified when an S3 bucket becomes publicly readable in the future.

What is the MOST operationally efficient way to meet this requirement?

- A. Create an AWS Lambda function that periodically checks the public access settings for each S3 bucket.Set up Amazon Simple Notification Service (Amazon SNS) to send notifications.
- B. Create a cron script that uses the S3 API to check the public access settings for each S3 bucke
- C. Set up Amazon Simple Notification Service (Amazon SNS) to send notifications
- D. Enable S3 Event notified tons for each S3 bucke
- E. Subscribe S3 Event Notifications to an Amazon Simple Notification Service (Amazon SNS) topic.
- F. Enable the s3-bucket-public-read-prohibited managed rule in AWS Confi
- G. Subscribe the AWS Config rule to an Amazon Simple Notification Service (Amazon SNS) topic.

**Answer:** D

#### NEW QUESTION 204

- (Exam Topic 1)

A Sysops administrator needs to configure automatic rotation for Amazon RDS database credentials. The credentials must rotate every 30 days. The solution must integrate with Amazon RDS.

Which solution will meet these requirements with the LEAST operational overhead?

- A. Store the credentials in AWS Systems Manager Parameter Store as a secure strin
- B. Configure automatic rotation with a rotation interval of 30 days.
- C. Store the credentials in AWS Secrets Manage
- D. Configure automatic rotation with a rotation interval of 30 days.
- E. Store the credentials in a file in an Amazon S3 bucke
- F. Deploy an AWS Lambda function to automatically rotate the credentials every 30 days.
- G. Store the credentials in AWS Secrets Manage
- H. Deploy an AWS Lambda function to automatically rotate the credentials every 30 days.

**Answer:** B

#### Explanation:

Storing the credentials in AWS Secrets Manager and configuring automatic rotation with a rotation interval of 30 days is the most efficient way to meet the requirements with the least operational overhead. AWS Secrets Manager automatically rotates the credentials at the specified interval, so there is no need for an additional AWS Lambda function or manual rotation. Additionally, Secrets Manager is integrated with Amazon RDS, so the credentials can be easily used with the RDS database.

#### NEW QUESTION 206

- (Exam Topic 1)

A company uses Amazon Elasticsearch Service (Amazon ES) to analyze sales and customer usage data. Members of the company's geographically dispersed sales team are traveling. They need to log in to Kibana by using their existing corporate credentials that are stored in Active Directory. The company has deployed Active Directory Federation Services (AD FS) to enable authentication to cloud services. Which solution will meet these requirements?

- A. Configure Active Directory as an authentication provider in Amazon E
- B. Add the Active Directory server's domain name to Amazon E
- C. Configure Kibana to use Amazon ES authentication.
- D. Deploy an Amazon Cognito user poo
- E. Configure Active Directory as an external identity provider for the user poo
- F. Enable Amazon Cognito authentication for Kibana on Amazon ES.
- G. Enable Active Directory user authentication in Kiban
- H. Create an IP-based custom domain access policy in Amazon ES that includes the Active Directory server's IP address.
- I. Establish a trust relationship with Kibana on the Active Directory serve
- J. Enable Active Directory user authentication in Kiban
- K. Add the Active Directory server's IP address to Kibana.

**Answer:** B

#### Explanation:

<https://aws.amazon.com/blogs/security/how-to-enable-secure-access-to-kibana-using-aws-single-sign-on/> <https://docs.aws.amazon.com/elasticsearch-service/latest/developerguide/es-cognito-auth.html>

#### NEW QUESTION 207

- (Exam Topic 1)

A company's SysOps administrator deploys four new Amazon EC2 instances by using the standard Amazon Linux 2 Amazon Machine Image (AMI). The company needs to be able to use AWS Systems Manager to manage the instances The SysOps administrator notices that the instances do not appear in the Systems Manager console

What must the SysOps administrator do to resolve this issue?

- A. Connect to each instance by using SSH Install Systems Manager Agent on each instance Configure Systems Manager Agent to start automatically when the instances start up
- B. Use AWS Certificate Manager (ACM) to create a TLS certificate Import the certificate into each instance Configure Systems Manager Agent to use the TLS certificate for secure communications
- C. Connect to each instance by using SSH Create an ssm-user account Add the ssm-user account to the/etcsudoers d directory
- D. Attach an IAM instance profile to the instances Ensure that the instance profile contains the AmazonSSMManagedinstanceCore policy

**Answer:** D

#### NEW QUESTION 211

- (Exam Topic 1)

A SysOps administrator configures an Amazon S3 gateway endpoint in a VPC. The private subnets inside the VPC do not have outbound internet access. A user logs in to an Amazon EC2 instance in one of the private subnets and cannot upload a file to an Amazon S3 bucket in the same AWS Region. Which solution will solve this problem?

- A. Update the EC2 instance role policy to allow s3:PutObject access to the target S3 bucket.
- B. Update the EC2 security group to allow outbound traffic to 0.0.0.0/0 for port 80.
- C. Update the EC2 subnet route table to include the S3 prefix list destination routes to the S3 gateway endpoint.
- D. Update the S3 bucket policy to allow s3:PutObject access from the private subnet CIDR block.

**Answer:** C

#### NEW QUESTION 215

- (Exam Topic 1)

An Amazon EC2 instance needs to be reachable from the internet. The EC2 instance is in a subnet with the following route table:

Destination	Target
10.0.0.0/16	Local
172.31.0.0/16	pcx-1122334455

Which entry must a SysOps administrator add to the route table to meet this requirement?

- A. A route for 0.0.0.0/0 that points to a NAT gateway
- B. A route for 0.0.0.0/0 that points to an egress-only internet gateway
- C. A route for 0.0.0.0/0 that points to an internet gateway
- D. A route for 0.0.0.0/0 that points to an elastic network interface

**Answer:** C

#### NEW QUESTION 216

- (Exam Topic 1)

A SysOps administrator has an AWS CloudFormation template of the company's existing infrastructure in us-west-2. The administrator attempts to use the template to launch a new stack in eu-west-1, but the stack only partially deploys, receives an error message, and then rolls back. Why would this template fail to deploy? (Select TWO.)

- A. The template referenced an IAM user that is not available in eu-west-1.
- B. The template referenced an Amazon Machine Image (AMI) that is not available in eu-west-1.
- C. The template did not have the proper level of permissions to deploy the resources.
- D. The template requested services that do not exist in eu-west-1.
- E. CloudFormation templates can be used only to update existing services.

**Answer:** BD

#### NEW QUESTION 220

- (Exam Topic 1)

A company is expanding its use of AWS services across its portfolios. The company wants to provision AWS accounts for each team to ensure a separation of business processes for security compliance and billing. Account creation and bootstrapping should be completed in a scalable and efficient way so new accounts are created with a defined baseline and governance guardrails in place. A SysOps administrator needs to design a provisioning process that saves time and resources.

Which action should be taken to meet these requirements?

- A. Automate using AWS Elastic Beanstalk to provision the AWS accounts, set up infrastructure, and integrate with AWS Organizations.
- B. Create bootstrapping scripts in AWS OpsWorks and combine them with AWS CloudFormation templates to provision accounts and infrastructure.
- C. Use AWS Config to provision accounts and deploy instances using AWS Service Catalog.
- D. Use AWS Control Tower to create a template in Account Factory and use the template to provision new accounts.

**Answer:** D

#### NEW QUESTION 222

- (Exam Topic 1)

A company wants to collect data from an application to use for analytics. For the first 90 days, the data will be infrequently accessed but must remain highly available. During this time, the company's analytics team requires access to the data in milliseconds. However, after 90 days, the company must retain the data for the long term at a lower cost. The retrieval time after 90 days must be less than 5 hours.

Which solution will meet these requirements MOST cost-effectively?

- A. Store the data in S3 Standard-Infrequent Access (S3 Standard-IA) for the first 90 days.
- B. Set up an S3 Lifecycle rule to move the data to S3 Glacier Flexible Retrieval after 90 days.
- C. Store the data in S3 One Zone-Infrequent Access (S3 One Zone-IA) for the first 90 days.
- D. Set up an S3 Lifecycle rule to move the data to S3 Glacier Deep Archive after 90 days.
- E. Store the data in S3 Standard for the first 90 days.
- F. Set up an S3 Lifecycle rule to move the data to S3 Glacier Flexible Retrieval after 90 days.
- G. Store the data in S3 Standard for the first 90 days.
- H. Set up an S3 Lifecycle rule to move the data to S3 Glacier Deep Archive after 90 days.

**Answer:** A

**Explanation:**

Glacier Deep Archive retrieval time more than 5 hours (it's 12 hours), so B&D out. S3 Standard IA is cheaper than S3 Standard.  
<https://aws.amazon.com/tw/s3/pricing/>

**NEW QUESTION 223**

- (Exam Topic 1)

A data storage company provides a service that gives users the ability to upload and download files as needed. The files are stored in Amazon S3 Standard and must be immediately retrievable for 1 year. Users access files frequently during the first 30 days after the files are stored. Users rarely access files after 30 days. The company's SysOps administrator must use S3 Lifecycle policies to implement a solution that maintains object availability and minimizes cost. Which solution will meet these requirements?

- A. Move objects to S3 Glacier after 30 days.
- B. Move objects to S3 One Zone-Infrequent Access (S3 One Zone-IA) after 30 days.
- C. Move objects to S3 Standard-Infrequent Access (S3 Standard-IA) after 30 days.
- D. Move objects to S3 Standard-Infrequent Access (S3 Standard-IA) immediately.

**Answer:** C

**Explanation:**

<https://aws.amazon.com/s3/storage-classes/>

**NEW QUESTION 228**

- (Exam Topic 1)

A company has attached the following policy to an IAM user:

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Effect": "Allow",
      "Action": "rds:Describe*",
      "Resource": "*"
    },
    {
      "Effect": "Allow",
      "Action": "ec2:*",
      "Resource": "*",
      "Condition": {
        "StringEquals": {
          "ec2:Region": "us-east-1"
        }
      }
    },
    {
      "Effect": "Deny",
      "NotAction": [
        "ec2:*",
```



```
{
  "Effect": "Allow",
  "Action": "ec2:*",
  "Resource": "*",
  "Condition": {
    "StringEquals": {
      "ec2:Region": "us-east-1"
    }
  }
},
{
  "Effect": "Deny",
  "NotAction": [
    "ec2:*",
    "s3:GetObject"
  ],
  "Resource": "*"
}
```

Which of the following actions are allowed for the IAM user?

- A. Amazon RDS DescribeDBInstances action in the us-east-1 Region
- B. Amazon S3 Putobject operation in a bucket named testbucket
- C. Amazon EC2 Describe Instances action in the us-east-1 Region
- D. Amazon EC2 AttachNetworkinterface action in the eu-west-1 Region

**Answer: C**

#### NEW QUESTION 231

- (Exam Topic 1)

A company updates its security policy to clarify cloud hosting arrangements for regulated workloads. Workloads that are identified as sensitive must run on hardware that is not shared with other customers or with other AWS accounts within the company.

Which solution will ensure compliance with this policy?

- A. Deploy workloads only to Dedicated Hosts.
- B. Deploy workloads only to Dedicated Instances.
- C. Deploy workloads only to Reserved Instances.
- D. Place all instances in a dedicated placement group.

**Answer: A**

#### Explanation:

Dedicated Hosts are physical servers that are dedicated to a single customer, ensuring that the customer's workloads are not shared with other customers or with other AWS accounts within the company. This will ensure that the company's security policy is followed and that sensitive workloads are running on hardware that is not shared with other customers or with other AWS accounts within the company.

#### NEW QUESTION 233

- (Exam Topic 1)

A company hosts its website in the us-east-1 Region. The company is preparing to deploy its website into the eu-central-1 Region. Website visitors who are located in Europe should access the website that is hosted in eu-central-1. All other visitors access the website that is hosted in us-east-1. The company uses Amazon Route 53 to manage the website's DNS records.

Which routing policy should a SysOps administrator apply to the Route 53 record set to meet these requirements?

- A. Geolocation routing policy
- B. Geoproximity routing policy
- C. Latency routing policy
- D. Multivalue answer routing policy

**Answer: A**

#### Explanation:

geolocation "Geolocation routing lets you choose the resources that serve your traffic based on the geographic location of your users, meaning the location that DNS queries originate from. For example, you might want all queries from Europe to be routed to an ELB load balancer in the Frankfurt region."

Could be confused with geoproximity - "Geoproximity routing lets Amazon Route 53 route traffic to your resources based on the geographic location of your users and your resources. You can also optionally choose to route more traffic or less to a given resource by specifying a value, known as a bias. A bias expands or shrinks the size of the geographic region from which traffic is routed to a resource" the use case is not needed as per question.

<https://docs.aws.amazon.com/Route53/latest/DeveloperGuide/routing-policy.html>

#### NEW QUESTION 238

- (Exam Topic 1)

A SysOps administrator is required to monitor free space on Amazon EBS volumes attached to Microsoft Windows-based Amazon EC2 instances within a



company's account. The administrator must be alerted to potential issues.

What should the administrator do to receive email alerts before low storage space affects EC2 instance performance?

- A. Use built-in Amazon CloudWatch metrics, and configure CloudWatch alarms and an Amazon SNS topic for email notifications
- B. Use AWS CloudTrail logs and configure the trail to send notifications to an Amazon SNS topic.
- C. Use the Amazon CloudWatch agent to send disk space metrics, then set up CloudWatch alarms using an Amazon SNS topic.
- D. Use AWS Trusted Advisor and enable email notification alerts for EC2 disk space

**Answer:** C

#### NEW QUESTION 240

- (Exam Topic 1)

A recent organizational audit uncovered an existing Amazon RDS database that is not currently configured for high availability. Given the critical nature of this database, it must be configured for high availability as soon as possible.

How can this requirement be met?

- A. Switch to an active/passive database pair using the create-db-instance-read-replica with the --availability-zone flag.
- B. Specify high availability when creating a new RDS instance, and live-migrate the data.
- C. Modify the RDS instance using the console to include the Multi-AZ option.
- D. Use the modify-db-instance command with the --na flag.

**Answer:** C

#### NEW QUESTION 245

- (Exam Topic 1)

A company maintains a large set of sensitive data in an Amazon S3 bucket. The company's security team asks a SysOps administrator to help verify that all current objects in the S3 bucket are encrypted.

What is the MOST operationally efficient solution that meets these requirements?

- A. Create a script that runs against the S3 bucket and outputs the status of each object.
- B. Create an S3 Inventory configuration on the S3 bucket. Induce the appropriate status fields.
- C. Provide the security team with an IAM user that has read access to the S3 bucket.
- D. Use the AWS CLI to output a list of all objects in the S3 bucket.

**Answer:** D

#### NEW QUESTION 248

- (Exam Topic 1)

With the threat of ransomware viruses encrypting and holding company data hostage, which action should be taken to protect an Amazon S3 bucket?

- A. Deny Pos
- B. Put
- C. and Delete on the bucket.
- D. Enable server-side encryption on the bucket.
- E. Enable Amazon S3 versioning on the bucket.
- F. Enable snapshots on the bucket.

**Answer:** B

#### NEW QUESTION 252

- (Exam Topic 1)

A company uses an Amazon Elastic File System (Amazon EFS) file system to share files across many Linux Amazon EC2 instances. A SysOps administrator notices that the file system's PercentIOLimit metric is consistently at 100% for 15 minutes or longer. The SysOps administrator also notices that the application that reads and writes to that file system is performing poorly. The application requires high throughput and IOPS while accessing the file system.

What should the SysOps administrator do to remediate the consistently high PercentIOLimit metric?

- A. Create a new EFS file system that uses Max I/O performance mode
- B. Use AWS DataSync to migrate data to the new EFS file system.
- C. Create an EFS lifecycle policy to transition future files to the Infrequent Access (IA) storage class to improve performance
- D. Use AWS DataSync to migrate existing data to IA storage.
- E. Modify the existing EFS file system and activate Max I/O performance mode.
- F. Modify the existing EFS file system and activate Provisioned Throughput mode.

**Answer:** A

#### Explanation:

To support a wide variety of cloud storage workloads, Amazon EFS offers two performance modes, General Purpose mode and Max I/O mode. You choose a file system's performance mode when you create it, and it cannot be changed. If the PercentIOLimit percentage returned was at or near 100 percent for a significant amount of time during the test, your application should use the Max I/O performance mode. <https://docs.aws.amazon.com/efs/latest/ug/performance.html>

#### NEW QUESTION 257

- (Exam Topic 1)

A SysOps administrator is using AWS Systems Manager Patch Manager to patch a fleet of Amazon EC2 instances. The SysOps administrator has configured a patch baseline and a maintenance window. The SysOps administrator also has used an instance tag to identify which instances to patch.

The SysOps administrator must give Systems Manager the ability to access the EC2 instances. Which additional action must the SysOps administrator perform to meet this requirement?

- A. Add an inbound rule to the instances' security group.

- B. Attach an IAM instance profile with access to Systems Manager to the instances.
- C. Create a Systems Manager activation Then activate the fleet of instances.
- D. Manually specify the instances to patch Instead of using tag-based selection.

**Answer:** A

#### NEW QUESTION 261

- (Exam Topic 1)

A SysOps administrator is deploying a test site running on Amazon EC2 instances. The application requires both incoming and outgoing connectivity to the internet.

Which combination of steps are required to provide internet connectivity to the EC2 instances? (Choose two.)

- A. Add a NAT gateway to a public subnet.
- B. Attach a private address to the elastic network interface on the EC2 instance.
- C. Attach an Elastic IP address to the internet gateway.
- D. Add an entry to the route table for the subnet that points to an internet gateway.
- E. Create an internet gateway and attach it to a VPC.

**Answer:** DE

#### Explanation:

[https://docs.aws.amazon.com/vpc/latest/userguide/VPC\\_Internet\\_Gateway.html](https://docs.aws.amazon.com/vpc/latest/userguide/VPC_Internet_Gateway.html)

#### NEW QUESTION 262

- (Exam Topic 1)

A company using AWS Organizations requires that no Amazon S3 buckets in its production accounts should ever be deleted.

What is the SIMPLEST approach the SysOps administrator can take to ensure S3 buckets in those accounts can never be deleted?

- A. Set up MFA Delete on all the S3 buckets to prevent the buckets from being deleted.
- B. Use service control policies to deny the s3:DeleteBucket action on all buckets in production accounts.
- C. Create an IAM group that has an IAM policy to deny the s3:DeleteBucket action on all buckets in production accounts.
- D. Use AWS Shield to deny the s3:DeleteBucket action on the AWS account instead of all S3 buckets.

**Answer:** B

#### Explanation:

[https://docs.aws.amazon.com/organizations/latest/userguide/orgs\\_manage\\_policies\\_scps.html](https://docs.aws.amazon.com/organizations/latest/userguide/orgs_manage_policies_scps.html)

If you're using AWS Organizations, check the service control policies for any statements that explicitly deny Amazon S3 access. In particular, check the service control policies for statements denying the s3:PutBucketPolicy action.

<https://aws.amazon.com/tw/premiumsupport/knowledge-center/s3-access-denied-bucket-policy/>

#### NEW QUESTION 266

- (Exam Topic 1)

A company is running a serverless application on AWS Lambda The application stores data in an Amazon RDS for MySQL DB instance Usage has steadily increased and recently there have been numerous "too many connections" errors when the Lambda function attempts to connect to the database The company already has configured the database to use the maximum max\_connections value that is possible

What should a SysOps administrator do to resolve these errors'?

- A. Create a read replica of the database Use Amazon Route 53 to create a weighted DNS record that contains both databases
- B. Use Amazon RDS Proxy to create a proxy Update the connection string in the Lambda function
- C. Increase the value in the max\_connect\_errors parameter in the parameter group that the database uses
- D. Update the Lambda function's reserved concurrency to a higher value

**Answer:** B

#### Explanation:

<https://aws.amazon.com/blogs/compute/using-amazon-rds-proxy-with-aws-lambda/>

RDS Proxy acts as an intermediary between your application and an RDS database. RDS Proxy establishes and manages the necessary connection pools to your database so that your application creates fewer database connections. Your Lambda functions interact with RDS Proxy instead of your database instance. It handles the connection pooling necessary for scaling many simultaneous connections created by concurrent Lambda functions. This allows your Lambda applications to reuse existing connections, rather than creating new connections for every function invocation.

Check "Database proxy for Amazon RDS" section in the link to see how RDS proxy help Lambda handle huge connections to RDS MySQL

<https://aws.amazon.com/blogs/compute/using-amazon-rds-proxy-with-aws-lambda/>

#### NEW QUESTION 268

- (Exam Topic 1)

A manufacturing company uses an Amazon RDS DB instance to store inventory of all stock items. The company maintains several AWS Lambda functions that interact with the database to add, update, and delete items. The Lambda functions use hardcoded credentials to connect to the database.

A SysOps administrator must ensure that the database credentials are never stored in plaintext and that the password is rotated every 30 days.

Which solution will meet these requirements in the MOST operationally efficient manner?

- A. Store the database password as an environment variable for each Lambda function
- B. Create a new Lambda function that is named PasswordRotate
- C. Use Amazon EventBridge (Amazon CloudWatch Events) to schedule the PasswordRotate function every 30 days to change the database password and update the environment variable for each Lambda function.
- D. Use AWS Key Management Service (AWS KMS) to encrypt the database password and to store the encrypted password as an environment variable for each Lambda function
- E. Grant each Lambda function access to the KMS key so that the database password can be decrypted when require
- F. Create a new Lambda function that is named PasswordRotate to change the password every 30 days.

- G. Use AWS Secrets Manager to store credentials for the databas
- H. Create a Secrets Manager secret, and select the database so that Secrets Manager will use a Lambda function to update the database password automaticall
- I. Specify an automatic rotation schedule of 30 day
- J. Update each Lambda function to access the database password from SecretsManager.
- K. Use AWS Systems Manager Parameter Store to create a secure string to store credentials for the databas
- L. Create a new Lambda function called PasswordRotat
- M. Use Amazon EventBridge (Amazon CloudWatch Events) to schedule the PasswordRotate function every 30 days to change the database password and to update the secret within Parameter Stor
- N. Update each Lambda function to access the database password from Parameter Store.

**Answer: C**

**Explanation:**

When you choose to enable rotation, Secrets Manager supports the following Amazon Relational Database Service (Amazon RDS) databases with AWS written and tested Lambda rotation function templates, and full configuration of the rotation process:

Amazon Aurora on Amazon RDS MySQL on Amazon RDS PostgreSQL on Amazon RDS Oracle on Amazon RDS MariaDB on Amazon RDS

Microsoft SQL Server on Amazon RDS <https://docs.aws.amazon.com/secretsmanager/latest/userguide/intro.html>

**NEW QUESTION 269**

- (Exam Topic 1)

A company hosts a web application on an Amazon EC2 instance in a production VPC. Client connections to the application are failing. A SysOps administrator inspects the VPC flow logs and finds the following entry:

```
2 111122223333 eni-####> 192.0.2.15 203.0.113.56 40711 443 6 1 40 1418530010 1418530070 REJECT OK
```

What is a possible cause of these failed connections?

- A. A security group is denying traffic on port 443.
- B. The EC2 instance is shut down.
- C. The network ACL is blocking HTTPS traffic.
- D. The VPC has no internet gateway attached.

**Answer: A**

**Explanation:**

<https://docs.aws.amazon.com/vpc/latest/userguide/flow-logs-records-examples.html#flow-log-example-accepted>

<https://docs.aws.amazon.com/vpc/latest/userguide/flow-logs-records-examples.html#>

Accepted and rejected traffic: In this example, RDP traffic (destination port 3389, TCP protocol) to network interface eni-1235b8ca123456789 in account 123456789010 was rejected. 2 123456789010

```
eni-1235b8ca123456789 172.31.9.69 172.31.9.12 49761 3389 6 20 4249 1418530010 1418530070 REJECT OK
```

**NEW QUESTION 271**

- (Exam Topic 1)

A company has a new requirement stating that all resources In AWS must be tagged according to a set policy. Which AWS service should be used to enforce and continually Identify all resources that are not in compliance with the policy?

- A. AWS CloudTrail
- B. Amazon Inspector
- C. AWS Config
- D. AWS Systems Manager

**Answer: C**

**NEW QUESTION 273**

- (Exam Topic 1)

A software development company has multiple developers who work on the same product. Each developer must have their own development environment, and these development environments must be identical. Each development environment consists of Amazon EC2 instances and an Amazon RDS DB instance. The development environments should be created only when necessary, and they must be terminated each night to minimize costs.

What is the MOST operationally efficient solution that meets these requirements?

- A. Provide developers with access to the same AWS CloudFormation template so that they can provision their development environment when necessar
- B. Schedule a nightly cron job on each development instance to stop all running processes to reduce CPU utilization to nearly zero.
- C. Provide developers with access to the same AWS CloudFormation template so that they can provision their development environment when necessar
- D. Schedule a nightly Amazon EventBridge (Amazon CloudWatch Events) rule to invoke an AWS Lambda function to delete the AWS CloudFormation stacks.
- E. Provide developers with CLI commands so that they can provision their own development environment when necessar
- F. Schedule a nightly Amazon EventBridge (Amazon CloudWatch Events) rule to invoke an AWS Lambda function to terminate all EC2 instances and the DB instance.
- G. Provide developers with CLI commands so that they can provision their own development environment when necessar
- H. Schedule a nightly Amazon EventBridge (Amazon CloudWatch Events) rule to cause AWS CloudFormation to delete all of the development environment resources.

**Answer: B**

**NEW QUESTION 278**

- (Exam Topic 1)

A company is expanding its fleet of Amazon EC2 instances before an expected increase of traffic. When a SysOps administrator attempts to add more instances, an InstanceLimitExceeded error is returned.

What should the SysOps administrator do to resolve this error?

- A. Add an additional CIDR block to the VPC.
- B. Launch the EC2 instances in a different Availability Zone.

- C. Launch new EC2 instances in another VPC.
- D. Use Service Quotas to request an EC2 quota increase.

**Answer:** D

#### NEW QUESTION 281

- (Exam Topic 1)

A company runs an application on an Amazon EC2 instance. A SysOps administrator creates an Auto Scaling group and an Application Load Balancer (ALB) to handle an increase in demand. However, the EC2 instances are failing the health check. What should the SysOps administrator do to troubleshoot this issue?

- A. Verify that the Auto Scaling group is configured to use all AWS Regions.
- B. Verify that the application is running on the protocol and the port that the listener is expecting.
- C. Verify the listener priority in the ALB. Change the priority if necessary.
- D. Verify the maximum number of instances in the Auto Scaling group. Change the number if necessary.

**Answer:** B

#### NEW QUESTION 285

- (Exam Topic 1)

A company hosts an online shopping portal in the AWS Cloud. The portal provides HTTPS security by using a TLS certificate on an Elastic Load Balancer (ELB). Recently, the portal suffered an outage because the TLS certificate expired. A SysOps administrator must create a solution to automatically renew certificates to avoid this issue in the future. What is the MOST operationally efficient solution that meets these requirements?

- A. Request a public certificate by using AWS Certificate Manager (ACM). Associate the certificate from ACM with the ELB.
- B. Write a scheduled AWS Lambda function to renew the certificate every 18 months.
- C. Request a public certificate by using AWS Certificate Manager (ACM). Associate the certificate from ACM with the ELB.
- D. ACM will automatically manage the renewal of the certificate.
- E. Register a certificate with a third-party certificate authority (CA). Import this certificate into AWS Certificate Manager (ACM). Associate the certificate from ACM with the ELB.
- F. ACM will automatically manage the renewal of the certificate.
- G. Register a certificate with a third-party certificate authority (CA). Configure the ELB to import the certificate directly from the CA.
- H. Set the certificate refresh cycle on the ELB to refresh when the certificate is within 3 months of the expiration date.

**Answer:** B

#### Explanation:

"A certificate is eligible for automatic renewal subject to the following considerations: ELIGIBLE if associated with another AWS service, such as Elastic Load Balancing or CloudFront. ELIGIBLE if exported since being issued or last renewed. ELIGIBLE if it is a private certificate issued by calling the ACM RequestCertificate API and then exported or associated with another AWS service. ELIGIBLE if it is a private certificate issued through the management console and then exported or associated with another AWS service." <https://docs.aws.amazon.com/acm/latest/userguide/managed-renewal.html>

#### NEW QUESTION 287

- (Exam Topic 1)

A company has an internal web application that runs on Amazon EC2 instances behind an Application Load Balancer. The instances run in an Amazon EC2 Auto Scaling group in a single Availability Zone. A SysOps administrator must make the application highly available. Which action should the SysOps administrator take to meet this requirement?

- A. Increase the maximum number of instances in the Auto Scaling group to meet the capacity that is required at peak usage.
- B. Increase the minimum number of instances in the Auto Scaling group to meet the capacity that is required at peak usage.
- C. Update the Auto Scaling group to launch new instances in a second Availability Zone in the same AWS Region.
- D. Update the Auto Scaling group to launch new instances in an Availability Zone in a second AWS Region.

**Answer:** C

#### Explanation:

"An Auto Scaling group can contain EC2 instances in one or more Availability Zones within the same Region. However, Auto Scaling groups cannot span multiple Regions". As stated in <https://docs.aws.amazon.com/autoscaling/ec2/userguide/auto-scaling-benefits.htm>

#### NEW QUESTION 288

- (Exam Topic 1)

A company plans to run a public web application on Amazon EC2 instances behind an Elastic Load Balancer (ELB). The company's security team wants to protect the website by using AWS Certificate Manager (ACM) certificates. The ELB must automatically redirect any HTTP requests to HTTPS. Which solution will meet these requirements?

- A. Create an Application Load Balancer that has one HTTPS listener on port 80. Attach an SSL/TLS certificate to listener port 80. Create a rule to redirect requests from HTTP to HTTPS.
- B. Create an Application Load Balancer that has one HTTP listener on port 80 and one HTTPS protocol listener on port 443. Attach an SSL/TLS certificate to listener port 443. Create a rule to redirect requests from port 80 to port 443.
- C. Create an Application Load Balancer that has two TCP listeners on port 80 and port 443. Attach an SSL/TLS certificate to listener port 443. Create a rule to redirect requests from port 80 to port 443.
- D. Create a Network Load Balancer that has two TCP listeners on port 80 and port 443. Attach an SSL/TLS certificate to listener port 443. Create a rule to redirect requests from port 80 to port 443.

**Answer:** B

#### NEW QUESTION 289



- (Exam Topic 1)

A SysOps administrator is tasked with deploying a company's infrastructure as code. The SysOps administrator want to write a single template that can be reused for multiple environments.

How should the SysOps administrator use AWS CloudFormation to create a solution?

- A. Use Amazon EC2 user data in a CloudFormation template
- B. Use nested stacks to provision resources
- C. Use parameters in a CloudFormation template
- D. Use stack policies to provision resources

**Answer: C**

**Explanation:**

Reuse templates to replicate stacks in multiple environments After you have your stacks and resources set up, you can reuse your templates to replicate your infrastructure in multiple environments. For example, you can create environments for development, testing, and production so that you can test changes before implementing them into production. To make templates reusable, use the parameters, mappings, and conditions sections so that you can customize your stacks when you create them. For example, for your development environments, you can specify a lower-cost instance type compared to your production environment, but all other configurations and settings remain the same. <https://docs.aws.amazon.com/AWSCloudFormation/latest/UserGuide/best-practices.html#reuse>

**NEW QUESTION 293**

- (Exam Topic 1)

A company migrated an I/O intensive application to an Amazon EC2 general purpose instance. The EC2 instance has a single General Purpose SSD Amazon Elastic Block Store (Amazon EBS) volume attached.

Application users report that certain actions that require intensive reading and writing to the disk are taking much longer than normal or are failing completely. After reviewing the performance metrics of the EBS volume, a SysOps administrator notices that the VolumeQueueLength metric is consistently high during the same times in which the users are reporting issues. The SysOps administrator needs to resolve this problem to restore full performance to the application.

Which action will meet these requirements?

- A. Modify the instance type to be storage optimized.
- B. Modify the volume properties by deselecting Auto-Enable Volume 10.
- C. Modify the volume properties to increase the IOPS.
- D. Modify the instance to enable enhanced networking.

**Answer: C**

**NEW QUESTION 295**

- (Exam Topic 1)

A SysOps administrator configuring AWS Client VPN to connect use's on a corporate network to AWS resources mat are running in a VPC According to compliance requirements, only traffic that is destined for the VPC can travel across the VPN tunnel.

How should the SysOps administrator configure Client VPN to meet these requirements?

- A. Associate the Client VPN endpoint with a private subnet that has an internet route through a NAT gateway.
- B. On the Client VPN endpoint, turns on the split-tunnel option.
- C. On the Client VPN endpoint, specify DNS server IP addresses
- D. Select a private certificate to use as the identity certificate tor the VPN client.

**Answer: C**

**NEW QUESTION 298**

- (Exam Topic 1)

A company has an Auto Scaling group of Amazon EC2 instances that scale based on average CPU utilization. The Auto Scaling group events log indicates an InsufficientInstanceCapacity error.

Which actions should a SysOps administrator take to remediate this issue? (Select TWO.)

- A. Change the instance type that the company is using.
- B. Configure the Auto Scaling group in different Availability Zones.
- C. Configure the Auto Scaling group to use different Amazon Elastic Block Store (Amazon EBS) volume sizes.
- D. Increase the maximum size of the Auto Scaling group.
- E. Request an increase in the instance service quota.

**Answer: AB**

**NEW QUESTION 300**

- (Exam Topic 1)

A company hosts a website on multiple Amazon EC2 instances that run in an Auto Scaling group. Users are reporting slow responses during peak times between 6 PM and 11 PM every weekend. A SysOps administrator must implement a solution to improve performance during these peak times.

What is the MOST operationally efficient solution that meets these requirements?

- A. Create a scheduled Amazon EventBridge (Amazon CloudWatch Events) rule to invoke an AWS Lambda function to increase the desired capacity before peak times.
- B. Configure a scheduled scaling action with a recurrence option to change the desired capacity before and after peak times.
- C. Create a target tracking scaling policy to add more instances when memory utilization is above 70%.
- D. Configure the cooldown period for the Auto Scaling group to modify desired capacity before and after peak times.

**Answer: B**

**Explanation:**

"Scheduled scaling helps you to set up your own scaling schedule according to predictable load changes. For example, let's say that every week the traffic to your web application starts to increase on Wednesday, remains high on Thursday, and starts to decrease on Friday. You can configure a schedule for Amazon EC2



Auto Scaling to increase capacity on Wednesday and decrease capacity on Friday." [https://docs.aws.amazon.com/autoscaling/ec2/userguide/schedule\\_time.html](https://docs.aws.amazon.com/autoscaling/ec2/userguide/schedule_time.html)

#### NEW QUESTION 301

- (Exam Topic 1)

A compliance learn requites all administrator passwords for Amazon RDS DB instances to be changed at least annually.

Which solution meets this requirement in the MOST operationally efficient manner?

- A. Store the database credentials in AWS Secrets Manage
- B. Configure automatic rotation for the secret every 365 days.
- C. Store the database credentials as a parameter In the RDS parameter grou
- D. Create a database trigger to rotate the password every 365 days.
- E. Store the database credentials in a private Amazon S3 bucke
- F. Schedule an AWS Lambda function to generate a new set of credentials every 365 days.
- G. Store the database credentials in AWS Systems Manager Parameter Store as a secure string parameter. Configure automatic rotation for the parameter every 365 days.

**Answer:** A

#### NEW QUESTION 305

- (Exam Topic 1)

A SysOps administrator needs to give users the ability to upload objects to an Amazon S3 bucket. The SysOps administrator creates a presigned URL and provides the URL to a user, but the user cannot upload an object to the S3 bucket. The presigned URL has not expired, and no bucket policy is applied to the S3 bucket.

Which of the following could be the cause of this problem?

- A. The user has not properly configured the AWS CLI with their access key and secret access key.
- B. The SysOps administrator does not have the necessary permissions to upload the object to the S3 bucket.
- C. The SysOps administrator must apply a bucket policy to the S3 bucket to allow the user to upload the object.
- D. The object already has been uploaded through the use of the presigned URL, so the presigned URL is no longer valid.

**Answer:** B

#### NEW QUESTION 310

- (Exam Topic 1)

An Amazon S3 Inventory report reveals that more than 1 million objects in an S3 bucket are not encrypted These objects must be encrypted, and all future objects must be encrypted at the time they are written

Which combination of actions should a SysOps administrator take to meet these requirements? (Select TWO )

- A. Create an AWS Config rule that runs evaluations against configuration changes to the S3 bucket When an unencrypted object is found run an AWS Systems Manager Automation document to encrypt the object in place
- B. Edit the properties of the S3 bucket to enable default server-side encryption
- C. Filter the S3 Inventory report by using S3 Select to find all objects that are not encrypted Create an S3 Batch Operations job to copy each object in place with en crypton enabled
- D. Filter the S3 Inventory report by using S3 Select to find all objects that are not encrypted Send each object name as a message to an Amazon Simple Queue Service (Amazon SQS) queue Use the SQS queue to invoke an AWS Lambda function to tag each object with a key of "Encryption" and a value of "SSE-KMS"
- E. Use S3 Event Notifications to invoke an AWS Lambda function on all new object-created events for the S3 bucket Configure the Lambda function to check whether the object is encrypted and to run an AWS Systems Manager Automation document to encrypt the object in place when an unencrypted object is found

**Answer:** BC

#### Explanation:

<https://aws.amazon.com/blogs/storage/encrypting-objects-with-amazon-s3-batch-operations/>

#### NEW QUESTION 314

- (Exam Topic 1)

A SysOps administrator is using Amazon EC2 instances to host an application. The SysOps administrator needs to grant permissions for the application to access an Amazon DynamoDB table.

Which solution will meet this requirement?

- A. Create access keys to access the DynamoDB tabl
- B. Assign the access keys to the EC2 instance profile.
- C. Create an EC2 key pair to access the DynamoDB tabl
- D. Assign the key pair to the EC2 instance profile.
- E. Create an IAM user to access the DynamoDB tabl
- F. Assign the IAM user to the EC2 instance profile.
- G. Create an IAM role to access the DynamoDB tabl
- H. Assign the IAM role to the EC2 instance profile.

**Answer:** D

#### NEW QUESTION 315

- (Exam Topic 2)

If your AWS Management Console browser does not show that you are logged in to an AWS account, close the browser and relaunch the console by using the AWS Management Console shortcut from the VM desktop.

If the copy-paste functionality is not working in your environment, refer to the instructions file on the VM desktop and use Ctrl+C, Ctrl+V or Command-C , Command-V.

Configure Amazon EventBridge to meet the following requirements.

\* 1. use the us-east-2 Region for all resources,

- \* 2. Unless specified below, use the default configuration settings.
- \* 3. Use your own resource naming unless a resource name is specified below.
- \* 4. Ensure all Amazon EC2 events in the default event bus are replayable for the past 90 days.
- \* 5. Create a rule named RunFunction to send the exact message every 15 minutes to an existing AWS Lambda function named LogEventFunction.
- \* 6. Create a rule named SpotWarning to send a notification to a new standard Amazon SNS topic named TopicEvents whenever an Amazon EC2 Spot Instance is interrupted. Do NOT create any topic subscriptions. The notification must match the following structure:

Input path:

```
{"instance": "$.detail.instance-id"}
```

Input Path:

{"instance" : "\$.detail.instance-id"}

Input template:

"The EC2 Spot Instance <instance> has been on account."

- A. Mastered
- B. Not Mastered

**Answer:** A

**Explanation:**

Here are the steps to configure Amazon EventBridge to meet the above requirements:

- Log in to the AWS Management Console by using the AWS Management Console shortcut from the VM desktop. Make sure that you are logged in to the desired AWS account.
- Go to the EventBridge service in the us-east-2 Region.
- In the EventBridge service, navigate to the "Event buses" page.
- Click on the "Create event bus" button.
- Give a name to your event bus, and select "default" as the event source type.
- Navigate to "Rules" page and create a new rule named "RunFunction"
- In the "Event pattern" section, select "Schedule" as the event source and set the schedule to run every 15 minutes.
- In the "Actions" section, select "Send to Lambda" and choose the existing AWS Lambda function named "LogEventFunction"
- Create another rule named "SpotWarning"
- In the "Event pattern" section, select "EC2" as the event source, and filter the events on "EC2 Spot Instance interruption"
- In the "Actions" section, select "Send to SNS topic" and create a new standard Amazon SNS topic named "TopicEvents"
- In the "Input Transformer" section, set the Input Path to {"instance" : "\$.detail.instance-id"} and Input template to "The EC2 Spot Instance <instance> has been interrupted on account."
- Now all Amazon EC2 events in the default event bus will be replayable for past 90 days. Note:
- You can use the AWS Management Console, AWS CLI, or SDKs to create and manage EventBridge resources.
- You can use CloudTrail event history to replay events from the past 90 days.
- You can refer to the AWS EventBridge documentation for more information on how to configure and use the service: <https://aws.amazon.com/eventbridge/>

**NEW QUESTION 318**

.....

## Relate Links

**100% Pass Your SOA-C02 Exam with Exam Bible Prep Materials**

<https://www.exambible.com/SOA-C02-exam/>

## Contact us

We are proud of our high-quality customer service, which serves you around the clock 24/7.

Viste - <https://www.exambible.com/>