

Amazon

Exam Questions AWS-Certified-DevOps-Engineer-Professional

Amazon AWS Certified DevOps Engineer Professional



NEW QUESTION 1

You need to perform ad-hoc business analytics queries on well-structured data. Data comes in constantly at a high velocity. Your business intelligence team can understand SQL. What AWS service(s) should you look to first?

- A. Kinesis Firehose + RDS
- B. Kinesis Firehose + RedShift
- C. EMR using Hive
- D. EMR running Apache Spark

Answer: B

Explanation:

Kinesis Firehose provides a managed service for aggregating streaming data and inserting it into RedShift. RedShift also supports ad-hoc queries over well-structured data using a SQL-compliant wire protocol, so the business team should be able to adopt this system easily.

Reference: <https://aws.amazon.com/kinesis/firehose/details/>

NEW QUESTION 2

You need to scale an RDS deployment. You are operating at 10% writes and 90% reads, based on your logging. How best can you scale this in a simple way?

- A. Create a second master RDS instance and peer the RDS groups.
- B. Cache all the database responses on the read side with CloudFront.
- C. Create read replicas for RDS since the load is mostly reads.
- D. Create a Multi-AZ RDS installs and route read traffic to standby

Answer: C

Explanation:

The high-availability feature is not a scaling solution for read-only scenarios; you cannot use a standby replica to serve read traffic. To service read-only traffic, you should use a Read Replica. For more information, see Working with PostgreSQL, MySQL, and MariaDB Read Replicas.

Reference: <http://docs.aws.amazon.com/AmazonRDS/latest/UserGuide/Concepts.MultiAZ.html>

NEW QUESTION 3

When thinking of AWS Elastic Beanstalk, the 'Swap Environment URLs' feature most directly aids in what?

- A. Immutable Rolling Deployments
- B. Mutable Rolling Deployments
- C. Canary Deployments
- D. Blue-Green Deployments

Answer: D

Explanation:

Simply upload the new version of your application and let your deployment service (AWS Elastic Beanstalk, AWS CloudFormation, or AWS OpsWorks) deploy a new version (green). To cut over to the new version, you simply replace the ELB URLs in your DNS records. Elastic Beanstalk has a Swap Environment URLs feature to facilitate a simpler cutover process.

Reference: <https://d0.awsstatic.com/whitepapers/overview-of-deployment-options-on-aws.pdf>

NEW QUESTION 4

You are designing a service that aggregates clickstream data in batch and delivers reports to subscribers via email only once per week. Data is extremely spikey, geographically distributed, high-scale, and unpredictable. How should you design this system?

- A. Use a large RedShift cluster to perform the analysis, and a fleet of Lambdas to perform record inserts into the RedShift table
- B. Lambda will scale rapidly enough for the traffic spikes.
- C. Use a CloudFront distribution with access log delivery to S3. Clicks should be recorded as querystring GETs to the distribution
- D. Reports are built and sent by periodically running EMR jobs over the access logs in S3.
- E. Use API Gateway invoking Lambdas which PutRecords into Kinesis, and EMR running Spark performing GetRecords on Kinesis to scale with spike
- F. Spark on EMR outputs the analysis to S3, which are sent out via email.
- G. Use AWS Elasticsearch service and EC2 Auto Scaling group
- H. The Autoscaling groups scale based on click throughput and stream into the Elasticsearch domain, which is also scalable
- I. Use Kibana to generate reports periodically.

Answer: B

Explanation:

Because you only need to batch analyze, anything using streaming is a waste of money. CloudFront is a Gigabit-Scale HTTP(S) global request distribution service, so it can handle scale, geo-spread, spikes, and unpredictability. The Access Logs will contain the GET data and work just fine for batch analysis and email using EMR.

Can I use Amazon CloudFront if I expect usage peaks higher than 10 Gbps or 15,000 RPS? Yes. Complete our request for higher limits here, and we will add more capacity to your account within two business days.

Reference: <https://aws.amazon.com/Cloudfront/faqs/>

NEW QUESTION 5

Your system automatically provisions EIPs to EC2 instances in a VPC on boot. The system provisions the whole VPC and stack at once. You have two of them per VPC. On your new AWS account, your attempt to create a Development environment failed, after successfully creating Staging and Production environments in the same region. What happened?

- A. You didn't choose the Development version of the AMI you are using.

- B. You didn't set the Development flag to true when deploying EC2 instances.
- C. You hit the soft limit of 5 EIPs per region and requested a 6th.
- D. You hit the soft limit of 2 VPCs per region and requested a 3rd.

Answer: C

Explanation:

There is a soft limit of 5 EIPs per Region for VPC on new accounts. The third environment could not allocate the 6th EIP.
Reference: http://docs.aws.amazon.com/general/latest/gr/aws_service_limits.html#limits_vpc

NEW QUESTION 6

You are building out a layer in a software stack on AWS that needs to be able to scale out to react to increased demand as fast as possible. You are running the code on EC2 instances in an Auto Scaling Group behind an ELB. Which application code deployment method should you use?

- A. SSH into new instances that come online, and deploy new code onto the system by pulling it from an S3 bucket, which is populated by code that you refresh from source control on new pushes.
- B. Bake an AMI when deploying new versions of code, and use that AMI for the Auto Scaling Launch Configuration.
- C. Create a Dockerfile when preparing to deploy a new version to production and publish it to S3. Use UserData in the Auto Scaling Launch configuration to pull down the Dockerfile from S3 and run it when new instances launch.
- D. Create a new Auto Scaling Launch Configuration with UserData scripts configured to pull the latest code at all times.

Answer: B

Explanation:

the bootstrapping process can be slower if you have a complex application or multiple applications to install. Managing a fleet of applications with several build tools and dependencies can be a challenging task during rollouts. Furthermore, your deployment service should be designed to do faster rollouts to take advantage of Auto Scaling.

Reference: <https://d0.awsstatic.com/whitepapers/overview-of-deployment-options-on-aws.pdf>

NEW QUESTION 7

When thinking of DynamoDB, what are true of Local Secondary Key properties?

- A. Either the partition key or the sort key can be different from the table, but not both.
- B. Only the sort key can be different from the table.
- C. The partition key and sort key can be different from the table.
- D. Only the partition key can be different from the table.

Answer: B

Explanation:

Global secondary index — an index with a partition key and a sort key that can be different from those on the table. A global secondary index is considered "global" because queries on the index can span all of the data in a table, across all partitions.

Reference: <http://docs.aws.amazon.com/amazondynamodb/latest/developerguide/SecondaryIndexes.html>

NEW QUESTION 8

Which major database needs a BYO license?

- A. PostgreSQL
- B. MariaDB
- C. MySQL
- D. Oracle

Answer: D

Explanation:

Oracle is not open source, and requires a bring your own license model.

Reference: http://docs.aws.amazon.com/AmazonRDS/latest/UserGuide/CHAP_Oracle.html

NEW QUESTION 9

What is the maximum supported single-volume throughput on EBS?

- A. 320 MiB/s
- B. 160 MiB/s
- C. 40 MiB/s
- D. 640 MiB/s

Answer: A

Explanation:

The ceiling throughput for PIOPS on EBS is 320 MiB/s.

Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/EBSVolumeTypes.html>

NEW QUESTION 10

You need to know when you spend \$1000 or more on AWS. What's the easy way for you to see that notification?

- A. AWS CloudWatch Events tied to API calls, when certain thresholds are exceeded, publish to SNS.
- B. Scrape the billing page periodically and pump into Kinesis.

- C. AWS CloudWatch Metrics + Billing Alarm + Lambda event subscription
- D. When a threshold is exceeded, email the manager.
- E. Scrape the billing page periodically and publish to SNS

Answer: C

Explanation:

Even if you're careful to stay within the free tier, it's a good idea to create a billing alarm to notify you if you exceed the limits of the free tier. Billing alarms can help to protect you against unknowingly accruing charges if you inadvertently use a service outside of the free tier or if traffic exceeds your expectations. Reference: <http://docs.aws.amazon.com/awsaccountbilling/latest/aboutv2/free-tier-alarms.html>

NEW QUESTION 10

You are experiencing performance issues writing to a DynamoDB table. Your system tracks high scores for video games on a marketplace. Your most popular game experiences all of the performance issues. What is the most likely problem?

- A. DynamoDB's vector clock is out of sync, because of the rapid growth in request for the most popular game.
- B. You selected the Game ID or equivalent identifier as the primary partition key for the table.
- C. Users of the most popular video game each perform more read and write requests than average.
- D. You did not provision enough read or write throughput to the table

Answer: B

Explanation:

The primary key selection dramatically affects performance consistency when reading or writing to DynamoDB. By selecting a key that is tied to the identity of the game, you forced DynamoDB to create a hotspot in the table partitions, and over-request against the primary key partition for the popular game. When it stores data, DynamoDB divides a table's items into multiple partitions, and distributes the data primarily based upon the partition key value. The provisioned throughput associated with a table is also divided evenly among the partitions, with no sharing of provisioned throughput across partitions. Reference: <http://docs.aws.amazon.com/amazondynamodb/latest/developerguide/GuidelinesForTables.html#GuidelinesForTables.UniformWorkload>

NEW QUESTION 15

You meet once per month with your operations team to review the past month's data. During the meeting, you realize that 3 weeks ago, your monitoring system which pings over HTTP from outside AWS recorded a large spike in latency on your 3-tier web service API.

You use DynamoDB for the database layer, ELB, EBS, and EC2 for the business logic tier, and SQS, ELB, and EC2 for the presentation layer.

Which of the following techniques will NOT help you figure out what happened?

- A. Check your CloudTrail log history around the spike's time for any API calls that caused slowness.
- B. Review CloudWatch Metrics graphs to determine which component(s) slowed the system down.
- C. Review your ELB access logs in S3 to see if any ELBs in your system saw the latency.
- D. Analyze your logs to detect bursts in traffic at that time

Answer: B

Explanation:

Metrics data are available for 2 weeks. If you want to store metrics data beyond that duration, you can retrieve it using our GetMetricStatistics API as well as a number of applications and tools offered by AWS partners.

Reference: <https://aws.amazon.com/cloudwatch/faqs/>

NEW QUESTION 18

For AWS CloudFormation, which is true?

- A. Custom resources using SNS have a default timeout of 3 minutes.
- B. Custom resources using SNS do not need a `ServiceToken` property.
- C. Custom resources using Lambda and `Code.ZipFile` allow inline nodejs resource composition.
- D. Custom resources using Lambda do not need a `ServiceToken` property

Answer: C

Explanation:

Code is a property of the `AWS::Lambda::Function` resource that enables you to specify the source code of an AWS Lambda (Lambda) function. You can point to a file in an Amazon Simple Storage Service (Amazon S3) bucket or specify your source code as inline text (for nodejs runtime environments only). Reference:

<http://docs.aws.amazon.com/AWSCloudFormation/latest/UserGuide/template-custom-resources.html>

NEW QUESTION 22

You need to deploy an AWS stack in a repeatable manner across multiple environments. You have selected CloudFormation as the right tool to accomplish this, but have found that there is a resource type you need to create and model, but is unsupported by CloudFormation. How should you overcome this challenge?

- A. Use a CloudFormation Custom Resource Template by selecting an API call to proxy for create, update, and delete action
- B. CloudFormation will use the AWS SDK, CLI, or API method of your choosing as the state transition function for the resource type you are modeling.
- C. Submit a ticket to the AWS Forum
- D. AWS extends CloudFormation Resource Types by releasing tooling to the AWS Labs organization on GitHub
- E. Their response time is usually 1 day, and they complete requests within a week or two.
- F. Instead of depending on CloudFormation, use Chef, Puppet, or Ansible to author Heat templates, which are declarative stack resource definitions that operate over the OpenStack hypervisor and cloud environment.
- G. Create a CloudFormation Custom Resource Type by implementing create, update, and delete functionality, either by subscribing a Custom Resource Provider to an SNS topic, or by implementing the logic in AWS Lambda.

Answer: D

Explanation:

Custom resources provide a way for you to write custom provisioning logic in AWS CloudFormation template and have AWS CloudFormation run it during a stack operation, such as when you create, update or delete a stack. For more information, see Custom Resources.

Reference:

<http://docs.aws.amazon.com/AWSCloudFormation/latest/UserGuide/template-custom-resources.html>

NEW QUESTION 23

You run a 2000-engineer organization. You are about to begin using AWS at a large scale for the first time. You want to integrate with your existing identity management system running on Microsoft Active Directory, because your organization is a power-user of Active Directory. How should you manage your AWS identities in the most simple manner?

- A. Use a large AWS Directory Service Simple AD.
- B. Use a large AWS Directory Service AD Connector.
- C. Use an Sync Domain running on AWS Directory Service.
- D. Use an AWS Directory Sync Domain running on AWS Lambda

Answer: B

Explanation:

You must use AD Connector as a power-user of Microsoft Active Directory. Simple AD only works with a subset of AD functionality. Sync Domains do not exist; they are made up answers.

AD Connector is a directory gateway that allows you to proxy directory requests to your on-premises Microsoft Active Directory, without caching any information in the cloud. AD Connector comes in 2 sizes; small and large. A small AD Connector is designed for smaller organizations of up to 500 users. A large AD Connector is designed for larger organizations of up to 5,000 users.

Reference: <https://aws.amazon.com/directoryservice/details/>

NEW QUESTION 24

Your team wants to begin practicing continuous delivery using CloudFormation, to enable automated builds and deploys of whole, versioned stacks or stack layers. You have a 3-tier, mission-critical system. Which of the following is NOT a best practice for using CloudFormation in a continuous delivery environment?

- A. Use the AWS CloudFormation `ValidateTemplate` call before publishing changes to AWS.
- B. Model your stack in one template, so you can leverage CloudFormation's state management and dependency resolution to propagate all changes.
- C. Use CloudFormation to create brand new infrastructure for all stateless resources on each push, and run integration tests on that set of infrastructure.
- D. Parametrize the template and use `Mappings` to ensure your template works in multiple Regions.

Answer: B

Explanation:

Putting all resources in one stack is a bad idea, since different tiers have different life cycles and frequencies of change. For additional guidance about organizing your stacks, you can use two common frameworks: a multi-layered architecture and service-oriented architecture (SOA).

Reference:

<http://docs.aws.amazon.com/AWSCloudFormation/latest/UserGuide/best-practices.html#organizingstack>

NEW QUESTION 28

What is the scope of AWS IAM?

- A. Global
- B. Availability Zone
- C. Region
- D. Placement Group

Answer: A

Explanation:

IAM resources are all global; there is not regional constraint. Reference: <https://aws.amazon.com/iam/faqs/>

NEW QUESTION 30

You are building a mobile app for consumers to post cat pictures online. You will be storing the images in AWS S3. You want to run the system very cheaply and simply. Which one of these options allows you to build a photo sharing application without needing to worry about scaling expensive uploads processes, authentication/authorization and so forth?

- A. Build the application out using AWS Cognito and web identity federation to allow users to log in using Facebook or Google Account
- B. Once they are logged in, the secret token passed to that user is used to directly access resources on AWS, like AWS S3.
- C. Use JWT or SANIL compliant systems to build authorization policies
- D. Users log in with a username and password, and are given a token they can use indefinitely to make calls against the photo infrastructure.
- E. Use AWS API Gateway with a constantly rotating API Key to allow access from the client-side
- F. Construct a custom build of the SDK and include S3 access in it.
- G. Create an AWS OAuth Service Domain and grant public signup and access to the domain
- H. During setup, add at least one major social media site as a trusted Identity Provider for users.

Answer: A

Explanation:

The short answer is that Amazon Cognito is a superset of the functionality provided by web identity federation. It supports the same providers, and you configure your app and authenticate with those providers in the same way. But Amazon Cognito includes a variety of additional features. For example, it enables your users to start using the app as a guest user and later sign in using one of the supported identity providers.

Reference:

<https://blogs.aws.amazon.com/security/post/Tx3SYCORF5EKRCO/How-Does-Amazon-Cognito-Relate-to-Existing-Web-Identity-Federation>

NEW QUESTION 31

Your CTO has asked you to make sure that you know what all users of your AWS account are doing to change resources at all times. She wants a report of who is doing what over time, reported to her once per week, for as broad a resource type group as possible. How should you do this?

- A. Create a global AWS CloudTrail Trail
- B. Configure a script to aggregate the log data delivered to S3 once per week and deliver this to the CTO.
- C. Use CloudWatch Events Rules with an SNS topic subscribed to all AWS API call
- D. Subscribe the CTO to an email type delivery on this SNS Topic.
- E. Use AWS IAM credential reports to deliver a CSV of all uses of IAM User Tokens over time to the CTO.
- F. Use AWS Config with an SNS subscription on a Lambda, and insert these changes over time into a DynamoDB table
- G. Generate reports based on the contents of this table.

Answer: A

Explanation:

This is the ideal use case for AWS CloudTrail.

CloudTrail provides visibility into user activity by recording API calls made on your account. CloudTrail records important information about each API call, including the name of the API, the identity of the caller, the time of the API call, the request parameters, and the response elements returned by the AWS service. This information helps you to track changes made to your AWS resources and to troubleshoot operational issues. CloudTrail makes it easier to ensure compliance with internal policies and regulatory standards. Reference: <https://aws.amazon.com/Cloudtrail/faqs/>

NEW QUESTION 35

What is required to achieve gigabit network throughput on EC2? You already selected cluster-compute, 10GB instances with enhanced networking, and your workload is already network-bound, but you are not seeing 10 gigabit speeds.

- A. Enable biphase networking on your servers, so packets are non-blocking in both directions and there's no switching overhead.
- B. Ensure the instances are in different VPCs so you don't saturate the Internet Gateway on any one VPC.
- C. Select PIOPS for your drives and mount several, so you can provision sufficient disk throughput.
- D. Use a placement group for your instances so the instances are physically near each other in the same Availability Zone.

Answer: D

Explanation:

You are not guaranteed 10 gigabit performance, except within a placement group.

A placement group is a logical grouping of instances within a single Availability Zone. Using placement groups enables applications to participate in a low-latency, 10 Gbps network. Placement groups are recommended for applications that benefit from low network latency, high network throughput, or both. Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/placement-groups.html>

NEW QUESTION 40

If I want CloudFormation stack status updates to show up in a continuous delivery system in as close to real time as possible, how should I achieve this?

- A. Use a long-poll on the Resources object in your CloudFormation stack and display those state changes in the UI for the system.
- B. Use a long-poll on the `ListStacks` API call for your CloudFormation stack and display those state changes in the UI for the system.
- C. Subscribe your continuous delivery system to an SNS topic that you also tell your CloudFormation stack to publish events into.
- D. Subscribe your continuous delivery system to an SQS queue that you also tell your CloudFormation stack to publish events into.

Answer: C

Explanation:

Use NotificationARNs.member.N when making a CreateStack call to push stack events into SNS in nearly real-time.

Reference:

<http://docs.aws.amazon.com/AWSCloudFormation/latest/UserGuide/using-cfn-updating-stacks-monitor-stack.html>

NEW QUESTION 44

Which of these configuration or deployment practices is a security risk for RDS?

- A. Storing SQL function code in plaintext
- B. Non-Multi-AZ RDS instance
- C. Having RDS and EC2 instances exist in the same subnet
- D. RDS in a public subnet

Answer: D

Explanation:

Making RDS accessible to the public internet in a public subnet poses a security risk, by making your database directly addressable and spammable.

DB instances deployed within a VPC can be configured to be accessible from the Internet or from EC2 instances outside the VPC. If a VPC security group specifies a port access such as TCP port 22, you would not be able to access the DB instance because the firewall for the DB instance provides access only via the IP addresses specified by the DB security groups the instance is a member of and the port defined when the DB instance was created.

Reference: <http://docs.aws.amazon.com/AmazonRDS/latest/UserGuide/Overview.RDSSecurityGroups.html>

NEW QUESTION 45

Which of these is not a reason a Multi-AZ RDS instance will failover?

- A. An Availability Zone outage
- B. A manual failover of the DB instance was initiated using Reboot with failover
- C. To autoscale to a higher instance class
- D. The primary DB instance fails

Answer:

C

Explanation:

The primary DB instance switches over automatically to the standby replica if any of the > following conditions occur: An Availability Zone outage, the primary DB instance fails, the DB instance's server type is changed, the operating system of the DB instance is, undergoing software patching, a manual failover of the DB instance was initiated using Reboot with failover

Reference: <http://docs.aws.amazon.com/AmazonRDS/latest/UserGuide/Concepts.MultiAZ.html>

NEW QUESTION 47

You need to create an audit log of all changes to customer banking data. You use DynamoDB to store this customer banking data. It's important not to lose any information due to server failures. What is an elegant way to accomplish this?

- A. Use a DynamoDB StreamSpecification and stream all changes to AWS Lambda
- B. Log the changes to AWS CloudWatch Logs, removing sensitive information before logging.
- C. Before writing to DynamoDB, do a pre-write acknowledgment to disk on the application server, removing sensitive information before logging
- D. Periodically rotate these log files into S3.
- E. Use a DynamoDB StreamSpecification and periodically flush to an EC2 instance store, removing sensitive information before putting the object
- F. Periodically flush these batches to S3.
- G. Before writing to DynamoDB, do a pre-write acknowledgment to disk on the application server, removing sensitive information before logging
- H. Periodically pipe these files into CloudWatch Logs.

Answer: A

Explanation:

All suggested periodic options are sensitive to server failure during or between periodic flushes. Streaming to Lambda and then logging to CloudWatch Logs will make the system resilient to instance and Availability Zone failures.

Reference: <http://docs.aws.amazon.com/lambda/latest/dg/with-ddb.html>

NEW QUESTION 51

You need your API backed by DynamoDB to stay online during a total regional AWS failure. You can tolerate a couple minutes of lag or slowness during a large failure event, but the system should recover with normal operation after those few minutes. What is a good approach?

- A. Set up DynamoDB cross-region replication in a master-standby configuration, with a single standby in another region
- B. Create an Auto Scaling Group behind an ELB in each of the two regions DynamoDB is running in
- C. Add a Route53 Latency DNS Record with DNS Failover, using the ELBs in the two regions as the resource records.
- D. Set up a DynamoDB Multi-Region table
- E. Create an Auto Scaling Group behind an ELB in each of the two regions DynamoDB is running in
- F. Add a Route53 Latency DNS Record with DNS Failover, using the ELBs in the two regions as the resource records.
- G. Set up a DynamoDB Multi-Region table
- H. Create a cross-region ELB pointing to a cross-region Auto Scaling Group, and direct a Route53 Latency DNS Record with DNS Failover to the cross-region ELB.
- I. Set up DynamoDB cross-region replication in a master-standby configuration, with a single standby in another region
- J. Create a cross-region ELB pointing to a cross-region Auto Scaling Group, and direct a Route53 Latency DNS Record with DNS Failover to the cross-region ELB.

Answer: A

Explanation:

There is no such thing as a cross-region ELB, nor such thing as a cross-region Auto Scaling Group, nor such thing as a DynamoDB Multi-Region Table. The only option that makes sense is the cross-regional replication version with two ELBs and ASGs with Route53 Failover and Latency DNS.

Reference: <http://docs.aws.amazon.com/amazondynamodb/latest/developerguide/Streams.CrossRegionRepl.html>

NEW QUESTION 56

Your company wants to understand where cost is coming from in the company's production AWS account. There are a number of applications and services running at any given time. Without expending too much initial development time, how best can you give the business a good understanding of which applications cost the most per month to operate?

- A. Create an automation script which periodically creates AWS Support tickets requesting detailed intra-month information about your bill.
- B. Use custom CloudWatch Metrics in your system, and put a metric data point whenever cost is incurred.
- C. Use AWS Cost Allocation Tagging for all resources which support it
- D. Use the Cost Explorer to analyze costs throughout the month.
- E. Use the AWS Price API and constantly running resource inventory scripts to calculate total price based on multiplication of consumed resources over time.

Answer: C

Explanation:

Cost Allocation Tagging is a built-in feature of AWS, and when coupled with the Cost Explorer, provides a simple and robust way to track expenses.

You can also use tags to filter views in Cost Explorer. Note that before you can filter views by tags in Cost Explorer, you must have applied tags to your resources and activate them, as described in the following sections. For more information about Cost Explorer, see Analyzing Your Costs with Cost Explorer. Reference:

<http://docs.aws.amazon.com/awsaccountbilling/latest/aboutv2/cost-alloc-tags.html>

NEW QUESTION 58

What is a circular dependency in AWS CloudFormation?

- A. When a Template references an earlier version of itself.
- B. When Nested Stacks depend on each other.
- C. When Resources form a DependOn loop.
- D. When a Template references a region, which references the original Template

Answer: C

Explanation:

To resolve a dependency error, add a DependsOn attribute to resources that depend on other resources in your template. In some cases, you must explicitly declare dependencies so that AWS CloudFormation can create or delete resources in the correct order. For example, if you create an Elastic IP and a VPC with an Internet gateway in the same stack, the Elastic IP must depend on the Internet gateway attachment. For additional information, see DependsOn Attribute. Reference: <http://docs.aws.amazon.com/AWSCloudFormation/latest/UserGuide/troubleshooting.html#troubleshooting-g-errors-dependence-error>

NEW QUESTION 60

You work for a company that automatically tags photographs using artificial neural networks (ANNs), which run on GPUs using C++. You receive millions of images at a time, but only 3 times per day on average. These images are loaded into an AWS S3 bucket you control for you in a batch, and then the customer publishes a JSON-formatted manifest into another S3 bucket you control as well. Each image takes 10 milliseconds to process using a full GPU. Your neural network software requires 5 minutes to bootstrap. Image tags are JSON objects, and you must publish them to an S3 bucket. Which of these is the best system architectures for this system?

- A. Create an OpsWorks Stack with two Layer
- B. The first contains lifecycle scripts for launching and bootstrapping an HTTP API on G2 instances for ANN image processing, and the second has an always-on instance which monitors the S3 manifest bucket for new file
- C. When a new file is detected, request instances to boot on the ANN layer
- D. When the instances are booted and the HTTP APIs are up, submit processing requests to indM dual instances.
- E. Make an S3 notification configuration which publishes to AWS Lambda on the manifest bucket
- F. Make the Lambda create a CloudFormation Stack which contains the logic to construct an autoscaling worker tier of EC2 G2 instances with the ANN code on each instance
- G. Create an SQS queue of the images in the manifest
- H. Tear the stack down when the queue is empty.
- I. Deploy your ANN code to AWS Lambda as a bundled binary for the C++ extension
- J. Make an S3 notification configuration on the manifest, which publishes to another AWS Lambda running controller code
- K. This controller code publishes all the images in the manifest to AWS Kinesis
- L. Your ANN code Lambda Function uses the Kinesis as an Event Source
- M. The system automatically scales when the stream contains image events.
- N. Create an Auto Scaling, Load Balanced Elastic Beanstalk worker tier Application and Environment
- O. Deploy the ANN code to G2 instances in this tier
- P. Set the desired capacity to 1. Make the code periodically check S3 for new manifest
- Q. When a new manifest is detected, push all of the images in the manifest into the SQS queue associated with the Elastic Beanstalk worker tier.

Answer: B

Explanation:

The Elastic Beanstalk option is incorrect because it requires a constantly-polling instance, which may break and costs money.

The Lambda fleet option is incorrect because AWS Lambda does not support GPU usage.

The OpsWorks stack option both requires a constantly-polling instance, and also requires complex timing and capacity planning logic.

The CloudFormation option requires no polling, has no always-on instances, and allows arbitrarily fast processing by simply setting the instance count as high as needed.

Reference: <http://docs.aws.amazon.com/lambda/latest/dg/current-supported-versions.html>

NEW QUESTION 65

You were just hired as a DevOps Engineer for a startup. Your startup uses AWS for 100% of their infrastructure. They currently have no automation at all for deployment, and they have had many failures while trying to deploy to production. The company has told you deployment process risk mitigation is the most important thing now, and you have a lot of budget for tools and AWS resources.

Their stack: 2-tier API

Data stored in DynamoDB or S3, depending on type. Compute layer is EC2 in Auto Scaling Groups. They use Route53 for DNS pointing to an ELB.

An ELB balances load across the EC2 instances.

The scaling group properly varies between 4 and 12 EC2 instances.

Which of the following approaches, given this company's stack and their priorities, best meets the company's needs?

- A. Model the stack in AWS Elastic Beanstalk as a single Application with multiple Environments
- B. Use Elastic Beanstalk's Rolling Deploy option to progressively roll out application code changes when promoting across environments.
- C. Model the stack in 3 CloudFormation templates: Data layer, compute layer, and networking layer
- D. Write stack deployment and integration testing automation following Blue-Green methodologies.
- E. Model the stack in AWS OpsWorks as a single Stack, with 1 compute layer and its associated ELB
- F. Use Chef and App Deployments to automate Rolling Deployment.
- G. Model the stack in 1 CloudFormation template, to ensure consistency and dependency graph resolution
- H. Write deployment and integration testing automation following Rolling Deployment methodologies.

Answer: B

Explanation:

AWS recommends Blue-Green for zero-downtime deploys. Since you use DynamoDB, and neither AWS OpsWorks nor AWS Elastic Beanstalk directly supports DynamoDB, the option selecting CloudFormation and Blue-Green is correct.

You use various strategies to migrate the traffic from your current application stack (blue) to a new version of the application (green). This is a popular technique for deploying applications with zero downtime. The deployment services like AWS Elastic Beanstalk, AWS CloudFormation, or AWS OpsWorks are particularly useful as they provide a simple way to clone your running application stack. You can set up a new version of your application (green) by simply cloning the current version of the application (blue). Reference: <https://d0.awsstatic.com/whitepapers/overview-of-deployment-options-on-aws.pdf>

NEW QUESTION 66

Your company needs to automate 3 layers of a large cloud deployment. You want to be able to track this deployment's evolution as it changes over time, and carefully control any alterations. What is a good way to automate a stack to meet these requirements?

- A. Use OpsWorks Stacks with three layers to model the layering in your stack.

- B. Use CloudFormation Nested Stack Templates, with three child stacks to represent the three logical layers of your cloud.
- C. Use AWS Config to declare a configuration set that AWS should roll out to your cloud.
- D. Use Elastic Beanstalk Linked Applications, passing the important DNS entries between layers using the metadata interface.

Answer: B

Explanation:

Only CloudFormation allows source controlled, declarative templates as the basis for stack automation. Nested Stacks help achieve clean separation of layers while simultaneously providing a method to control all layers at once when needed.

Reference:

<https://blogs.aws.amazon.com/application-management/post/TxIT9JYOOS8AB9I/Use-Nested-Stacks-to-Create-Reusable-Templates-and-Support-Role-Specialization>

NEW QUESTION 71

You need the absolute highest possible network performance for a cluster computing application. You already selected homogeneous instance types supporting 10 gigabit enhanced networking, made sure that your workload was network bound, and put the instances in a placement group. What is the last optimization you can make?

- A. Use 9001 MTU instead of 1500 for Jumbo Frames, to raise packet body to packet overhead ratios.
- B. Segregate the instances into different peered VPCs while keeping them all in a placement group, so each one has its own Internet Gateway.
- C. Bake an AMI for the instances and relaunch, so the instances are fresh in the placement group and don't have noisy neighbors.
- D. Turn off SYN/ACK on your TCP stack or begin using UDP for higher throughput

Answer: A

Explanation:

For instances that are colocated inside a placement group, jumbo frames help to achieve the maximum network throughput possible, and they are recommended in this case. For more information, see Placement Groups.

Reference: http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/network_mtu.html#jumbo_frame_instances

NEW QUESTION 75

If you're trying to configure an AWS Elastic Beanstalk worker tier for easy debugging if there are problems finishing queue jobs, what should you configure?

- A. Configure Rolling Deployments.
- B. Configure Enhanced Health Reporting
- C. Configure Blue-Green Deployments.
- D. Configure a Dead Letter Queue

Answer: D

Explanation:

Elastic Beanstalk worker environments support Amazon Simple Queue Service (SQS) dead letter queues. A dead letter queue is a queue where other (source) queues can send messages that for some reason could not be successfully processed. A primary benefit of using a dead letter queue is the ability to sideline and isolate the unsuccessfully processed messages. You can then analyze any messages sent

to the dead letter queue to try to determine why they were not successfully processed. Reference:

<http://docs.aws.amazon.com/elasticbeanstalk/latest/dg/using-features-managing-env-tiers.html#worker-deadletter>

NEW QUESTION 78

.....

Thank You for Trying Our Product

We offer two products:

1st - We have Practice Tests Software with Actual Exam Questions

2nd - Questions and Answers in PDF Format

AWS-Certified-DevOps-Engineer-Professional Practice Exam Features:

- * AWS-Certified-DevOps-Engineer-Professional Questions and Answers Updated Frequently
- * AWS-Certified-DevOps-Engineer-Professional Practice Questions Verified by Expert Senior Certified Staff
- * AWS-Certified-DevOps-Engineer-Professional Most Realistic Questions that Guarantee you a Pass on Your First Try
- * AWS-Certified-DevOps-Engineer-Professional Practice Test Questions in Multiple Choice Formats and Updates for 1 Year

100% Actual & Verified — Instant Download, Please Click
[Order The AWS-Certified-DevOps-Engineer-Professional Practice Test Here](#)